

Electronic housing - HCS-T MINI C C C C 7035 - 2203130

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Handheld housing, T-Mini, light gray, front level closed, consisting of two half shells with screws

Why buy this product

- Item is from the HCS product range
- Suitable for handheld devices
- Ergonomic straight or staggered housing design
- Integration of LCD displays and membrane keypads
- Degree of protection: up to IP54
- Temperature range: -20 °C to +50 °C
- Shock-resistant ABS plastic
- Flammability rating UL 94-V0



Key Commercial Data

Packing unit	1 STK
GTIN	
GTIN	4055626376868

Technical data

Item properties

Type	HCS-T MINI C C C C 7035
Order No.	2203130
Type	stepped
Housing type	Complete housing
Battery compartment	no

Measurements

Caption	Schematic representation – for additional information, see product range drawing in the Download Center
---------	---

Electronic housing - HCS-T MINI C C C C 7035 - 2203130

Technical data

Measurements

Width [w]	85 mm
Height [h]	182.5 mm
Depth [d]	30 mm

Material specifications

Housing material	ABS
Color (RAL)	light gray (7035)

Ambient conditions


Ambient temperature (storage/transport)	-40 °C ... 55 °C
Ambient temperature (assembly)	-5 °C ... 80 °C
Ambient temperature (operation)	-40 °C ... 80 °C

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Drawings

Dimensional drawing



Schematic representation – for additional information, see product range drawing in the Download Center

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>