


# BC636...BC640



## PNP Silicon Epitaxial Planar Transistor

Medium Power Transistors  
for audio and video amplifiers



1. Emitter 2. Collector 3. Base  
TO-92 Plastic Package

### Absolute Maximum Ratings ( $T_a = 25\text{ }^\circ\text{C}$ )

Parameter	Symbol	Value	Unit
Collector Base Voltage	BC636	45	V
	BC638	60	
	BC640	100	
Collector Emitter Voltage	BC636	45	V
	BC638	60	
	BC640	80	
Emitter Base Voltage	$-V_{EBO}$	5	V
Collector Current	$-I_C$	1	A
Peak Collector Current	$-I_{CM}$	1.5	A
Base Current	$-I_B$	100	mA
Peak Base Current	$-I_{BM}$	200	mA
Power Dissipation	$P_{tot}$	830	mW
Junction Temperature	$T_j$	150	$^\circ\text{C}$
Storage Temperature Range	$T_{stg}$	- 65 to + 150	$^\circ\text{C}$



Characteristics at  $T_a = 25\text{ }^\circ\text{C}$

Parameter	Symbol	Min.	Max.	Unit	
DC Current Gain at $-V_{CE} = 2\text{ V}$ , $-I_C = 5\text{ mA}$ at $-V_{CE} = 2\text{ V}$ , $-I_C = 150\text{ mA}$ at $-V_{CE} = 2\text{ V}$ , $-I_C = 500\text{ mA}$	Current Gain Group -10 -16	$h_{FE}$	40	-	-
		$h_{FE}$	63	160	-
		$h_{FE}$	100	250	-
		$h_{FE}$	25	-	-
Collector Base Cutoff Current at $-V_{CB} = 30\text{ V}$	$-I_{CBO}$	-	100	nA	
Emitter Base Cutoff Current at $V_{EB} = 5\text{ V}$	$-I_{EBO}$	-	100	nA	
Collector Base Breakdown Voltage at $-I_C = 100\text{ }\mu\text{A}$	BC636 BC638 BC640 $-V_{(BR)CBO}$	45 60 100	- - -	V	
Collector Emitter Breakdown Voltage at $-I_C = 10\text{ mA}$	BC636 BC638 BC640 $-V_{(BR)CEO}$	45 60 80	- - -	V	
Emitter Base Breakdown Voltage at $-I_E = 10\text{ }\mu\text{A}$	$-V_{(BR)EBO}$	5	-	V	
Collector Emitter Saturation Voltage at $-I_C = 500\text{ mA}$ , $-I_B = 50\text{ mA}$	$-V_{CE(sat)}$	-	0.5	V	
Base Emitter Voltage at $-V_{CE} = 2\text{ V}$ , $-I_C = 500\text{ mA}$	$-V_{BE}$	-	1	V	
Gain Bandwidth Product at $-V_{CE} = 5\text{ V}$ , $-I_C = 50\text{ mA}$ , $f = 100\text{ MHz}$	$f_T$	100	-	MHz	

