


Two Terminals SMD Switching Diode

Features

- Low Forward Voltage
- Fast Reverse Recovery Time
- Small Total Capacitance
- RoHS Compliant



SOD-523

Mechanical Data

Case:	SOD-523, Plastic Case
Terminals:	Solderable per MIL-STD-750, Method 2026
Polarity:	Color band denotes cathode end
Weight:	Approx. 0.0016 gram

Maximum Ratings *(T_{Ambient}=25°C unless noted otherwise)*

Symbol	Description	TWD160WT	Unit	Conditions
	Marking Code	UF		
VRM	Reverse Voltage	80	V	
VRRM	Peak Reverse Voltage	85	V	
IFM	Max. Peak Forward Current	300	mA	
IF(AV)	Max. Forward Average Current at T _A =25° C	100	mA	
IFSM	Peak Forward Surge Current, Pulse Width=1.0us	2.0	A	
PD	Power Dissipation Derate above 25°C	-	mW	
TJ	Junction Temperature	150	° C	
TSTG	Storage Temperature Range	-55 to +150	° C	

Two Terminals SMD Switching Diode

TWD160WT

Electrical Characteristics ($T_{Ambient}=25^{\circ}C$ unless noted otherwise)

Symbol	Description	TYP.	MAX.	Unit	Conditions
V_F	Max. Forward Voltage	0.6	-	V	I _F =1mA
		0.72	-		I _F =10mA
		0.9	1.2		I _F =100mA
I_R	Reverse Current	-	0.5	μA	V _R =80V
C_T	Total Capacitance	0.9	3.0	pF	V _R =0V, f=1MHz
T_{rr}	Max. Reverse Recovery Time	1.6	4.0	ns	I _F =10mA ,

Typical Characteristics Curves

Fig.1- Typical Instantaneous Forward Characteristics





Fig.2- Typical Instantaneous Reverse Characteristics Curve



Two Terminals SMD Switching Diode

TWD160WT







Fig. 1. REVERSE RECOVERY TIME(t_{rr}) TEST CIRCUIT




Marking Information:



Two Terminals SMD Switching Diode


TWD160WT

Dimensions in inch (mm)



SOD-523

Mounting Pad Layout in inch (mm)



Two Terminals SMD Switching Diode

TWD160WT

How to contact us:

US HEADQUARTERS

28040 WEST HARRISON PARKWAY, VALENCIA, CA 91355-4162
Tel: (800) TAITRON (800) 824-8766 (661) 257-6060
Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415
Email: taitron@taitroncomponents.com
Http://www.taitroncomponents.com

TAITRON COMPONENTS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO C.P. 42970
MEXICO
Tel: +52-55-5560-1519
Fax: +52-55-5560-2190

TAITRON COMPONENTS INCORPORATED REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001 BRAZIL
Tel: +55-11-5574-7949
Fax: +55-11-5572-0052

TAITRON COMPONENTS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

METROBANK PLAZA, 1160 WEST YAN' AN ROAD, SUITE 1503, SHANGHAI, 200052, CHINA
Tel: +86-21-5424-9942
Fax: +86-21-5424-9931