


CL08-10T High Voltage Diode



FEATURES

- Low leakage,high surge capability
- High voltage,fast recovery rectifier
- $T_j:-40^{\circ}\text{C} \sim +150^{\circ}\text{C}$
- Polyimide passivation technology
- Epoxy resin molding,compact encapsulation
- ROHS compliant

| DEVICE ELECTRICAL CHARACTERISTICS (25°C ambient temperature unless stated otherwise) | CONDITIONS | SYMBOL | CL08-10T |
|---|--|-----------|--------------------|
| Repetitive Peak Reverse Voltage | | V_{RRM} | 10KV |
| Average Forward Current | | I_{AV} | 500mA |
| Non-Repetitive Peak Forward Current | | I_{FSM} | 40A |
| Allowable Junction Temperature | | T_j | 125°C |
| Storage Temperature Range | | T_{stg} | -40~125°C |
| Maximum Forward Voltage Drop | $I_F=500\text{mA}, T_a=25^{\circ}\text{C}$ | V_F | 18.0V |
| Maximum Reverse Recovery Time | $I_F=50\text{mA}, I_R=100\text{mA}$ | trr | 100nS |
| Maximum Reverse Current | $V_R=V_{RRM}, T_a=25^{\circ}\text{C}$ | I_{R1} | 2.0 μA |
| Maximum Reverse Current | $V_R=V_{RRM}, T_a=100^{\circ}\text{C}$ | I_{R2} | 50.0 μA |



| SYMBOL | CL08-10T (Unit : mm) |
|--------|---------------------------|
| A | 22.0 |
| D | $\Phi 7.5$ |
| B | 22 |
| C | $\Phi 1.2$ |