Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

83026 Hook-up/Lead - UL AWM Style 1180

For more Information please call

1-800-Belden1



Description:

Stranded silver-coated copper conductor insulation with extruded TFE Teflon.

Physical Characteristics (Overall)						
Conductor						
AWG: # Conductors AWG Stranding Conductor Mat	orial					
1 22 19x34 SPC - Silver Pla						
Insulation						
Insulation Material:						
Insulation Material Wall Thickness (mm) TFE - Tetrafluoroethylene 0.381	4					
	7					
Overall Insulation Overall Cabling						
Overall Nominal Diameter:	1.524 mm					
Applicable Specifications and Agence	y Compliance (Overall)					
Applicable Standards & Environmental F						
UL AWM Style:	1180					
UL Rating:	300 V RMS, 200°C	300 V RMS, 200°C				
EU CE Mark:	Yes					
EU Directive 2000/53/EC (ELV):	Yes					
EU Directive 2002/95/EC (RoHS):	Yes					
EU RoHS Compliance Date (mm/dd/yyyy)	: 04/01/2005					
EU Directive 2002/96/EC (WEEE):	Yes					
EU Directive 2003/11/EC (BFR):	Yes					
CA Prop 65 (CJ for Wire & Cable):	Yes					
MII Order #39 (China RoHS):	Yes					
Military Specification:	MIL-W-16878/5 (Exce	MIL-W-16878/5 (Except For Stranding)				
MIL Spec Rating:	1000 V, 200°C	1000 V, 200°C				
Flame Test						
UL Flame Test:	VW-1					
Plenum/Non-Plenum						
Plenum (Y/N):	No					
Related Documents:						
No related documents are available for this product						
Put Ups and Colors:						
Item # Putup Ship W	eight Color	Notes	Item Desc			
83026 001100 30 MT 0.181 K	G BROWN	E	#22 STR TFE BRN			

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

83026 Hook-up/Lead - UL AWM Style 1180

83026 0011000	305 MT	1.814 KG	BROWN	ES	#22 STR TFE BRN
83026 002100	30 MT	0.181 KG	RED	E	#22 STR TFE RED
83026 0021000	305 MT	1.814 KG	RED	ES	#22 STR TFE RED
83026 003100	30 MT	0.181 KG	ORANGE	E	#22 STR TFE ORG
83026 0031000	305 MT	1.814 KG	ORANGE	ES	#22 STR TFE ORG
83026 004100	30 MT	0.181 KG	YELLOW	E	#22 STR TFE YEL
83026 0041000	305 MT	1.814 KG	YELLOW	ES	#22 STR TFE YEL
83026 005100	30 MT	0.181 KG	GREEN, DARK	E	#22 STR TFE GRNDK
83026 0051000	305 MT	1.814 KG	GREEN, DARK	ES	#22 STR TFE GRNDK
83026 006100	30 MT	0.181 KG	BLUE, LIGHT	E	#22 STR TFE BLULT
83026 0061000	305 MT	1.814 KG	BLUE, LIGHT	ES	#22 STR TFE BLULT
83026 007100	30 MT	0.181 KG	VIOLET	E	#22 STR TFE VIO
83026 0071000	305 MT	1.814 KG	VIOLET	ES	#22 STR TFE VIO
83026 008100	30 MT	0.181 KG	GRAY	E	#22 STR TFE GRY
83026 0081000	305 MT	1.814 KG	GRAY	ES	#22 STR TFE GRY
83026 009100	30 MT	0.181 KG	WHITE	E	#22 STR TFE WHT
83026 0091000	305 MT	1.814 KG	WHITE	ES	#22 STR TFE WHT
83026 010100	30 MT	0.181 KG	BLACK	E	#22 STR TFE BLK
83026 0101000	305 MT	1.814 KG	BLACK		#22 STR TFE BLK
83026 010500	152 MT	1.361 KG	BLACK	ES	#22 STR TFE BLK

Notes:

E = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'

S = STRIPING ADDERS FOR TYPES E AND EE: 123 STRIPES. MINIMUM ORDER10

Revision Number: 1 Revision Date: 05-14-2007

© 2011 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.