


Typical units



| Output Voltage (V) | Output Current (A) | Input Voltage (V) |
|--------------------|--------------------|-------------------|
| 3.3                | 15                 | 18-75             |
| 5                  | 10                 | 18-75             |
| 12                 | 4.5                | 18-75             |

Optimized for harsh environments in industrial/railway applications, the IRS DC-DC converter series offer regulated outputs in an industry-standard sixteen-brick fully encased package.

### FEATURES

- High efficiency synchronous flyback topology
- 18-75 Volts DC wide input range with 3.3, 5 and 12 Volts for Output voltage
- Up to 54 Watts total output power with over-temperature shutdown
- Tiny 1.44" x 1.04" x 0.50" baseplate package
- Industry standard DOSA "brick" format and pinout
- Extensive self-protection shut down features
- Small footprint DC-DC converter, ideal for high current applications
- 2250 Volt Basic input/output isolation
- Operating temperature range -40 to +85°C with derating
- Stable no-load operation with no required external components
- Certified to UL 60950-1, 2nd Edition, EN60950-1 safety approvals

### PRODUCT OVERVIEW

The world of "brick" DC-DC converters has seen a steady size reduction. The IRS series makes another dramatic size shrink down to a "sixteenth-brick" width (0.90 inches) while still retaining a high power output and full 2250 Volt DC isolation. The converter family accepts 18 to 75 Volts DC inputs and delivers fixed outputs regulated to within  $\pm 0.125\%$ . The IRS converters are ideal for industrial and railway applications, datacom and telecom applications, cell phone towers, data centers, server farms and network repeaters.


IRS outputs may be trimmed while delivering fast settling to current step loads and no adverse effects from higher capacitive loads. Excellent ripple and noise specifications assure compatibility to circuits using CPU's, ASIC's, programmable logic

and FPGA's. No minimum load is required. For systems requiring controlled startup/shutdown, an external remote On/Off control may use a switch, transistor or digital logic.


Many self-protection features on the IRS series avoid both converter and external circuit hazards. These include input undervoltage lockout and overtemperature shutdown. The output of these DC-DC converters have current limit using the "hiccup" autorestart technique and the outputs may be short-circuited indefinitely. Additional features include output overvoltage and reverse conduction elimination.

The synchronous flyback topology yields high efficiency for minimal heat buildup and "no fan" operation.

#### Standard Baseplate Option



#### Flanged Baseplate Option



### SAFETY FEATURES


- Basic insulation
- 2250Vdc input to output isolation
- UL 60950-1, 2<sup>nd</sup> Edition
- CAN/CSA-C22.2 NO. 60950-1
- EN 60950-1
- RoHS compliant



| PERFORMANCE SPECIFICATIONS SUMMARY AND ORDERING GUIDE ① |                      |                            |           |                |      |                     |         |                          |           |                                |                                 |       |         |                    |
|---|----------------------|----------------------------|-----------|----------------|------|---------------------|---------|--------------------------|-----------|--------------------------------|---------------------------------|-------|---------|--------------------|
| Root Model ①  | Output               |                            |           |                |      |                     | Input   |                          |           |                                | Efficiency                      |       | Package |                    |
|   | V <sub>OUT</sub> (V) | I <sub>OUT</sub> (A, max.) | Power (W) | R/N (mV pk-pk) |      | Regulation (max.) ③ |         | V <sub>IN</sub> Nom. (V) | Range (V) | I <sub>IN</sub> , no load (mA) | I <sub>IN</sub> , full load (A) | Min.  | Typ.    | Case (inches)      |
|   |                      |                            |           | Typ.           | Max. | Line                | Load    |                          |           |                                |                                 |       |         |                    |
| IRS-3.3/15-Q48  | 3.3                  | 15 ④                       | 49.5      | 90             | 125  | ±0.15%              | ±0.3%   | 48                       | 18-75     | 25                             | 1.16                            | 87.5% | 89%     | 1.44 x 1.04 x 0.50 |
| IRS-5/10-Q48  | 5                    | 10 ⑤                       | 50        | 90             | 130  | ±0.125%             | ±0.125% | 48                       | 18-75     | 30                             | 1.14                            | 88%   | 91%     | 1.44 x 1.04 x 0.50 |
| IRS-12/4.5-Q48  | 12                   | 4.5 ⑥                      | 54        | 115            | 150  | ±0.125%             | ±0.125% | 48                       | 18-75     | 25                             | 1.24                            | 89%   | 91%     | 1.44 x 1.04 x 0.50 |

- ① Please refer to the Part Number Structure when ordering.
- ② All specifications are at nominal line voltage and full load, +25°C unless otherwise noted. See detailed specifications. Output capacitors are 1 µF ceramic multilayer in parallel with 10 µF. I/O caps are necessary for our test equipment and may not be needed for your application.
- ③ Regulation specifications describe output voltage deviations from a nominal/midpoint value to either extreme (50% load step).
- ④ I<sub>OUT</sub> = 13A max. if V<sub>IN</sub> < 36V.
- ⑤ I<sub>OUT</sub> = 8A max. if V<sub>IN</sub> < 36V.
- ⑥ I<sub>OUT</sub> = 3.5A max. if V<sub>IN</sub> < 36V.

## PART NUMBER STRUCTURE



\*Sense is included on the IRS-3.3/15-Q48 and IRS-5/10-Q48.

Examples:

IRS-3.3/15-Q48NF-C stands for Industrial Railway 1/16 Brick, 3.3V<sub>OUT</sub>@15A, 18V-75V<sub>IN</sub>, Negative Logic, Flanged Baseplate, RoHS-6 Compliant.

IRS-12/4.5-Q48P-C stands for Industrial Railway 1/16 Brick, 12V<sub>OUT</sub>@4.5A, 18V-75V<sub>IN</sub>, Positive Logic, Standard Baseplate, RoHS-6 Compliant.

- ① Special quantity order is required.
- ② Some model number combinations may not be available. See website or contact your local Murata sales representative.

### FUNCTIONAL SPECIFICATIONS, IRS-3.3/15-Q48


| ABSOLUTE MAXIMUM RATINGS  |  | Conditions [1]   | Minimum | Typical/Nominal | Maximum | Units                   |
|---|--|--|---------|-----------------|---------|-------------------------|
| Input Voltage, Continuous   |  | Full temperature range   | 0       |                 | 75      | Vdc                     |
| Input Voltage, Transient  |  | Operating or non-operating, 100 mS max. duration                       |         |                 | 100     | Vdc                     |
| Isolation Voltage   |  | Input to output tested   | 2250    |                 |         | Vdc                     |
| Input Reverse Polarity  |  | None, install external fuse  |         | None            |         | Vdc                     |
| On/Off Remote Control   |  | Power on or off, referred to -Vin                                      | 0       |                 | 15      | Vdc                     |
| Output Power  |  |  | 0       | 49.5            | 50      | W                       |
| Output Current  |  | Current-limited, no damage, short-circuit protected                    | 0       | 15              | 15      | A                       |
| Storage Temperature Range   |  | Vin = Zero (no power)  | -55     |                 | 125     | °C                      |
| Absolute maximums are stress ratings. Exposure of devices to greater than any of these conditions may adversely affect long-term reliability. Proper operation under conditions other than those listed in the Performance/Functional Specifications Table is not implied or recommended. |  |  |         |                 |         |                         |
| <b>INPUT</b>  |  |  |         |                 |         |                         |
| Operating voltage range   |  |  | 18      | 48              | 75      | Vdc                     |
| Recommended External Fuse   |  | Fast blow  |         | 7               |         | A                       |
| Start-up threshold  |  | Rising input voltage   | 16      | 17              | 17.9    | Vdc                     |
| Undervoltage lockout [9]  |  | Falling input voltage  | 15      | 16.25           | 17.50   | Vdc                     |
| Overvoltage shutdown  |  | Rising input voltage   |         | None            |         | Vdc                     |
| Reverse Polarity Protection [11]  |  | None, install external fuse  |         | None            |         | Vdc                     |
| Internal Filter Type  |  |  |         | LC              |         |                         |
| <b>Input current</b>  |  |  |         |                 |         |                         |
| Full Load Conditions  |  | Vin = nominal  |         | 1.16            | 1.19    | A                       |
| Low Line  |  | Vin = minimum, 13A load  |         | 2.63            | 2.72    | A                       |
| Inrush Transient  |  |  |         | 0.4             |         | A2-Sec.                 |
| Output in Short Circuit   |  |  |         | 100             | 200     | mA                      |
| No Load Input current   |  | Iout = minimum, unit=ON  |         | 25              | 60      | mA                      |
| Shut-Down mode Input Current (Off, UV, OT)  |  |  |         | 5               | 10      | mA                      |
| Reflected (back) ripple current [2]   |  | Measured at input with specified filter                                |         | 15              | 30      | mA, pk-pk               |
| Pre-biased startup  |  | External output voltage < Vset   |         | Monotonic       |         |                         |
| <b>GENERAL and SAFETY</b>   |  |  |         |                 |         |                         |
| Efficiency  |  | Vin=48V, full load   | 87.5    | 89              |         | %                       |
|   |  | Vin=24V, full load   | 88.5    | 90.5            |         | %                       |
| <b>Isolation</b>  |  |  |         |                 |         |                         |
| Isolation Voltage, Input to Output  |  |  | 2250    |                 |         | Vdc                     |
| Isolation Voltage, Input to Baseplate   |  |  | 1500    |                 |         | Vdc                     |
| Isolation Voltage, Baseplate to Output  |  |  | 1500    |                 |         | Vdc                     |
| Insulation Safety Rating  |  |  |         | Basic           |         |                         |
| Isolation Resistance  |  |  |         | 100             |         | MΩ                      |
| Isolation Capacitance   |  |  |         | 1300            |         | pF                      |
| Safety  |  | Certified to UL-60950-1, IEC/EN60950-1, 2nd Edition                    |         | Yes             |         |                         |
| Calculated MTBF [3]   |  | Belcore, Telcordia SR-332, Method 1, Class 3, ground fixed, Tcase=25°C |         | 3.0             |         | Hours x 10 <sup>6</sup> |
| <b>DYNAMIC CHARACTERISTICS</b>  |  |  |         |                 |         |                         |
| Fixed Switching Frequency   |  |  | 250     | 280             | 310     | KHz                     |
| Power Up Startup Time   |  | Power On to Vout regulated   |         |                 | 30      | mS                      |
| On/Off Startup Time   |  | Remote ON to Vout regulated  |         |                 | 30      | mS                      |
| Dynamic Load Response   |  | 50-75-50% load step, settling time to within 1% of Vout                |         | 100             | 200     | μSec                    |
| Dynamic Load Peak Deviation   |  | Same as above,   |         | ±180            | ±240    | mV                      |
| <b>FEATURES and OPTIONS</b>   |  |  |         |                 |         |                         |
| <b>Remote On/Off Control [4]</b>  |  |  |         |                 |         |                         |
| <b>"N" suffix</b>   |  |  |         |                 |         |                         |
| Negative Logic, ON state  |  | ON=Pin grounded or external voltage                                    | -0.1    |                 | 0.8     | Vdc                     |
| Negative Logic, OFF state   |  | OFF=Pin open or external voltage                                       | 2.5     |                 | 15      | Vdc                     |
| Control Current   |  | Open collector/drain, sourcing   |         | 1               | 2       | mA                      |
| <b>"P" suffix</b>   |  |  |         |                 |         |                         |
| Positive Logic, ON state  |  | ON=Pin open or external voltage  | 10      |                 | 15      | Vdc                     |

## FUNCTIONAL SPECIFICATIONS, IRS-3.3/15-Q48 (CONT.)


|  |   |                |                        |                |               |
|--|---|----------------|------------------------|----------------|---------------|
| Positive Logic, OFF state                          | OFF=Ground pin or external voltage                  | 0              |                        | 0.7            | Vdc           |
| Control Current                                    | Open collector/drain                                |                | 1                      | 2              | mA            |
| <b>OUTPUT</b>                                      | <b>Conditions [1]</b>                               | <b>Minimum</b> | <b>Typical/Nominal</b> | <b>Maximum</b> | <b>Units</b>  |
| Total Output Power                                 | See Derating  | 0.0            | 49.5                   | 50             | W             |
| <b>Voltage</b>                                     |   |                |                        |                |               |
| Nominal Output Voltage                             | No trim   | 3.267          | 3.3                    | 3.333          | Vdc           |
| Setting Accuracy                                   | At 50% load   |                | 1                      |                | % of Vnom.    |
| Output Voltage Range [6]                           | User-adjustable                                     | -10            |                        | 10             | % of Vnom.    |
| Overvoltage Protection [8]                         | Via magnetic feedback                               | 4              | 4.3                    | 4.9            | Vdc           |
| <b>Current</b>                                     |   |                |                        |                |               |
| Output Current Range                               | Vin=18V-36V   | 0.0            |                        | 13.0           | A             |
| Output Current Range                               | Vin=36V-75V   | 0.0            |                        | 15.0           | A             |
| Minimum Load                                       |   |                | No minimum load        |                |               |
| Current Limit Inception                            | 98% of Vnom., after warmup                          | 18.4           | 21.9                   | 25.4           | A             |
| <b>Short Circuit</b>                               |   |                |                        |                |               |
| Short Circuit Current                              | Hiccup technique, autorecovery within 1.25% of Vout |                | 0.6                    |                | A             |
| Short Circuit Duration (remove short for recovery) | Output shorted to ground, no damage                 |                | Continuous             |                |               |
| Short circuit protection method                    | Current limiting                                    |                |                        |                |               |
| <b>Regulation [5]</b>                              |   |                |                        |                |               |
| Line Regulation                                    | Vin=min. to max., Vout=nom., full load              |                |                        | ±0.15          | %             |
| Load Regulation                                    | Iout=min. to max., Vin=48V                          |                |                        | ±0.3           | %             |
| Ripple and Noise [7][10]                           | With a 1uF    10uF output caps                      |                | 90                     | 125            | mV pk-pk      |
|  | With a 1uF    100uF output caps                     |                | 60                     |                | mV pk-pk      |
| Temperature Coefficient                            | At all outputs                                      |                | 0.02                   |                | % of Vnom./°C |
| Remote Sense Compensation [12]                     | Sense connected at load                             |                |                        | 10             | % of Vout     |
| Maximum Capacitive Load                            | Constant resistance mode, low ESR                   | 0              | 10,000                 |                | µF            |
| <b>MECHANICAL</b>                                  |   |                |                        |                |               |
| Outline Dimensions                                 | Standard Basplate                                   |                | 1.44 x 1.04 x 0.5      |                | Inches        |
| (Please refer to outline drawing)                  | L x W x H   |                | 36.47 x 26.31 x 12.7   |                | mm            |
| Outline Dimensions                                 | Flanged Basplate                                    |                | 1.44 x 1.5 x 0.5       |                | Inches        |
| (Please refer to outline drawing)                  | L x W x H   |                | 36.47 x 38.1 x 12.7    |                | mm            |
| Weight   |   |                | 0.58                   |                | Ounces        |
|  |   |                | 16.4                   |                | Grams         |
| Through Hole Pin Diameter                          |   |                | 0.06 & 0.04            |                | Inches        |
|  |   |                | 1.524 & 1.016          |                | mm            |
| Through Hole Pin Material                          |   |                | Copper alloy           |                |               |
| EMI/RFI Shielding                                  |   |                | None                   |                |               |
| <b>ENVIRONMENTAL</b>                               |   |                |                        |                |               |
| Operating Ambient Temperature Range                | See derating, full power, natural convection        | -40            |                        | 85             | °C            |
| Operating Case Temperature Range                   | No derating, full power, natural convection         | -40            |                        | 105            | °C            |
| Storage Temperature                                | Vin = Zero (no power)                               | -55            |                        | 125            | °C            |
| Thermal Protection/Shutdown                        | Measured in center                                  | 115            | 125                    | 130            | °C            |
| Electromagnetic Interference                       | External filter is required                         |                |                        |                |               |
| Conducted, EN55022/CISPR22                         |   |                | B                      |                | Class         |
| RoHS rating [4]                                    |   |                | RoHS-6                 |                |               |

**TYPICAL PERFORMANCE DATA, IRS-3.3/15-Q48**


Efficiency vs. Line Voltage and Load Current @ 25°C




Power Dissipation vs. Load Current @ 25°C




Maximum Current Temperature Derating at Sea Level  
(V<sub>IN</sub> = 24V, airflow is from vin- to vin+)




Maximum Current Temperature Derating at Sea Level  
(V<sub>IN</sub> = 48V, airflow is from vin- to vin+)



Maximum Current Temperature Derating at Sea Level  
(V<sub>IN</sub> = 60V, airflow is from vin- to vin+)




Maximum Current Temperature Derating at Sea Level  
(V<sub>IN</sub> = 75V, airflow is from vin- to vin+)




**TYPICAL PERFORMANCE DATA, IRS-3.3/15-Q48**


Output Ripple and Noise (Vin=48V, Vout=nom., Iout=no load,  
Cload=1μF ceramic || 10μF tantalum, Ta=+25°C., ScopeBW=20MHz)




Output Ripple and Noise (Vin=48V, Vout=nom., Iout=15A,  
Cload=1μF ceramic || 10μF tantalum, Ta=+25°C., ScopeBW=20MHz)




On/Off Enable Delay (Vin=48V, Vout=nom., Iout=15A, Cload=0 μF, Ta=+25°C.,  
ScopeBW=20MHz) Trace 1=Enable, Trace 4=Vout




Step Load Transient Response (Vin=48V, Vout=nom., Iout=50-75-50% of full load,  
Cload=1μF ceramic || 10μF tantalum, Ta=+25°C., ScopeBW=20MHz)



Step Load Transient Response (Vin=48V, Vout=nom., Iout=50-75-50% of full load,  
Cload=10,000 μF, Ta=+25°C., ScopeBW=20MHz)



Thermal Derating vs. Baseplate Temperature



### FUNCTIONAL SPECIFICATIONS, IRS-5/10-Q48

| ABSOLUTE MAXIMUM RATINGS  | Conditions [1]   | Minimum | Typical/Nominal | Maximum | Units                   |
|---|--|---------|-----------------|---------|-------------------------|
| Input Voltage, Continuous   | Full temperature range   | 0       |                 | 75      | Vdc                     |
| Input Voltage, Transient  | Operating or non-operating, tested:<br>100 mS max. duration                  | 0       |                 | 100     | Vdc                     |
| Isolation Voltage   | Input to output  |         |                 | 2250    | Vdc                     |
| Input Reverse Polarity  | None, install external fuse  |         | None            |         | Vdc                     |
| On/Off Remote Control   | Power on, referred to -Vin   | 0       |                 | 15      | Vdc                     |
| Output Power  |  | 0       | 50              | 50.63   | W                       |
| Output Current  | Current-limited, no damage, short-circuit protected                          | 0       | 10              | 10      | A                       |
| Storage Temperature Range   | Vin = Zero (no power)  | -55     |                 | 125     | °C                      |
| Absolute maximums are stress ratings. Exposure of devices to greater than any of these conditions may adversely affect long-term reliability. Proper operation under conditions other than those listed in the Performance/Functional Specifications Table is not implied or recommended. |  |         |                 |         |                         |
| <b>INPUT</b>  |  |         |                 |         |                         |
| Operating voltage range   |  | 18      | 48              | 75      | Vdc                     |
| Recommended External Fuse   | Fast blow  |         |                 | 5       | A                       |
| Start-up threshold, turn on   | Rising input voltage   | 16      | 17.5            | 17.9    | Vdc                     |
| Undervoltage shutdown, turn off [9]   | Falling input voltage  | 15      | 16.75           | 17.5    | Vdc                     |
| Overshoot shutdown  |  |         | NA              |         | Vdc                     |
| Reverse Polarity Protection [11]  | None, install external fuse  |         | None            |         | Vdc                     |
| Internal Filter Type  |  |         | LC              |         |                         |
| <b>Input current</b>  |  |         |                 |         |                         |
| Full Load Conditions  | Vin = nominal  |         | 1.14            | 1.2     | A                       |
| Low Line  | Vin = minimum  |         | 2.44            | 2.51    | A                       |
| Inrush Transient  |  |         | 0.4             |         | A2-Sec.                 |
| Output in Short Circuit   |  |         | 100             | 200     | mA                      |
| No Load Input Current   | Iout = minimum, unit=ON  |         | 30              | 60      | mA                      |
| Shut-Down Mode Input Current  |  |         | 5               | 10      | mA                      |
| Reflected (back) ripple current [2]   | No filtering   |         | 150             | 200     | mAp-p                   |
| Reflected (back) ripple current [2]   | Measured at input with specified filter                                      |         | 15              | 30      | mAp-p                   |
| Pre-biased startup  | External output voltage < Vset   |         | Monotonic       |         |                         |
| <b>GENERAL and SAFETY</b>   |  |         |                 |         |                         |
| Efficiency  | Vin=48V, full load   | 88      | 91              |         | %                       |
|   | Vin=24V, full load   | 89.5    | 91              |         | %                       |
| <b>Isolation</b>  |  |         |                 |         |                         |
| Isolation Voltage, Input to Output  |  | 2250    |                 |         | Vdc                     |
| Isolation Voltage, Input to Baseplate   |  | 1500    |                 |         | Vdc                     |
| Isolation Voltage, Baseplate to Output  |  | 1500    |                 |         | Vdc                     |
| Insulation Safety Rating  |  |         | Basic           |         |                         |
| Isolation Resistance  |  |         | 100             |         | MΩ                      |
| Isolation Capacitance   |  |         | 1000            |         | pF                      |
| Safety (meets the following requirements)   | UL-60950-1, CSA-C22.2 No.60950-1,<br>IEC/EN60950-1, 2nd Edition              |         | Yes             |         |                         |
| Calculated MTBF [3]   | Belcore, Telcordia SR-332, Method 1, class 3,<br>ground fixed, Tambient=25°C |         | 3.0             |         | Hours x 10 <sup>6</sup> |
| <b>DYNAMIC CHARACTERISTICS</b>  |  |         |                 |         |                         |
| Fixed Switching Frequency   |  | 225     | 275             | 325     | KHz                     |
| Startup Time  | Power On to Vout regulated   |         |                 | 30      | mS                      |
| Startup Time  | Remote ON to Vout regulated  |         |                 | 30      | mS                      |
| Dynamic Load Response   | 50-75-50% load step, settling time to within<br>1% of Vout                   |         | 100             | 200     | μSec                    |
| Dynamic Load Peak Deviation   | Same as above,   |         | ±180            | ±240    | mV                      |
| <b>FEATURES and OPTIONS</b>   |  |         |                 |         |                         |
| <b>Remote On/Off Control [4]</b>  |  |         |                 |         |                         |
| <b>"N" suffix</b>   |  |         |                 |         |                         |
| Negative Logic, ON state  | ON = Pin grounded or external voltage  | -0.1    |                 | 0.8     | V                       |
| Negative Logic, OFF state   | OFF = Pin open or external voltage   | 2.5     |                 | 15      | V                       |
| Control Current   | open collector/drain   |         | 1               | 2       | mA                      |
| <b>"P" suffix</b>   |  |         |                 |         |                         |
| Positive Logic, ON state  | ON = Pin open or external voltage  | 10      |                 | 15      | V                       |
| Positive Logic, OFF state   | OFF = Ground pin or external voltage   | 0       |                 | 0.7     | V                       |
| Control Current   | open collector/drain   |         | 1               | 2       | mA                      |




## FUNCTIONAL SPECIFICATIONS, IRS-5/10-Q48 (CONT.)

| OUTPUT   | Conditions [1]                                      | Minimum | Typical/Nominal                                 | Maximum | Units         |
|--|---|---------|---|---------|---------------|
| <b>Total Output Power</b>                                      | See Derating  | 0.0     | 50  | 50.63   | W             |
| <b>Voltage</b>   |   |         |   |         |               |
| <b>Nominal Output Voltage</b>                                  | No trim   | 4.938   | 5   | 5.063   | Vdc           |
| <b>Setting Accuracy</b>  | At 50% load   | -1.25   |   | 1.25    | % of Vset     |
| <b>Output Voltage Range [6]</b>                                | User-adjustable                                     | -20     |   | 10      |               |
| <b>Overvoltage Protection [8]</b>                              | Via magnetic feedback                               | 6.2     | 6.4   | 6.6     | Vdc           |
| <b>Current</b>   |   |         |   |         |               |
| <b>Output Current Range</b>                                    | Vin=18V to 36V                                      | 0       |   | 8       |               |
| <b>Output Current Range</b>                                    | Vin=36V to 75V                                      | 0       |   | 10      | A             |
| <b>Minimum Load</b>  |   |         | No minimum load                                 |         |               |
| <b>Current Limit Inception</b>                                 | 98% of Vnom., cold condition                        | 12      | 14  | 16.5    | A             |
| <b>Short Circuit</b>   |   |         |   |         |               |
| <b>Short Circuit Current</b>                                   | Hiccup technique, autorecovery within 1.25% of Vout |         | 0.6   |         | A             |
| <b>Short Circuit Duration (remove short for recovery)</b>      | Output shorted to ground, no damage                 |         | Continuous                                      |         |               |
| <b>Short circuit protection method</b>                         | Current limiting                                    |         |   |         |               |
| <b>Regulation [5]</b>  |   |         |   |         |               |
| <b>Line Regulation</b>   | Vin=min. to max., Vout=nom., nom load               |         | ±0.125  |         | V             |
| <b>Load Regulation</b>   | Iout=min. to max                                    |         | ±0.125  |         | V             |
| <b>Ripple and Noise [7][10]</b>                                | With a 1uF    10 uF output caps.                    |         | 90  | 130     | mV pk-pk      |
|  | With a 1uF    100uF tantalum output caps            |         | 65  |         | mV pk-pk      |
| <b>Temperature Coefficient</b>                                 | At all outputs                                      |         | 0.02  |         | % of Vout./°C |
| <b>Remote Sense Compensation [12]</b>                          | Sense connected at load                             |         |   | 10      | % of Vout     |
| <b>Maximum Capacitive Loading (10% ceramic, 90% Oscon)</b>     | Constant resistance mode , low ESR                  | 0       | 5000  |         | µF            |
| <b>MECHANICAL</b>  |   |         |   |         |               |
| <b>Outline Dimensions</b>                                      | Standard Basplate                                   |         | 1.44 x 1.04 x 0.5                               |         | Inches        |
| <b>(Please refer to outline drawing)</b>                       | L x W x H   |         | 36.47 x 26.31 x 12.7                            |         | mm            |
| <b>Outline Dimensions</b>                                      | Flanged Basplate                                    |         | 1.44 x 1.5 x 0.5                                |         | Inches        |
| <b>(Please refer to outline drawing)</b>                       | L x W x H   |         | 36.47 x 38.1 x 12.7                             |         | mm            |
| <b>Weight</b>  |   |         | 0.58  |         | Ounces        |
|  |   |         | 16.4  |         | Grams         |
| <b>Through Hole Pin Diameter</b>                               | Diameter of pins standard                           |         | 0.06 & 0.04                                     |         | Inches        |
|  |   |         | 1.524 & 1.016                                   |         | mm            |
| <b>Through Hole Pin Material</b>                               |   |         | Gold-plated copper alloy with nickel underplate |         |               |
| <b>TH Pin Plating Metal and Thickness</b>                      | Nickel subplate                                     |         | 50  |         | µ-inches      |
|  | Gold overplate                                      |         | 5   |         | µ-inches      |
| <b>EMI/RFI Shielding</b>                                       |   |         | None  |         |               |
| <b>ENVIRONMENTAL</b>   |   |         |   |         |               |
| <b>Operating Ambient Temperature Range</b>                     | See derating curves                                 | -40     |   | 85      | °C            |
| <b>Storage Temperature</b>                                     | Vin = Zero (no power)                               | -55     |   | 125     | °C            |
| <b>Operating Case Temp</b>                                     | No derating required                                | -40     |   | 105     | °C            |
| <b>Thermal Protection/Shutdown</b>                             | Measured at hotspot                                 | 115     | 125   | 130     | °C            |
| <b>Electromagnetic Interference Conducted, EN55022/CISPR22</b> | External filter is required                         |         | B   |         | Class         |
| <b>RoHS rating [4]</b>   |   |         | RoHS-6  |         |               |




**TYPICAL PERFORMANCE DATA, IRS-5/10-Q48**


Efficiency vs. Line Voltage and Load Current @ 25°C – Vin = 18V-36V




Efficiency vs. Line Voltage and Load Current @ 25°C – Vin = 36V-75V




Maximum Current Temperature Derating at Sea Level  
(Vin = 24V, airflow is from vin- to vin+)




Maximum Current Temperature Derating at Sea Level  
(Vin = 48V, airflow is from vin- to vin+)



Maximum Current Temperature Derating at Sea Level  
(Vin = 60V, airflow is from vin- to vin+)




Maximum Current Temperature Derating at Sea Level  
(Vin = 75V, airflow is from vin- to vin+)




**TYPICAL PERFORMANCE DATA, IRS-5/10-Q48**


Power On Startup Delay (Vin=0 to 48V, Vout=nom, Iout=10A, Cload=0 uF, Ta=+25°C., ScopeBW=20Mhz) Trace 1=Vin, Trace 4=Vout



Power On Startup Delay (Vin=0 to 48V, Vout=nom, Iout=0A, Cload=0 uF, Ta=+25°C., ScopeBW=20Mhz) Trace 1=Vin, Trace 4=Vout




On/Off Enable Delay (Vin=48V, Vout=nom, Iout=10A, Cload=0 uF, Ta=+25°C., ScopeBW=20Mhz) Trace 1=Enable, Trace 4=Vout




**TYPICAL PERFORMANCE DATA, IRS-5/10-Q48**


Output Ripple and Noise (Vin=48V, Vout=nom., Iout=10A, Cload=1 uFceramic II 10uF tantulum, Ta=+25°C., ScopeBW=20MHz)




Output Ripple and Noise (Vin=48V, Vout=nom., Iout=0A, Cload=1 uFceramic II 10uF tantulum, Ta=+25°C., ScopeBW=20MHz)




Step Load Transient Response (Vin=48V, Vout=nom., Iout=50-75-50% of full load, Cload=1 uF ceramic II 10uF tantulum, Ta=+25°C., ScopeBW=20MHz Ch1=5Vo, Ch2=Io 2amps/div)



Step Load Transient Response (Vin=48V, Vout=nom., Iout=50-75-50% of full load, Cload=680uF, Ta=+25°C., ScopeBW=20MHz Ch1=5Vo, Ch2=Io 2amps/div)



Thermal Derating vs. Baseplate Temperature



## FUNCTIONAL SPECIFICATIONS, IRS-12/4.5-Q48


| ABSOLUTE MAXIMUM RATINGS  | Conditions [1]   | Minimum | Typical/Nominal | Maximum | Units                   |
|---|--|---------|-----------------|---------|-------------------------|
| Input Voltage, Continuous   | Full temperature range   | 0       |                 | 75      | Vdc                     |
| Input Voltage, Transient  | Operating or non-operating, 100 mS max. duration                     | 0       |                 | 100     | Vdc                     |
| Isolation Voltage   | Input to output tested   |         |                 | 2250    | Vdc                     |
| Input Reverse Polarity  | None, install external fuse  |         | None            |         | Vdc                     |
| On/Off Remote Control   | Power on or off, referred to -Vin                                    | 0       |                 | 15      | Vdc                     |
| Output Power  |  | 0       | 54              | 54.54   | W                       |
| Output Current  | Current-limited, no damage, short-circuit protected                  | 0       | 4.5             | 4.5     | A                       |
| Storage Temperature Range   | Vin = Zero (no power)  | -55     |                 | 125     | °C                      |
| Absolute maximums are stress ratings. Exposure of devices to greater than any of these conditions may adversely affect long-term reliability. Proper operation under conditions other than those listed in the Performance/Functional Specifications Table is not implied or recommended. |  |         |                 |         |                         |
| <b>INPUT</b>  |  |         |                 |         |                         |
| Operating voltage range   |  | 18      | 48              | 75      | Vdc                     |
| Recommended External Fuse   | Fast blow  |         | 6               |         | A                       |
| Start-up threshold  | Rising input voltage   | 16.5    | 17.2            | 17.9    | Vdc                     |
| Undervoltage lockout [9]  | Falling input voltage  | 15      | 16.5            | 17.50   | Vdc                     |
| Overvoltage shutdown  | Rising input voltage   |         | None            |         | Vdc                     |
| Reverse Polarity Protection [11]  | None, install external fuse  |         | None            |         | Vdc                     |
| Internal Filter Type  |  |         | Capacitive      |         |                         |
| <b>Input current</b>  |  |         |                 |         |                         |
| Full Load Conditions  | Vin = nominal  |         | 1.24            | 1.28    | A                       |
| Low Line  | Vin = minimum , 3.5A load  |         | 2.55            | 2.63    | A                       |
| Inrush Transient  |  |         | 0.05            |         | A2-Sec.                 |
| Output in Short Circuit   |  |         | 100             | 200     | mA                      |
| No Load Input Current   | Iout = minimum, unit=ON  |         | 25              | 60      | mA                      |
| Shut-Down Mode Input Current (Off, UV, OT)  |  |         | 5               | 10      | mA                      |
| Reflected (back) ripple current [2]   | Measured at input with specified filter                              |         | 30              | 40      | mA, pk-pk               |
| Pre-biased startup  | External output voltage < Vset                                       |         | Monotonic       |         |                         |
| <b>GENERAL and SAFETY</b>   |  |         |                 |         |                         |
| Efficiency  | Vin=48V, full load   | 89      | 91              |         | %                       |
|   | Vin=24V, full load   | 89.5    | 91.5            |         | %                       |
| <b>Isolation</b>  |  |         |                 |         |                         |
| Isolation Voltage, Input to Output  |  | 2250    |                 |         | Vdc                     |
| Isolation Voltage, Input to Baseplate   |  | 1500    |                 |         | Vdc                     |
| Isolation Voltage, Baseplate to Output  |  | 1500    |                 |         | Vdc                     |
| Insulation Safety Rating  |  |         | Basic           |         |                         |
| Isolation Resistance  |  |         | 100             |         | MΩ                      |
| Isolation Capacitance   |  |         | 1000            |         | pF                      |
| Safety (Designed to meet the following requirements)  | UL-60950-1, IEC/EN60950-1, 2nd Edition                               |         | Yes             |         |                         |
| Calculated MTBF [3]   | Per Telcordia SR-332, Method 1, class 3, ground fixed, Tambient=25°C |         | 3.0             |         | Hours x 10 <sup>6</sup> |
| <b>DYNAMIC CHARACTERISTICS</b>  |  |         |                 |         |                         |
| Fixed Switching Frequency   |  | 200     | 230             | 260     | KHz                     |
| Power Up Startup Time   | Power On to Vout regulated   |         |                 | 30      | mS                      |
| On/Off Startup Time   | Remote ON to Vout regulated  |         |                 | 30      | mS                      |
| Dynamic Load Response   | 50-75-50% load step, settling time to within ±1% of Vout             |         | 250             | 300     | µSec                    |
| Dynamic Load Peak Deviation   | Same as above,   |         | ±350            | ±400    | mV                      |
| <b>FEATURES and OPTIONS</b>   |  |         |                 |         |                         |
| <b>Remote On/Off Control [4]</b>  |  |         |                 |         |                         |
| <b>"N" suffix</b>   |  |         |                 |         |                         |
| Negative Logic, ON state  | ON=Pin grounded or external voltage                                  | -0.1    |                 | 0.8     | Vdc                     |
| Negative Logic, OFF state   | OFF=Pin open or external voltage                                     | 2.5     |                 | 15      | Vdc                     |
| Control Current   | Open collector/drain, sourcing                                       |         | 1               | 2       | mA                      |
| <b>"P" suffix</b>   |  |         |                 |         |                         |
| Positive Logic, ON state  | ON=Pin open or external voltage                                      | 10      |                 | 15      | Vdc                     |
| Positive Logic, OFF state   | OFF=Pin grounded or external voltage                                 | 0       |                 | 0.7     | Vdc                     |

## FUNCTIONAL SPECIFICATIONS, IRS-12/4.5-Q48 (CONT.)


| Control Current                                    | Open collector/drain, sinking                        |         | 1                    | 2       | mA            |
|--|--|---------|----------------------|---------|---------------|
| OUTPUT   | Conditions [1]                                       | Minimum | Typical/Nominal      | Maximum | Units         |
| Total Output Power                                 | See Derating   | 0       | 54                   | 54.54   | W             |
| <b>Voltage</b>                                     |  |         |                      |         |               |
| Nominal Output Voltage                             | No trim  | 11.88   | 12                   | 12.12   | Vdc           |
| Setting Accuracy                                   | At 50% load  |         | ±1                   |         | % of Vnom.    |
| Output Voltage Range [6]                           | User-adjustable                                      | -20     |                      | 10      | % of Vnom.    |
| Overvoltage Protection [8]                         | Via magnetic feedback                                | 13.3    | 15.3                 | 18      | Vdc           |
| <b>Current</b>                                     |  |         |                      |         |               |
| Output Current Range                               | Vin=18V-36V  | 0       |                      | 3.5     | A             |
| Output Current Range                               | Vin=36V-75V  | 0       |                      | 4.5     | A             |
| Minimum Load                                       |  |         | No minimum load      |         |               |
| Current Limit Inception                            | 98% of Vnom., after warmup                           | 5.05    | 6.4                  | 7.4     | A             |
| <b>Short Circuit</b>                               |  |         |                      |         |               |
| Short Circuit Current                              | Hiccup technique, autorecovery within ±1.25% of Vout |         | 0.6                  |         | A             |
| Short Circuit Duration (remove short for recovery) | Output shorted to ground, no damage                  |         | Continuous           |         |               |
| Short circuit protection method                    | Current limiting                                     |         |                      |         |               |
| <b>Regulation [5]</b>                              |  |         |                      |         |               |
| Line Regulation                                    | Vin=min. to max., Vout=nom., full load               |         |                      | ±0.125  | %             |
| Load Regulation                                    | Iout=min. to max., Vin=48V                           |         |                      | ±0.125  | %             |
| Ripple and Noise [7][10]                           | with a 1uF    10uF output caps                       |         | 115                  | 150     | mV pk-pk      |
| Temperature Coefficient                            | At all outputs                                       |         | ±0.02                |         | % of Vnom./°C |
| Maximum Capacitive Load                            | Constant resistance mode, low ESR                    | 0       | 2200                 |         | µF            |
| <b>MECHANICAL</b>                                  |  |         |                      |         |               |
| Outline Dimensions                                 | Standard Basplate                                    |         | 1.44 x 1.04 x 0.5    |         | Inches        |
| (Please refer to outline drawing)                  | L x W x H  |         | 36.47 x 26.31 x 12.7 |         | mm            |
| Outline Dimensions                                 | Flanged Basplate                                     |         | 1.44 x 1.5 x 0.5     |         | Inches        |
| (Please refer to outline drawing)                  | L x W x H  |         | 36.47 x 38.1 x 12.7  |         | mm            |
| Weight   |  |         | 0.58                 |         | Ounces        |
|  |  |         | 16.4                 |         | Grams         |
| Through Hole Pin Diameter                          |  |         | 0.06 & 0.04          |         | Inches        |
|  |  |         | 1.524 & 1.016        |         | mm            |
| Through Hole Pin Material                          |  |         | Copper alloy         |         |               |
| TH Pin Plating Metal and Thickness                 | Nickel subplate                                      |         | 50                   |         | µ-inches      |
|  | Gold overplate                                       |         | 5                    |         | µ-inches      |
| EMI/RFI Shielding                                  |  |         | None                 |         |               |
| <b>ENVIRONMENTAL</b>                               |  |         |                      |         |               |
| Operating Ambient Temperature Range                | No derating, full power, natural convection          | -40     |                      | 85      | °C            |
| Operating Case Temperature Range                   | No derating, full power, natural convection          | -40     |                      | 105     | °C            |
| Storage Temperature                                | Vin = Zero (no power)                                | -55     |                      | 125     | °C            |
| Thermal Protection/Shutdown                        | Measured in center                                   | 115     | 125                  | 130     | °C            |
| Electromagnetic Interference                       | External filter is required                          |         |                      |         |               |
| Conducted, EN55022/CISPR22                         |  |         | B                    |         | Class         |
| RoHS rating [4]                                    |  |         | RoHS-6               |         |               |

**TYPICAL PERFORMANCE DATA, IRS-12/4.5-Q48**


Efficiency vs. Line Voltage and Load Current @ 25°C




Power Dissipation vs. Load Current @ 25°C




Maximum Current Temperature Derating at Sea Level  
(VIN = 24V, airflow is from vin- to vin+)




Maximum Current Temperature Derating at Sea Level  
(VIN = 48V, airflow is from vin- to vin+)



Maximum Current Temperature Derating at Sea Level  
(VIN = 60V, airflow is from vin- to vin+)




Maximum Current Temperature Derating at Sea Level  
(VIN = 75V, airflow is from vin- to vin+)




**TYPICAL PERFORMANCE DATA, IRS-12/4.5-Q48**


Output Ripple and Noise (Vin=48V, Vout=nom., Iout=no load,  
Cload=1μF ceramic || 10μF tantalum, Ta=+25°C., ScopeBW=20MHz)




Output Ripple and Noise (Vin=48V, Vout=nom., Iout=4.5A,  
Cload=1μF ceramic || 10μF tantalum, Ta=+25°C., ScopeBW=20MHz)




On/Off Enable Delay (Vin=48V, Vout=nom., Iout=no load, Cload=0 μF, Ta=+25°C.,  
ScopeBW=20MHz) Trace 1=Enable, Trace 4=Vout



On/Off Enable Delay (Vin=48V, Vout=nom., Iout=4.5A, Cload=0 μF, Ta=+25°C.,  
ScopeBW=20MHz) Trace 1=Enable, Trace 4=Vout




Step Load Transient Response (Vin=48V, Vout=nom., Iout=50-75-50% of full load,  
Cload=1μF ceramic || 10μF tantalum, Ta=+25°C., ScopeBW=20MHz)






**TYPICAL PERFORMANCE DATA, IRS-12/4.5-Q48**


Power On Startup Delay (Vin=0 to 48V, Vout=nom., Iout=no load, Cload=0 μF, Ta=+25°C., ScopeBW=20MHz) Trace 1=Vin, Trace 4=Vout



Power On Startup Delay (Vin=0 to 48V, Vout=nom., Iout=4.5A, Cload=0 μF, Ta=+25°C., ScopeBW=20MHz) Trace 1=Vin, Trace 4=Vout



Thermal Derating vs. Baseplate Temperature



### Performance Specification Notes

1. All specifications are typical unless noted. Ambient temperature = +25°Celsius,  $V_{IN}$  is nominal, output current is maximum rated nominal. External output capacitance is 1  $\mu$ F multilayer ceramic paralleled with 10  $\mu$ F electrolytic. All caps are low ESR. These capacitors are necessary for our test equipment and may not be needed in your application. Testing must be kept short enough that the converter does not appreciably heat up during testing. For extended testing, use plenty of airflow. See Derating Curves for temperature performance. All models are stable and regulate within spec without external capacitance.
2. Input Ripple Current is tested and specified over a 5-20 MHz bandwidth and uses a special set of external filters only for the Ripple Current specifications. Input filtering is  $C_{IN} = 33 \mu$ F,  $C_{BUS} = 220 \mu$ F,  $L_{BUS} = 12 \mu$ H. Use capacitor rated voltages which are twice the maximum expected voltage. Capacitors must accept high speed AC switching currents.
3. Mean Time Before Failure (MTBF) is calculated using the Telcordia (Belcore) SR-332 Method 1, Case 3, Issue 1, ground fixed conditions. Operating temperature = +30°C, full output load, natural air convection.
4. The On/Off Control is normally driven from a switch or relay. An open collector/open drain transistor may be used in saturation and cut-off (pinch-off) modes. External logic may also be used if voltage levels are fully compliant to the specifications.
5. Regulation specifications describe the deviation as the input line voltage or output load current is varied from a nominal midpoint value to either extreme (50% load).
6. Do not exceed maximum power ratings or output overvoltage when adjusting output trim values.
7. At zero output current,  $V_{out}$  may contain components which slightly exceed the ripple and noise specifications.
8. Output overload protection is non-latching. When the output overload is removed, the output will automatically recover.
9. The converter will shut off if the input falls below the undervoltage threshold. It will not restart until the input exceeds the Input Start Up Voltage.
10. Output noise may be further reduced by installing an external filter. See the Application Notes. Use only as much output filtering as needed *and no more*. Larger caps (especially low-ESR ceramic types) may slow transient response or degrade dynamic performance. Thoroughly test your application with all components installed.
11. If reverse polarity is accidentally applied to the input, to ensure reverse input protection with full output load, always connect an external fast blow input fuse in series with the + $V_{IN}$  input.
12. If remote sense is not used, connect it to its respective  $V_{out}$  terminal. Sense is included on IRS-3.3/15-Q48 and IRS-5/10-Q48 models only.

## STANDARDS COMPLIANCE

| Parameter                         | Notes  |
|-----------------------------------|--|
| EN 60950-1/A12:2011               | Basic insulation   |
| UL 60950-1/R:2011-12              |  |
| CAN/CSA-C22.2 No. 60950-1/A1:2011 |  |
| IEC 61000-4-2                     | ESD test, 8 kV - NP, 15 kV air - NP (Normal Performance) |


Note: An external input fuse must always be used to meet these safety requirements.

## ENVIRONMENTAL QUALIFICATION TESTING

| Parameter                                 | #Units | Test Conditions   |
|---|--------|---|
| Vibration                                 | 15     | EN 61373:1999 Category I, Class B, Body mounted   |
| Mechanical Shock                          | 15     | EN 61373:1999 Category I, Class B, Body mounted   |
| DMTBF(Life Test)                          | 60     | Vin nom , units at derating point,101days   |
| Temperature Cycling Test( TCT)            | 15     | -40 °C to 125 °C, unit temp. ramp 15 °C/min.,500cycles  |
| Power and Temperature Cycling Test (PTCT) | 5      | Temperature operating = min to max, Vin = min to max, Load=50% of rated maximum,100cycles   |
| Temperature ,Humidity and Bias(THB)       | 15     | 85 °C85RH,Vin=max, Load=min load,1072Hour(72hours with a pre-conditioning soak, unpowered)  |
| Damp heat test, cyclic                    | 15     | EN60068-2-30: Temperatures: + 55 °C and + 25 °C; Number of cycles: 2 (respiration effect); Time: 2 x 24 hours; Relative Humidity: 95% |
| Dry heat test                             | 5      | EN60068-2-2, Vin=nom line, Full load, 85°C for 6 hours.   |
| High Temperature Operating Bias(HTOB)     | 15     | Vin=min to max ,95% rated load, units at derating point,500hours  |
| Low Temperature operating                 | 5      | Vin=nom line, Full load,-40°C for 2 hours.  |
| Highly Accelerated Life Test(HALT)        | 5      | High temperature limits, low temperature limits, Vibration limits, Combined Environmental Tests.                                      |
| EMI                                       | 3      | Class A in CISPR 22 or IEC62236-3-2(GB/T 24338.4)   |
| ESD                                       | 3      | IEC 6100-4-2: +/-8kv contact discharge +/-15kv air discharge  |
| Surge Protection                          | 3      | EN50121-3-2   |

Note: Governing Standard BS EN 50155:2007 Railway applications - Electronics equipment used on rolling stock.

**MECHANICAL SPECIFICATIONS (STANDARD BASEPLATE OPTION)**



**NOTES:**

UNLESS OTHERWISE SPECIFIED;

- 1: ALL DIMENSION ARE IN INCHES[MILIMETER];
- 2: THE GAP (Max.0.1mm) AFTER POTTING BAKING BETWEEN AL CASE AND PLASTIC COVER IS ACCEPTABLE;
- 3: FOR COSMETIC SPECIFICATION AND PRODUCTION WORKMANSHIP STANDARD, PLS FOLLOW THE FILE No.60887;
- 4: ALL TOLERANCES:  
 $x.xx \text{in}, \pm 0.02 \text{in}(x.xx \text{mm}, \pm 0.5 \text{mm})$   
 $x.xxx \text{in}, \pm 0.01 \text{in}(x.xxx \text{mm}, \pm 0.25 \text{mm})$

**INPUT/OUTPUT CONNECTIONS P75**

| Pin | Function       | Pin | Function    |
|-----|----------------|-----|-------------|
| 3   | -Vin           | 4   | -Vout       |
|     |                | 5   | -Sense*     |
| 2   | On/Off Control | 6   | Output Trim |
|     |                | 7   | +Sense*     |
| 1   | +Vin           | 8   | +Vout       |

\* Sense is included only on models IRS-3.3/15-Q48 and IRS-5/10-Q48. Sense pins are omitted on other models.


Note that some competitive units may use different pin numbering or alternate outline views. However, all units are pinout compatible.

It is recommended that no parts be placed beneath the converter.

**Material:**

- $\varnothing .040$  Pins: copper alloy
- $\varnothing .062$  Pins: copper alloy
- Finish: (all pins)  
Gold (5u"min) over nickel (50u" min)


Dimensions are in inches (mm) shown for ref. only.



- Tolerances (unless otherwise specified):  
 $.XX \pm 0.02$  (0.5)  
 $.XXX \pm 0.010$  (0.25)  
 Angles  $\pm 1^\circ$

Components are shown for reference only and may vary between units.

**MECHANICAL SPECIFICATIONS(FLANGED BASEPLATE OPTION)**



**NOTES:**

UNLESS OTHERWISE SPECIFIED;

1: ALL DIMENSION ARE IN INCHES[MILIMETER];

2:THE GAP (Max.0.1mm) AFTER POTTING BAKING BETWEEN AL CASE AND PLASTIC COVER IS AC CEPTABLE;

3: FOR COSMETIC SPECIFICATION AND PRODUCTION WORKMANSHIP STANDARD, PLS FOLLOW THE FILE No.60887;

4: ALL TOLERANCES:

x.xxin, ±0.02in(x.xmm, ±0.5mm)

x.xxxin, ±0.01in(x.xxmm, ±0.25mm)

**INPUT/OUTPUT CONNECTIONS P75**

| Pin | Function       | Pin | Function    |
|-----|----------------|-----|-------------|
| 3   | -Vin           | 4   | -Vout       |
|     |                | 5   | -Sense*     |
| 2   | On/Off Control | 6   | Output Trim |
|     |                | 7   | +Sense*     |
| 1   | +Vin           | 8   | +Vout       |

\* Sense is included only on models IRS-3.3/15-Q48 and IRS-5/10-Q48. Sense pins are omitted on other models.

Note that some competitive units may use different pin numbering or alternate outline views. However, all units are pinout compatible.

It is recommended that no parts be placed beneath the converter.

**Material:**


Ø .040 Pins: copper alloy

Ø .062 Pins: copper alloy

Finish: (all pins)

Gold (5u"min) over nickel (50u" min)

Dimensions are in inches (mm) shown for ref. only.



Tolerances (unless otherwise specified):


.XX ± 0.02 (0.5)

.XXX ± 0.010 (0.25)

Angles ± 1°

Components are shown for reference only and may vary between units.


**MECHANICAL SPECIFICATIONS**



\*Sense is included only on models IRS-3.3/15-Q48. Sense pins are omitted on other models.


| INPUT/OUTPUT CONNECTIONS P75 |                |     |             |
|------------------------------|----------------|-----|-------------|
| Pin                          | Function       | Pin | Function    |
| 3                            | -Vin           | 4   | -Vout       |
|                              |                | 5   | -Sense*     |
| 2                            | On/Off Control | 6   | Output Trim |
|                              |                | 7   | +Sense*     |
| 1                            | +Vin           | 8   | +Vout       |

**SHIPPING TRAYS AND BOXES, THROUGH-HOLE MOUNT**




**SHIPPING TRAY DIMENSIONS**

**Material: Low density, closed cell polyethylene anti-static foam**



Dimensions are in millimeters.



Tolerances (unless otherwise specified):  
 .XX ± 0.5  
 .XXX ± 0.25  
 Angles ± 2°



**TECHNICAL NOTES**

**Input Fusing**

Certain applications and/or safety agencies may require the installation of fuses at the inputs of power conversion components. Fuses should also be used if the possibility of sustained, non-current-limited, input-voltage polarity reversals exists. For Murata Power Solutions IRS series DC-DC converters, we recommend the use of a fast blow fuse, installed in the ungrounded input supply line with a typical value about twice the maximum input current, calculated at low line with the converter's minimum efficiency.

All relevant national and international safety standards and regulations must be observed by the installer. For system safety agency approvals, the converters must be installed in compliance with the requirements of the end use safety standard, i.e. IEC/EN/UL60950-1.

**Input Reverse-Polarity Protection**

If the input voltage polarity is accidentally reversed, an internal diode will become forward biased and likely draw excessive current from the power source. If this source is not current limited or the circuit appropriately fused, it could cause permanent damage to the converter.

**Input Under-Voltage Shutdown and Start-Up Threshold**

Under normal start-up conditions, devices will not begin to regulate properly until the ramping-up input voltage exceeds the Start-Up Threshold Voltage. Once operating, devices will not turn off until the input voltage drops below the Under-Voltage Shutdown limit. Subsequent re-start will not occur until the input is brought back up to the Start-Up Threshold. This built in hysteresis prevents any unstable on/off situations from occurring at a single input voltage.

**Start-Up Time**

The  $V_{IN}$  to  $V_{OUT}$  Start-Up Time is the time interval between the point at which the ramping input voltage crosses the Start-Up Threshold and the fully loaded output voltage enters and remains within its specified accuracy band. Actual measured times will vary with input source impedance, external input capacitance, and the slew rate and final value of the input voltage as it appears at the converter. The IRS Series implements a soft start circuit to limit the duty cycle of its PWM controller at power up, thereby limiting the input inrush current.

The On/Off Control to  $V_{OUT}$  start-up time assumes the converter has its nominal input voltage applied but is turned off via the On/Off Control pin. The specification defines the interval between the point at which the converter is turned on (released) and the fully loaded output voltage enters and remains within its specified accuracy band. Similar to the  $V_{IN}$  to  $V_{OUT}$  start-up, the On/Off Control to  $V_{OUT}$  start-up time is also governed by the internal soft start circuitry and external load capacitance. The difference in start up time from  $V_{IN}$  to  $V_{OUT}$  and from On/Off Control to  $V_{OUT}$  is therefore insignificant.

**Input Source Impedance**

The input of IRS converters must be driven from a low ac-impedance source. The DC-DC's performance and stability can be compromised by the use of highly inductive source impedances. The input circuit shown in Figure 2 is a practical solution that can be used to minimize the effects of inductance in the input traces. For optimum performance, components should be mounted close to the DC-DC converter.

**Transient and Surge Protection**

The input range of the IRS Q48 modules cover EN50155 requirements for Brownout and Transient conditions with Nominal input voltages of 37.5V & 48Vdc.

| EN50155 standard |   |  |                                      |
|------------------|---|--|--------------------------------------|
| Nominal Input    | Permanent input range<br>(0.7 - 1.25 $V_{in}$ ) | Brownout<br>100ms<br>(0.6 x $V_{in}$ ) | Transient<br>1s<br>(1.4 x $V_{in}$ ) |
| 37.5V            | 26 - 47V  | 22.5V                                  | 52.5V                                |
| 48V              | 33.6 - 60V                                      | 28.8V                                  | 67.2V                                |

**I/O Filtering, Input Ripple Current, and Output Noise**

All models in the IRS Series are tested/specified for input reflected ripple current and output noise using the specified external input/output components/circuits and layout as shown in the following two figures. External input capacitors ( $C_{IN}$  in Figure 2) serve primarily as energy-storage elements, minimizing line voltage variations caused by transient IR drops in conductors from backplane to the DC-DC. Input caps should be selected for bulk capacitance (at appropriate frequencies), low ESR, and high rms-ripple-current ratings. The switching nature of DC-DC converters requires that dc voltage sources have low ac impedance as highly inductive source impedance can affect system sta-





Figure 2. Measuring Input Ripple Current

bility. In Figure 2,  $C_{BUS}$  and  $L_{BUS}$  simulate a typical dc voltage bus. Your specific system configuration may necessitate additional considerations.

In critical applications, output ripple/noise (also referred to as periodic and random deviations or PARD) may be reduced below specified limits using filtering techniques, the simplest of which is the installation of additional external output capacitors. They function as true filter elements and should be selected for bulk capacitance, low ESR and appropriate frequency response.

All external capacitors should have appropriate voltage ratings and be located as close to the converter as possible. Temperature variations for all relevant parameters should also be taken carefully into consideration. The most effective combination of external I/O capacitors will be a function of line voltage and source impedance, as well as particular load and layout conditions.



C1 = 1µF  
C2 = 10µF  
LOAD 2-3 INCHES (51-76mm) FROM MODULE  
Figure 3. Measuring Output Ripple/Noise (PARD)

**Floating Outputs**

Since these are isolated DC-DC converters, their outputs are “floating” with respect to their input. Designers will normally use the –Output as the ground/return of the load circuit. You can however, use the +Output as ground/return to effectively reverse the output polarity.

**Minimum Output Loading Requirements**

IRS converters employ a synchronous-rectifier design topology and all models regulate within spec and are stable under no-load to full load conditions. Operation under no-load conditions however might slightly increase the output ripple and noise.

**Thermal Shutdown**

The IRS converters are equipped with thermal-shutdown circuitry. If environmental conditions cause the temperature of the DC-DC converter to rise above the designed operating temperature, a precision temperature sensor will power down the unit. When the internal temperature decreases below the threshold of the temperature sensor, the unit will self start. See Performance/Functional Specifications.

**Output Over-Voltage Protection**

The IRS output voltage is monitored for an over-voltage condition using a comparator. The signal is optically coupled to the primary side and if the output voltage rises to a level which could be damaging to the load, the sensing circuitry will power down the PWM controller causing the output voltage to decrease. Following a time-out period the PWM will restart, causing the output voltage to ramp to its appropriate value. If the fault condition persists, and the output voltage again climbs to excessive levels, the over-voltage circuitry will initiate another shutdown cycle. This on/off cycling is referred to as “hiccup” mode.

**Short Circuit Condition**

When a converter is in current-limit mode, the output voltage will drop as the output current demand increases. If the output voltage drops too low, the magnetically coupled voltage used to develop primary side voltages will also drop, thereby shutting down the PWM controller. Following a time-out period, the PWM will restart causing the output voltage to begin ramping to their appropriate value. If the short-circuit condition persists, another shutdown cycle will be initiated. This on/off cycling is referred to as “hiccup” mode. The hiccup cycling reduces the average output current, thereby preventing internal temperatures from rising to excessive levels. The IRS Series is capable of enduring an indefinite short circuit output condition.

**Current Limiting**

As soon as the output current increases to approximately 130% of its rated value, the DC-DC converter will go into a current-limiting mode. In this condition, the output voltage will decrease proportionately with increases in output current, thereby maintaining somewhat constant power dissipation. This is commonly referred to as power limiting. Current limit inception is defined as the point at which the full-power output voltage falls below the specified tolerance. See Performance/Functional Specifications. If the load current, being drawn from the converter, is significant enough, the unit will go into a short circuit condition as described below.

**Remote Sense (models IRS-3.3/15-Q48 and IRS-5/10-Q48 only)**

**Note:** The Sense and V<sub>OUT</sub> lines are internally connected through low-value resistors. Nevertheless, if the sense function is not used for remote regulation the user should connect the +Sense to +V<sub>OUT</sub> and –Sense to –V<sub>OUT</sub> at the DC-DC converter pins. IRS series converters employ a sense feature to provide point of use regulation, thereby overcoming moderate IR drops in PCB conductors or cabling. The remote sense lines carry very little current and therefore require minimal cross-sectional-area conductors. The sense lines, which are capacitively coupled to their respective output lines, are used by the feedback control-loop to regulate the output. As such, they are not low impedance points and must be treated with care in layouts and cabling. Sense lines on a PCB should be run adjacent to dc signals, preferably ground.

$$[V_{OUT(+)} - V_{OUT(-)}] - [Sense(+) - Sense(-)] \leq 10\% V_{OUT}$$

In cables and discrete wiring applications, twisted pair or other techniques should be used. Output over-voltage protection is monitored at the output voltage pin, not the Sense pin. Therefore, excessive voltage differences between V<sub>OUT</sub> and Sense in conjunction with trim adjustment of the output voltage can cause the over-voltage protection circuitry to activate (see Performance Specifications for over-voltage limits). Power derating is based on maximum output current and voltage at the converter’s output pins. Use of trim and sense functions can cause output voltages to increase, thereby increasing output power beyond the converter’s specified rating, or cause output voltages to climb into the output over-voltage region. Therefore, the designer must ensure:

$$(V_{OUT \text{ at pins}}) \times (I_{OUT}) \leq \text{rated output power}$$




Figure 4. Remote Sense Circuit Configuration  
Sense is included only on models IRS-3.3/15-Q48 and IRS-5/10-Q48.

**On/Off Control**

The input-side, remote On/Off Control function can be ordered to operate with either logic type:

**Positive** ("P" suffix) logic models are enabled when the On/Off pin is left open or is pulled high (see specifications) with respect to the -Input as per Figure 4. Positive-logic devices are disabled when the on/off pin is pulled low with respect to the -Input.

**Negative** ("N" suffix) logic devices are off when the On/Off pin is left open or is pulled high (see specifications), and on when the pin is pulled low with respect to the -Input. See specifications.

Dynamic control of the remote on/off function is best accomplished with a mechanical relay or an open-collector/open-drain drive circuit (optically isolated if appropriate). The drive circuit should be able to sink appropriate current (see Performance Specifications) when activated and withstand appropriate voltage when deactivated. Applying an external voltage to pin 2 when no input power is applied to the converter can cause permanent damage to the converter.




Figure 5. Driving the Negative Logic On/Off Control Pin (simplified circuit)

**Trim Equations**

**Trim Down**

$$R_{T\_DOWN} (k\Omega) = \frac{511}{\Delta\%} - 10.22$$

$$\text{Where } \Delta\% = \left( \left( \frac{V_{NOM} - V_{DES}}{V_{NOM}} \times 100 \right) \right)$$

**Trim Up**

$$R_{T\_UP} (k\Omega) = \frac{5.11 \times V_{NOM} \times (100 + \Delta\%)}{1.225 \times \Delta\%} - \frac{511}{\Delta\%} - 10.22$$

**Note:** "Δ%" is always a positive value.  
 "V<sub>NOM</sub>" is the nominal, rated output voltage.  
 "V<sub>DES</sub>" is the desired, changed output voltage.

**OUTPUT VOLTAGE ADJUSTMENT**




Figure 6. Trim Connections To Increase Output Voltages




Figure 7. Trim Connections To Decrease Output Voltages

Sense is included on IRS-3.3/15-D48 and IRS-5/10-Q48. Connect Trim to the respective Vout pin if sense is not installed.

Encapsulated Sixteenth-Brick DOSA-Compatible,  
Wide Input Isolated DC-DC Converters

**Vertical Wind Tunnel**

Murata Power Solutions employs a computer controlled custom-designed closed loop vertical wind tunnel, infrared video camera system, and test instrumentation for accurate airflow and heat dissipation analysis of power products. The system includes a precision low flow-rate anemometer, variable speed fan, power supply input and load controls, temperature gauges, and adjustable heating element.

The IR camera monitors the thermal performance of the Unit Under Test (UUT) under static steady-state conditions. A special optical port is used which is transparent to infrared wavelengths.

Both through-hole and surface mount converters are soldered down to a 10" x 10" host carrier board for realistic heat absorption and spreading. Both longitudinal and transverse airflow studies are possible by rotation of this carrier board since there are often significant differences in the heat dissipation in the two airflow directions. The combination of adjustable airflow, adjustable ambient heat, and adjustable Input/Output currents and voltages mean that a very wide range of measurement conditions can be studied.

The collimator reduces the amount of turbulence adjacent to the UUT by minimizing airflow turbulence. Such turbulence influences the effective heat transfer characteristics and gives false readings. Excess turbulence removes more heat from some surfaces and less heat from others, possibly causing uneven overheating.

Both sides of the UUT are studied since there are different thermal gradients on each side. The adjustable heating element and fan, built-in temperature gauges, and no-contact IR camera mean that power supplies are tested in real-world conditions.




Figure 8. Vertical Wind Tunnel

**Through-hole Soldering Guidelines**

Murata Power Solutions recommends the TH soldering specifications below when installing these converters. These specifications vary depending on the solder type. Exceeding these specifications may cause damage to the product. Your production environment may differ; therefore please thoroughly review these guidelines with your process engineers.

| Wave Solder Operations for through-hole mounted products (THMT) |           |
|---|-----------|
| <b>For Sn/Ag/Cu based solders:</b>                              |           |
| Maximum Preheat Temperature                                     | 115° C.   |
| Maximum Pot Temperature   | 270° C.   |
| Maximum Solder Dwell Time                                       | 7 seconds |
| <b>For Sn/Pb based solders:</b>                                 |           |
| Maximum Preheat Temperature                                     | 105° C.   |
| Maximum Pot Temperature   | 250° C.   |
| Maximum Solder Dwell Time                                       | 6 seconds |

Murata Power Solutions, Inc.  
129 Flanders Rd, Westborough, MA 01581 USA  
ISO 9001 and 14001 REGISTERED



**This product is subject to the following operating requirements and the Life and Safety Critical Application Sales Policy:  
Refer to: <http://www.murata-ps.com/requirements/>**

Murata Power Solutions, Inc. makes no representation that the use of its products in the circuits described herein, or the use of other technical information contained herein, will not infringe upon existing or future patent rights. The descriptions contained herein do not imply the granting of licenses to make, use, or sell equipment constructed in accordance therewith. Specifications are subject to change without notice. © 2018 Murata Power Solutions, Inc.