

Part Number: C0533A

Revision Level: 1

Date: 7/11/2007

6C 28 7/36 TC FMPP OAS BRAID PVC

LO-CAP COMPUTER CABLE

A. CONSTRUCTION

Conductor:	#28 AWG 7/36 Tinned Copper	0.015" nom.
Insulation:	0.016" Wall Foamed Polypropylene	0.047" nom.
Cable:	6 Conductors cabled LHL - Aluminum/polyester (Foil Out) - #28 7/36 TC D.W.	0.146" nom.
Braid	Tinned Copper Braid 70% nom. Coverage	0.168" nom.
Jacket:	0.032" Polyvinyl Chloride	0.232" +/- 0.012"
Print Legend:	CAROL (R) 28 AWG--C0533A--75C E60233-8 (UL) CL2 OR AWM STYLE 2919 LOW VOLTAGE COMPUTER CABLE ---CSA LL69381 CMH (DATE CODE) (PRINTED EVERY 2 FEET)	

DIAMETERS

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 13	Type CL2
UL Standard 758	AWM Style 2919
CSA International	Type CMH

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C (CL2) / 60C (CMH) / 80C (AWM)
SUGGESTED WORKING VOLTAGE (V _{rms}):	300 V _{rms}
CONDUCTOR D.C. RESISTANCE:	67.5 Ohms/1000 ft nom
SHIELD RESISTANCE:	6.2 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	9.0 pF/ft @ 1kHz nom
GROUND CAPACITANCE:	16.0 pF/ft @ 1kHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White
3	Red
4	Lt. Green
5	Brown
6	Lt. Blue