

DRJ30-12-1/E New Product



<b>Sales Region</b>	Worldwide
<b>Series</b>	DRJ
<b>Status</b>	Production
<b>Feature</b>	DIN rail installation compatible
<b>Option</b>	European terminal type
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Input Voltage Range[AC]	85 to 264V
Input Voltage Range[DC]	120 to 370V
Efficiency	85.5% Typ.
Rated Output Voltage[DC]	12V
Output Voltage Range[DC]	10.8 to 15V
Maximum Output Current	2.3A
Maximum Output Power	27.6W

### Cases Shape & Size

Case shape	DIN rail
Width(W)	21.5mm Nom.
Height(H)	75mm Nom.
Depth(D)	90mm Nom.
Weight	120g Typ.

### Other

Operating Temp. Range	-20 to 70°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	CSA C22.2 No.107.1
	EN60950-1
Safety Standard(Conformed)	UL508
	Den-an Appendix 8 at 100VAC only
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.