



TECHNICAL CHARACTERISTICS

MATERIAL  
 FLAMMABILITY RATING: UL94-V0  
 COLOR: BLACK  
 CONTACT MATERIAL: BRONZE  
 CONTACT PLATING: GOLD  
 QUALITY CLASS: 1 500 MATING CYCLES

ELECTRICAL  
 CURRENT RATING: 0.5 A  
 CONTACT RESISTANCE: 5 Ω MAX

PACKAGING  
 BAG

P1 USB 3.1 C MALE			P2 MICRO USB 2.0 MALE	
PIN	SIGNAL NAME	WIRE COLOR	PIN	SIGNAL NAME
A1,B1, A12,B12	GND	BLACK	5	GND
A4,B4, A9,B9	VBUS	RED	1	VBUS
A5	CC	-	-	-
B5	VCONN	-	-	-
A6	Dp1	GREEN	3	D+
A7	Dn1	WHITE	2	D-
-	-	-	4	ID
SHELL	SHIELD	BRAID	SHELL	SHIELD

RoHS Compliant			
G			
F			
E			
D			
C			
B	21-OCT-15	ELECTRICAL	AK
A	18-JUN-15	PDF	AK
REV	DATE	FILE	BY

PROJECTION:	
APPROVAL: NPr	

GENERAL TOLERANCE
.X = $\pm$ 0.2
.XX = $\pm$ 0.15
UNIT: MM
SCALE:
SHEET: 1/2
DRAW: AK

DESCRIPTION: CABLE USB 3.1 C MALE TO MICRO USB 2.0 MALE	
WERI PART NO: 632 910 731 611	

SIZE
<b>A4</b>

A  
B  
C  
D

1

2

3

4

5

## Cautions and Warnings:

This electronic component is designed and developed with the intention for use in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Würth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

A

B

C

RoHS Compliant

G				PROJECTION: 	GENERAL TOLERANCE .X = +/- 0.2 .XX = +/- 0.15		
F							
E							
D							
C				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE <b>A4</b>
B					SCALE:		
A	10-SEP-14	PDF	QL		SHEET: 2/2	WERI PART NO: DISCLAIMER	
REV	DATE	FILE	BY		DRAW: QL		

D