

CGL 1.5K SERIES PURE SINEWAVE INVERTER 1500W / 2000VA

12, 24, or 48VDC

120V 50/60 HZ or 220V 50/60HZ Output



APPLICATIONS

Nova Electric's CGL-Series inverters are intended for commercial and industrial applications wherever pure sinewave power is needed at 50 or 60 Hz.

These inverters are ideal for running electronic loads such as computers, monitors, printers, telecom systems, radios, fluorescent lamps from batteries, field generators, and solar electro-voltaic panels. They can also drive hand drills, motors and small compressors – please consult the factory for proper sizing.

These CGL models can also be optionally ruggedized against shock, vibration, and humidity for military applications including vehicle mounted, shipboard, submarine, aircraft, and ground fixed shelters.

- Computers
- Monitors
- Printers
- Electric Tools
- RVs
- Sail Boats
- Photo Voltaic
- Instruments
- Appliances
- Military



NOVA ELECTRIC
www.novaelectric.com
novasales@theallpower.com

AS 9100
BUREAU VERITAS
Certification
Certificate No. 12006247-1



A Leader in Inverter Technology since 1966 - 500VA to 500+KVA

CGL-SERIES PURE SINE WAVE DC-AC INVERTER

SPECIFICATIONS

FEATURES

- True sinewave output
- THD < 3%
- RS232 interface
- CR5 Remote control optional
- Input and output fully isolated
- Thermostat controlled cooling fan
- Advanced microprocessor control
- Output voltage switch selectable
- Output frequency 50/60 Hz switch selectable
- "Power Saver" mode for energy conservation
- Front panel LED meters and alarms
- CE approved

ELECTRICAL

Input Voltage: 12, 24 or 48VDC
 Output Voltage 110V models: 100/110/120 VAC
 Output Voltage 230V models: 220/230/240 VAC
 Rated Power: 1500W
 Surge Power: 2000W
 Frequency: 50 or 60 HZ switch selectable
 AC Regulation: +/- 3%
 Std. Receptacles 110V models: NEMA5-15r
 Std. Receptacles 220V models: Schuko
 Led Indicators: OVP, UVP, OTP, input voltage level, output load level, and fault status

ENVIRONMENTAL

Operating Temp: -20° to +50°C
 Storage Temp Range: -40° to +71°C
 Humidity: to 95% non condensing

SAFETY & EMC

Safety Standards: UL458
 (with optional GFCI outlet only)
 Isolation Resistance: I/P - O/P: 100M Ohms / 500VDC

FOR 110V Models

EMI Conduction and Radiation:
 Compliance to FCC class A

FOR 230V Models

EMI Conduction and Radiation:
 Compliance to EN55022 class A
 EMS Immunity: Compliance to EN61000-3-2,3

LVD: Compliance to EN60950-1
 e-MARK: Compliance to e-13 *
 72/245/EEC, 95/54/EC


PROTECTIVE FEATURES

- Input reverse polarity
- Undervoltage
- Overvoltage
- Output short circuit
- Overload
- Overtemperature

MODEL SELECTION

| | CGL1.5KVA-12-120 | CGL1.5KVA-24-120 | CGL1.5KVA-48-120 | CGL1.5KVA-12-220 | CGL1.5KVA-24-220 | CGL1.5KVA-48-220 |
|----------------------|-----------------------|------------------|------------------|------------------|------------------|------------------|
| DC Voltage | 12VDC | 24VDC | 48VDC | 12VDC | 24VDC | 48VDC |
| Voltage Range | 10.5~15.0VDC | 21.0~30.0VDC | 42.0~60.0VDC | 10.5~15.0VDC | 21.0~30.0VDC | 42.0~60.0VDC |
| Efficiency (Typ.) | 87.0% | 90.0% | 92.0% | 90.0% | 93.0% | 94.0% |
| Low VDC Alarm | 11VDC | 22VDC | 44VDC | 11VDC | 22VDC | 44VDC |
| Low VDC Shutdown | 10.5VDC | 21.0VDC | 42.0VDC | 10.5VDC | 21.0VDC | 42.0VDC |
| Over Voltage | 15.3VDC | 30.6VDC | 61.2VDC | 15.3VDC | 30.6VDC | 61.2VDC |
| No Load Current draw | 0.87A | 0.43A | 0.23A | 0.83A | 0.43A | 0.22A |
| Weight | 15.5 pounds / 7.0 Kg. | | | | | |

MECHANICAL SPECIFICATIONS



WEB : www.novaelectric.com

E-Mail : novasales@theallpower.com

PHONE : (201) 385-0500 FAX : (201) 385-0702



NOVA ELECTRIC

A Division of

TECHNOLOGY DYNAMICS, INC.

100 School St., Bergenfield NJ 07621

