



HWS30A-15/MEA

| Sales Region | Worldwide |
|------------------------|--|
| Series | HWS-A/ME |
| Status | Production |
| Feature | Medical for Medical instruments |
| Option | With cover type |
| | Approved by safety standards for medical equipment |
| Option Lineup | Please refer to here. |
| Recommended EMC Filter | Please refer to here. |
| Accessories | Please refer to the catalog |



| | Electrical Characteristics | |
|--------------------------|----------------------------|--|
| Input Voltage Range[AC] | 85 to 265V | |
| Input Voltage Range[DC] | 120 to 370V | |
| Efficiency | 87% Тур. | |
| Rated Output Voltage[DC] | 15V | |
| Output Voltage Range[DC] | 12 to 18V | |
| Maximum Output Current | 2A | |
| Maximum Output Power | 30W | |

| Cases Shape & Size | | |
|--------------------|-------------|--|
| Case'] shape | Unit | |
| Width(W) | 31.5mm Nom. | |
| Height(H) | 82mm Nom. | |
| Depth(D) | 95mm Nom. | |
| Weight | 240g Typ. | |

| Other | | |
|----------------------------|--|--|
| Operating Temp. Range | -10 to 70°C | |
| Cooling | Convection cooling | |
| | ES60601-1 | |
| Safety Standard(Certified) | EN60601-1 | |
| | CSA-C22.2 No.60101-1 | |
| Safety Standard(Conformed) | | |
| Remarks | This page only shows representative characteristics. Please refer to the | |
| Refildiks | technical data for detailed specifications and conditions. | |

! Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.