


CC3-0512DS-E



<b>Sales Region</b>	Worldwide
<b>Series</b>	CC-E
<b>Status</b>	 Production
<b>Option</b>	SIP type
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Rated Input Voltage[DC]	5V
Input Voltage Range[DC]	4.5 to 9V
Efficiency	81% Typ.
Rated Output Voltage[DC]	<u>+12V</u> <u>-12V</u>
Output Voltage Range[DC]	<u>+11.4 to +15V</u> <u>-11.4 to -15V</u>
Maximum Output Current	<u>0.125A</u> <u>0.125A</u>
Maximum Ripple Noise	<u>120mV</u> <u>120mV</u>
Maximum Output Power	3W
Withstanding Voltage1	Input - Case: 500VAC: 1min.
Withstanding Voltage2	Input - Output: 500VAC: 1min.
Withstanding Voltage3	Output - Case: 500VAC: 1min.

### Cases Shape & Size

Case'□' shape	On board/Power module
Width(W)	27.8mm Nom.
Height(H)	17.9mm Nom.
Depth(D)	9.2mm Nom.
Weight	7g Typ.
Industry Standard Size	
Terminal Style	SIP

### Other

Operating Temp. Range	-40 to 85°C
Isolated / Non-isolated	Isolated
Feature	
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 (C-UL) EN60950-1 (NEMKO)
Safety Standard(Conformed)	

