

CW INDUSTRIES130 James Way
Southampton, PA 18966

Phone: 215-355-7080 • Fax: 215-355-1088



Email: info@cwind.com • Website: <http://www.cwind.com>**Item # GRB258101BB, GRB Series Full Size Sealed Rocker Switches**

[Check Distributor Stock](#) · [Specifications](#) · [Materials](#) · [Technical Information](#)

Check Distributor Stock

Check Distributor Stock	DIGI-KEY MOUSER
-------------------------	--

Specifications

Circuitry	SPDT
Switch Function	(ON)-OFF-(ON)
Electrical Ratings	10 A @ 24 VAC 10 A @ 250 VAC 20 A @ 125 VAC 20 A @ 14 VAC 3/4 HP @ 125 VAC 3/4 HP @ 250 VAC
IP Level	56
Mounting	38.6 x 15.3
Actuator Color	Black
Housing Color	Black
C1	N
Polarization	N
Actuator Legend	None
Illumination	Non Illuminated
Terminal	0.250 Quick Connect (SQ)
Fitting	Snap-In
Options	 <p>Reference Lamp Chart larger image</p>
Optional Connector	Not Available
Compliance	

Materials

Frame Material	Nylon (UL: 94V-2)
Actuator Material	Nylon (UL: 94V-2) PC (UL: 94V-2)
Terminal Material	Copper Alloy Silver Plated

Technical Information

Operating Temperature	-20 to 85 °C
Maximum Contact Resistance	50m ohm
Minimum Insulation Resistance	DC 500VM 100M OHM
Dielectric Strength (AC) (1 Minute)	1500 °C
Mechanical Life	> 100,000 Cycles
Maximum Solderability of Terminals (Per 3 Seconds)	350 °C