

4桁LED数字表示

4 Digits LED Numeric Displays

Ta=25℃

機種名 Type No.		外觀 結線圖 Drawing	波長 Peak Wave-length	絕對最大定格 Absolute Maximum Ratings					推奨動作電流 If/seg Recommend.	電氣的 Optical 的特性 Electro-Optical Characteristics				
Com.-Anode	Com.-Cathode	No.	nm (Color)	If/seg mA	I _{FP} /seg mA	V _R /seg V	P _D W	T _{opr} ℃	If/seg mA	V _f Typ. V	I _F mA	Luminous Intensity Typ μcd	I _F mA	I _R Max. (V _R =3V) μA
SL 1405-20	SL 1406-20	L-25	700 (R)	15	60	3	1.0	-25~65	5~10	1.9	5	150	5	10
SL 2405-20	SL 2406-20	L-25	565 (G)	20	80	3	1.4	-25~65	10~15	2.05	15	200	15	10
SL-1435	SL-1436	L-26	700 (R)	15	-	3	1.0	-25~70	5~10	1.9	5	220	5	10
SL-2435	SL-2436	L-26	565 (G)	20	-	3	1.3	-25~65	10~15	2.05	15	370	15	10
SL-1435-01	SL-1436-01	L-27	700 (R)	15	50	3	0.9	-25~70	5~10	1.9	5	220	5	10
SL-2435-01	SL-2436-01	L-27	565 (G)	20	60	3	1.3	-25~65	10~15	2.05	15	370	15	10
	SL-1064-20	L 28	700 (R)	15	70	3	1.2	-25~75	5~10	1.9	5	180	5	10
	SL-2064-20K	L 28	565 (G)	20	90	3	1.7	-25~75	8~12	2.05	15	240	15	10

Tolerance ±0.25
Unit : mm

