
UTC 2SD468 NPN EPITAXI

NPN EPITAXIAL SILICON TRANSISTOR

LOW FREQUENCY POWER AMPLIFIER

FEATURES

*Low frequency power amplifier *Complement to 2SB562



1:EMITTER 2:COLLECTOR 3:BASE

ABSOLUTE MAXIMUM RATINGS (Ta=25°C, unless otherwise specified)

PARAMETER	SYMBOL	VALUE	UNIT		
Collector-Base Voltage	Vсво	25	V		
Collector-Emitter Voltage	VCEO	20	V		
Emitter-Base Voltage	Vebo	5	V		
Collector Current	lc	1	А		
Collector Peak Current	lc(peak)	1.5	А		
Collector Power Dissipation	Pc	0.9	W		
Junction Temperature	Tj	150	°C		
Storage Temperature	Tstg	-55 ~ +150	°C		

ELECTRICAL CHARACTERISTICS (Ta=25°C, unless otherwise specified)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
V(BR)CBO	Ic=10μΑ, IE=0	25			V
V(BR)CEO	lc=1mA, RBE=∞	20			V
V(BR)EBO	IE=10μA, IC=0	5			V
Ісво	VCB=20V, IE=0			1	μA
hFE	VCE=2V, Ic=0.5A (note)	85		240	
VCE(sat)	Ic=0.8A, IB=0.08A (note)		0.2	0.5	V
VBE	VCE=2V, Ic=0.5A (note)		0.79	1	V
fт	VCE=2V, Ic=0.5A (note)		190		MHz
Cob	VCB=10V, IE=0, f=1MHz		22		рF
	V(BR)CBO V(BR)CEO V(BR)EBO ICBO hFE VCE(sat) VBE fT	V(BR)CBO Ic=10µA, IE=0 V(BR)CEO Ic=1mA, RBE=∞ V(BR)EBO IE=10µA, IC=0 ICBO VCB=20V, IE=0 hFE VCE=2V, Ic=0.5A (note) VCE(sat) Ic=0.8A, IB=0.08A (note) VBE VCE=2V, Ic=0.5A (note) fT VCE=2V, Ic=0.5A (note)	V(BR)CBO Ic=10µA, IE=0 25 V(BR)CEO Ic=1mA, RBE=∞ 20 V(BR)EBO IE=10µA, IC=0 5 ICBO VCB=20V, IE=0 5 hFE VCE=2V, IC=0.5A (note) 85 VCE(sat) IC=0.8A, IB=0.08A (note) 5 VBE VCE=2V, Ic=0.5A (note) 5	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	$\begin{array}{c c c c c c c c c c c c c c c c c c c $

Note: Pulse test

UTC UNISONIC TECHNOLOGIES CO. LTD

QW-R201-050,A


1

UTC 2SD 468 NPN EPITAXIAL SILICON TRANSISTOR

CLASSIFICATION OF hFE

RANK	В	С
RANGE	85 - 170	120 - 240

TYPICAL PERFORMANCE CHARACTERISTICS




UTC UNISONIC TECHNOLOGIES CO. LTD 2


QW-R201-050,A

UTC 2SD468

NPN EPITAXIAL SILICON TRANSISTOR



Collector Output Capacitance vs. Collector to Base Voltage



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.

UTC UNISONIC TECHNOLOGIES CO. LTD 3

QW-R201-050,A