### **CPT 18-6037**

# **Temperature Compensated Power Amplifier**

6 GHz - 18 GHz

This Power Amplifier offers exceptional performance over the band 6 GHz to 18 GHz with 30 dBm P1dB output power and 32 dB Gain.

Teledyne Microwave amplifiers are balanced or feedback designs and manufactured with the latest MIC & MMIC technology. The GaAs FET's used in these amplifiers are well established proven devices from multiple sources.

Teledyne Microwave offers a complete line of Narrow and broadband Amplifiers covering the frequency range 500 MHz to 40 GHz. These products are available in either connectorized packages or as modules. For a complete list of these products and more, please visit our website.

Other products from Teledyne Microwave include: Transceivers, Synthesizers, and YIG Products



#### Specifications:

Model Number: CPT 18-6037 Frequency Range: 6 GHz - 18 GHz

Gain (min): 32 dB

Gain Vs Temp at any Frequency: +/-1.25 dB

Noise Figure (max): 12 dB

Output Power @ 1dB Compression: 30 dBm Gain Flatness Vs Frequency: +/-1.75 dB

3<sup>rd</sup> Order Intercept (Typ): 36 dBm

Power Supply:

Input Voltage: 11.5 to 15 VDC Current @ 12 VDC (typ): 3600 mA

Current @ 12 VDC (max): Contact Factory

Case Type (See attached Outline): HPX10


Temperature Range: -54 to +90C



ISO 9001:2000

## **CPT 18-6037**

# Temperature Compensated Power Amplifier 6 GHz - 18 GHz





ISO 9001:2000

1274 Terra Bella Avenue, Mountain View, CA 94043 • PHN# 800.832.6869 or +1.650.962.6944 • FAX# 650.962.6845 www.teledynemicrowave.com • microwave@teledyne.com