


## DESCRIPTION

MSB68DA-X is an ultra high brightness output red GaAlAs LED lamp encapsulated in a 4.95mmx4.95mm rectangular package with red diffused lens. 6 brightness grouping is provided for customer's selection.



- All dimension in mm (inch)
- No Scale
- Tol. : +/-0.3mm

## ABSOLUTE MAXIMUM RATINGS

Power Dissipation @ Ta=25°C	100mW
Forward Current, DC (IF)	40mA
Reverse Voltage	5V
Operating & Storage Temperature Range	-55 to +100°C
Lead Soldering Temperature (1/16" from body)	260°C for 5 sec.

## ELECTRO-OPTICAL CHARACTERISTI (Ta=25°C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	CONDITIONS
Forward Voltage	VF		1.8	2.4	V	IF=20mA
Reverse Breakdown Voltage	BVR	5			V	IR=100μA
Luminous Intensity	IV				mcd	IF=20mA
	-0	2.5	4.0			
	-1	4.0	6.0		mcd	IF=20mA
	-2	6.0	9.0		mcd	IF=20mA
	-3	9.0	13		mcd	IF=20mA
	-4	13	18		mcd	IF=20mA
	-5	18	24		mcd	IF=20mA
Peak Wavelength	λp		660		nm	IF=20mA
Spectral Line Half Width	Δλ		20		nm	IF=20mA
Viewing Angle	2θ 1/2		180		degree	IF=20mA



**MICRO ELECTRONICS LTD.**

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.

Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex:43510 Micro Hx. Tel: 2343 0181-5

Apr-99