



SANYO Semiconductors

DATA SHEET

15GN03SA

 — NPN Epitaxial Planar Silicon Transistor
VHF High-frequency Amplifier Applications

Applications

- VHF, RF, MIXER, OSC, IF amplifier.

Features

- High cut-off frequency : $f_T=1.5\text{GHz}$ typ.
- High gain : $|S_{21e}|^2=13\text{dB}$ typ ($f=0.4\text{GHz}$).
- Ultrasmall package permitting applied sets to be small and slim.

Specifications

Absolute Maximum Ratings at $T_a=25^\circ\text{C}$

Parameter	Symbol	Conditions	Ratings	Unit
Collector-to-Base Voltage	VCBO		20	V
Collector-to-Emitter Voltage	VCEO		10	V
Emitter-to-Base Voltage	VEBO		3	V
Collector Current	IC		70	mA
Collector Dissipation	PC		100	mW
Junction Temperature	Tj		150	°C
Storage Temperature	Tstg		-55 to +150	°C

Electrical Characteristics at $T_a=25^\circ\text{C}$

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Collector Cutoff Current	ICBO	$V_{CB}=10\text{V}, I_E=0\text{A}$			0.1	μA
Emitter Cutoff Current	IEBO	$V_{EB}=2\text{V}, I_C=0\text{A}$			1	μA
DC Current Gain	hFE	$V_{CE}=5\text{V}, I_C=10\text{mA}$	100		180	
Gain-Bandwidth Product	f_T	$V_{CE}=5\text{V}, I_C=20\text{mA}$	1.0	1.5		GHz

Marking : ZC

Continued on next page.

■ Any and all SANYO Semiconductor Co.,Ltd. products described or contained herein are, with regard to "standard application", intended for the use as general electronics equipment (home appliances, AV equipment, communication device, office equipment, industrial equipment etc.). The products mentioned herein shall not be intended for use for any "special application" (medical equipment whose purpose is to sustain life, aerospace instrument, nuclear control device, burning appliances, transportation machine, traffic signal system, safety equipment etc.) that shall require extremely high level of reliability and can directly threaten human lives in case of failure or malfunction of the product or may cause harm to human bodies, nor shall they grant any guarantee thereof. If you should intend to use our products for applications outside the standard applications of our customer who is considering such use and/or outside the scope of our intended standard applications, please consult with us prior to the intended use. If there is no consultation or inquiry before the intended use, our customer shall be solely responsible for the use.

■ Specifications of any and all SANYO Semiconductor Co.,Ltd. products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

15GN03SA






Continued from preceding page.

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Output Capacitance	Cob	V _{CB} =10V, f=1MHz		0.9	1.2	pF
Reverse Transfer Capacitance	Cre	V _{CB} =10V, f=1MHz		0.6		pF
Forward Transfer Gain	S _{21e} ²	V _{CE} =5V, I _C =20mA, f=0.4GHz	10	13		dB
Noise Figure	NF	V _{CE} =3V, I _C =2mA, f=0.4GHz		1.6		dB






Package Dimensions

unit : mm (typ)

7027-002



15GN03SA



15GN03SA

S Parameters (Common emitter)

$V_{CE}=5V, I_C=1mA, Z_O=50\Omega$

Freq(MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.943	-36.97	3.273	155.15	0.043	69.08	0.967	-8.53
200	0.884	-67.33	2.788	135.32	0.072	53.66	0.912	-15.10
300	0.835	-90.72	2.345	119.87	0.089	42.67	0.863	-19.22
400	0.796	-108.84	1.985	108.09	0.094	34.96	0.826	-22.13
500	0.773	-121.99	1.715	98.54	0.094	32.18	0.808	-24.68
600	0.757	-133.06	1.495	90.77	0.091	29.52	0.796	-27.45
700	0.747	-141.92	1.326	84.15	0.087	29.95	0.790	-30.22
800	0.742	-148.93	1.204	78.39	0.081	32.55	0.790	-33.18
900	0.736	-155.29	1.094	73.18	0.075	38.42	0.795	-35.94
1000	0.732	-160.69	1.006	69.03	0.072	47.05	0.793	-38.82

$V_{CE}=5V, I_C=3mA, Z_O=50\Omega$

Freq(MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.840	-62.35	7.872	140.90	0.036	59.22	0.884	-13.98
200	0.742	-101.75	5.680	117.87	0.051	44.52	0.776	-19.10
300	0.694	-124.66	4.222	104.25	0.057	40.79	0.722	-20.98
400	0.674	-139.18	3.324	95.32	0.059	40.26	0.695	-22.44
500	0.661	-149.13	2.745	88.33	0.059	45.31	0.686	-24.35
600	0.657	-156.52	2.329	82.52	0.060	50.45	0.682	-26.73
700	0.656	-162.31	2.030	77.58	0.063	57.99	0.681	-29.15
800	0.654	-167.20	1.808	73.11	0.068	63.76	0.684	-32.05
900	0.654	-171.42	1.632	68.95	0.073	72.04	0.689	-34.87
1000	0.656	-174.93	1.490	65.50	0.082	78.28	0.693	-37.73

$V_{CE}=5V, I_C=5mA, Z_O=50\Omega$

Freq(MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.764	-78.80	10.674	132.18	0.032	53.42	0.824	-16.44
200	0.675	-118.13	6.892	110.39	0.043	45.09	0.711	-19.51
300	0.643	-138.42	4.905	98.72	0.046	48.08	0.661	-20.42
400	0.633	-150.22	3.806	90.79	0.049	50.31	0.645	-21.59
500	0.627	-157.84	3.112	84.79	0.052	56.84	0.640	-23.43
600	0.627	-164.10	2.626	79.63	0.057	62.40	0.640	-25.81
700	0.626	-168.63	2.280	75.35	0.062	68.40	0.639	-28.44
800	0.629	-172.39	2.025	71.19	0.070	74.50	0.643	-31.20
900	0.630	-175.77	1.824	67.34	0.077	78.67	0.650	-34.10
1000	0.632	-178.89	1.663	64.07	0.090	83.70	0.655	-36.92

$V_{CE}=5V, I_C=10mA, Z_O=50\Omega$

Freq(MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.660	-103.13	14.230	120.64	0.024	49.45	0.728	-18.47
200	0.610	-137.53	8.234	102.03	0.034	50.63	0.626	-18.73
300	0.596	-152.55	5.660	92.68	0.037	56.96	0.597	-19.00
400	0.596	-161.17	4.324	86.37	0.043	63.29	0.586	-20.07
500	0.596	-166.66	3.511	81.12	0.050	68.02	0.587	-21.96
600	0.597	-171.07	2.958	76.64	0.057	73.05	0.590	-24.55
700	0.602	-174.45	2.559	72.58	0.066	77.96	0.591	-27.10
800	0.605	-177.26	2.267	68.82	0.077	80.92	0.596	-29.89
900	0.609	-179.81	2.032	65.06	0.086	84.59	0.604	-32.87
1000	0.611	-177.85	1.855	61.96	0.098	86.94	0.610	-35.66

15GN03SA

S Parameters (Common emitter)

$V_{CE}=5V, I_C=15mA, Z_O=50\Omega$

Freq(MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.614	-115.86	15.733	115.13	0.023	51.64	0.676	-18.67
200	0.587	-145.92	8.727	98.59	0.027	55.81	0.591	-17.74
300	0.580	-158.32	5.933	90.16	0.035	64.46	0.569	-17.98
400	0.582	-165.43	4.534	84.32	0.042	67.60	0.560	-19.12
500	0.586	-169.89	3.666	79.39	0.050	73.83	0.563	-21.07
600	0.589	-173.59	3.082	74.95	0.060	77.42	0.566	-23.60
700	0.594	-176.43	2.666	71.13	0.070	81.51	0.570	-26.22
800	0.599	-178.95	2.356	67.32	0.079	83.27	0.577	-29.13
900	0.604	-178.83	2.116	63.75	0.089	86.12	0.584	-32.05
1000	0.608	-176.67	1.926	60.55	0.100	87.51	0.590	-34.85

$V_{CE}=5V, I_C=20mA, Z_O=50\Omega$

Freq(MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.590	-123.88	16.491	111.84	0.020	52.74	0.645	-18.38
200	0.576	-150.93	8.952	96.58	0.026	58.67	0.573	-17.01
300	0.575	-161.70	6.065	88.73	0.034	65.27	0.553	-17.43
400	0.577	-167.82	4.616	82.83	0.043	69.85	0.547	-18.44
500	0.581	-171.66	3.726	78.17	0.051	74.84	0.550	-20.51
600	0.587	-174.81	3.132	73.88	0.061	80.30	0.556	-22.94
700	0.592	-177.52	2.703	69.83	0.070	81.90	0.559	-25.72
800	0.596	-179.80	2.389	66.21	0.081	84.16	0.566	-28.69
900	0.604	-178.21	2.144	62.50	0.091	86.52	0.576	-31.45
1000	0.608	-176.32	1.946	59.43	0.103	87.71	0.581	-34.28

$V_{CE}=5V, I_C=30mA, Z_O=50\Omega$

Freq(MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.572	-133.60	16.914	108.03	0.018	53.38	0.612	-17.49
200	0.570	-156.29	8.987	94.10	0.025	60.38	0.553	-15.82
300	0.573	-165.13	6.063	86.71	0.034	67.36	0.539	-16.11
400	0.581	-170.15	4.598	81.02	0.043	74.29	0.538	-17.30
500	0.586	-173.46	3.714	76.38	0.051	78.10	0.541	-19.51
600	0.592	-176.41	3.102	71.91	0.061	80.37	0.546	-22.19
700	0.597	-178.61	2.685	68.04	0.071	84.52	0.552	-24.92
800	0.605	-179.29	2.363	64.13	0.083	83.99	0.560	-28.08
900	0.612	-177.37	2.117	60.46	0.093	86.96	0.571	-30.99
1000	0.618	-175.30	1.919	57.30	0.105	89.37	0.579	-33.87

$V_{CE}=5V, I_C=50mA, Z_O=50\Omega$

Freq(MHz)	$ S_{11} $	$\angle S_{11}$	$ S_{21} $	$\angle S_{21}$	$ S_{12} $	$\angle S_{12}$	$ S_{22} $	$\angle S_{22}$
100	0.587	-145.69	15.447	103.29	0.015	56.49	0.581	-15.11
200	0.598	-163.07	8.069	90.62	0.024	64.68	0.545	-14.00
300	0.605	-169.75	5.391	83.37	0.034	72.91	0.536	-14.90
400	0.613	-173.58	4.075	77.64	0.041	77.20	0.536	-16.65
500	0.621	-176.33	3.277	72.72	0.051	82.02	0.542	-19.12
600	0.628	-178.89	2.735	68.14	0.060	83.52	0.551	-22.03
700	0.640	-178.96	2.338	64.06	0.071	85.56	0.556	-25.23
800	0.649	-177.02	2.065	60.00	0.083	88.30	0.566	-28.52
900	0.655	-175.07	1.839	56.23	0.094	90.06	0.577	-31.54
1000	0.663	-172.97	1.661	52.87	0.107	91.44	0.587	-35.17

- SANYO Semiconductor Co.,Ltd. assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO Semiconductor Co.,Ltd. products described or contained herein.
- SANYO Semiconductor Co.,Ltd. strives to supply high-quality high-reliability products, however, any and all semiconductor products fail or malfunction with some probability. It is possible that these probabilistic failures or malfunction could give rise to accidents or events that could endanger human lives, trouble that could give rise to smoke or fire, or accidents that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO Semiconductor Co.,Ltd. products described or contained herein are controlled under any of applicable local export control laws and regulations, such products may require the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written consent of SANYO Semiconductor Co.,Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO Semiconductor Co.,Ltd. product that you intend to use.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production.
- Upon using the technical information or products described herein, neither warranty nor license shall be granted with regard to intellectual property rights or any other rights of SANYO Semiconductor Co.,Ltd. or any third party. SANYO Semiconductor Co.,Ltd. shall not be liable for any claim or suits with regard to a third party's intellectual property rights which has resulted from the use of the technical information and products mentioned above.

This catalog provides information as of October, 2008. Specifications and information herein are subject to change without notice.