



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date:

Product Name: SAW Filter 713MHz SMD 5.0×5.0 mm

TST Parts No.:TA0342A

Customer Parts No.:_____

Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: _____ Elvis Chiu

Approval by: _____ Francis Chen

Date: _____ 2004/05/31



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 713 MHz

MODEL NO.: TA0342A

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 12 dB_m
2. DC voltage: 10 V
3. Operating Temperature: -10°C to +60°C
4. Storage Temperature: -40°C to +85°C

RoHS Compliant
Lead free
Lead-free soldering


B. ELECTRICAL CHARACTERISTICS:


Reference temperature: 25°C

Item				Min.	Typical	Max.
Center frequency	Fc	MHz		-	713	-
Insertion loss	710 ~ 716 MHz	IL	dB	-	2.4	4.5
Amplitude ripple	710 ~ 716 MHz		dB	-	0.5	-
Absolute Attenuation						
	0 ~ 613 MHz		dB	44	50	-
	613 ~ 663 MHz		dB	40	48	-
	663 ~ 690 MHz		dB	35	43	-
	740 ~ 746 MHz		dB	35	46	-
	763 ~ 813 MHz		dB	40	50	-
	813 ~ 1000 MHz		dB	38	45	-
	1000 ~ 1500 MHz		dB	25	34	-
Group Delay Variation (p-p)			ns	-	40	-
Temperature coefficient of frequency			ppm/°C		-35	
Source impedance		Z _s	Ω	-	50	-
Load impedance		Z _L	Ω	-	50	-


C. Frequency Characteristics :

Transfer Function:







Group Delay Variation:




D. MEASUREMENT CIRCUIT:



E. OUTLINE DRAWING:




F.PCB Footprint:



G. PACKING:

1. REEL DIMENSION



2. TAPE DIMENSION

