


SERIES 90B

Machine Insertable MIDIP


FEATURES

- Tested for TO-116 Equipment
- Up to 10 Positions
- High Pressure, Reliable Contacts
- Molded (Sealed) Base and Optional Top Seal



DIMENSIONS In inches (and millimeters) Switch is packaged as shown here with all positions on. .290 (7,37) MAX. .165 ± .005 LENGTH ± .010 (0,25) (4.19 ± 0.13) G .195 (4,95) MAX. .135 ± .010 .375 (3,43 ± 0,25) TYP. .020 ± .002 (0,51 ± 0,05) TYP. ±.010 .012 ± .001 (9,53 .100 ± .005 (2,54 ± 0,13) TYP. $(0,30 \pm 0,03)$ ± 0,25) .085 ± .005 (2,16 ± 0,13) TYP. TYP. DESIGNED FOR .100 X .300 (2,54 X 7,62) ON CENTER HOLES

CIRCUITRY



ORDERING INFORMATION: Tube Packaging (Each tube is 19.5 inches long)

				8,
No. of Positions	Length Inches	Length Metric	Number Per Tube	Part Number*
2 3 4 5 6 7 8 9	.270" .370" .470" .570" .670" .770" .870" .970"	6,9 mm 9,4 mm 11,9 mm 14,5 mm 17,0 mm 19,6 mm 22,1 mm	60 47 37 31 26 23 20 18	90B02PT 90B03PT 90B04PT 90B05PT 90B06PT 90B07PT 90B08PT 90B08PT
10	1.070"	24,6 mm 27,2 mm	16	90B10PT

Available from your local Grayhill Distributor. For prices and discounts, contact a local Sales Office, an authorized local Distributor or Grayhill.

*The "P"in the part number denotes top tape seal versions. To order without top tape seal, leave the "P" off the part number when ordering.

DIP Switches