

SPECIFICATION SHEET
JFW MODEL 75DR-018
DUAL ROTARY ATTENUATOR

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Frequency Range	DC-1000 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-30 dB in 1 dB steps
VSWR	1.35:1 maximum
Insertion Loss	0.5 dB maximum
Attenuation Accuracy	DC-500 MHz ± 0.2 dB (0-10 dB) ± 0.5 dB (10-30 dB) 500-1000 MHz ± 0.4 dB (0-10 dB) ± 0.5 dB (10-30 dB)
RF Input Power	1 Watt average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC or F female
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-2135

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	01/10/2002						
9999	05/15/2003	A	BAC 03/15/2004				
4524	03/15/2004	B	CLV 03/15/2004				