



TWO DIGIT VENDOR IDENTIFICATION CODE TO BE ASSIGNED AFTER VENDOR APPROVAL.

DC RESISTANCE IN OHMS	1 TO 2 .040 MAX
	3 TO 4 .040 MAX
POLARITY MUST BE CORRECT	
APPLY = .1V @ 10 KHZ	
INDUCTANCE = 1 TO 2 4.00 mHYS MIN	
IND 1-2 ≈ 3-4 WITHIN .508 mHY	
LEAKAGE INDUCTANCE = 45.0 uHYS	
- .225 uHY 1-3 WITH 2 & 4 SHORTED	
HIPOT = 2850 V FOR 1 SEC MIN	
WDG TO WDG	
CONTINUITY =	
IMPREGNATION NOTES =	
PINS TO BE FREE OF DEBRIS TO MTG SURFACE MIN	

REV	CHANGE	DATE	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES: TOLERANCES:	MATERIAL		
A	RELEASED	J.P.R. 4-23-92	x/x = ± 1/64 .xx = ± .01 .xxx = ± .005 .4 = ± 0° 30'			
B	ECN G7588	TH 5-17-97	THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO MAGNETEK. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING IS EXPRESSLY PROHIBITED EXCEPT AS MAGNETEK MAY OTHERWISE AGREE IN WRITING. DO NOT SCALE DRAWING.	FINISH		
C	ECN G8246	TH 10-9-97				
			DWN BY <i>[Signature]</i>	SCALE	TITLE COMMON MODE FILTER INDUCTOR	
			CHK BY	DATE		
			APVD BY <i>H. Chase</i>	4-22-92		
					SIZE	DRAWING NO.
					A	CMT908-H2