


GaAs MMIC

Data Sheet

CGY 60

- Low noise preamplifier for mobile communication (PCN, DECT, GSM) in 2.7 V to 6 V systems
- Biased monolithic microwave IC (MMIC) matched to 50Ω for 1.7 to 2 GHz
- Easily matchable to 50Ω for lower frequencies (i.e. GSM-application)
- No bias coil needed
- Low noise figure and high gain (typ. NF = 1.9 dB, $G = 12.5 \text{ dB} @ 3 \text{ V}, 1.85 \text{ GHz}$)
- Low power consumption
- Frequency range 200 MHz ... 2.5 GHz

ESD: Electrostatic discharge sensitive device,
observe handling precautions!



Type	Marking	Ordering Code (taped)	Package ¹⁾
CGY 60	Y7s	Q62702-G39	MW-6

¹⁾ Dimensions see **Page 10**.

Maximum Ratings

Parameter	Symbol	Value	Unit
Drain voltage	V_D	8	V
Channel temperature	T_{Ch}	150	°C
Storage temperature range	T_{stg}	- 55 ... + 150	°C
Total power dissipation ($T_S \leq 132 \text{ °C}$) ¹⁾	P_{tot}	80	mW

¹⁾ Please care for sufficient heat dissipation on the pcb!

Thermal Resistance

Parameter	Symbol	Value	Unit
Channel-soldering point (GND)	R_{thChS}	≤ 220	K/W
Channel-ambient ¹⁾	R_{thChA}	< 300	K/W

¹⁾ Package mounted on alumina 15 mm × 16.7 mm × 0.7 mm.

Electrical Characteristics of CGY 60 in GSM Application Circuit
 $T_A = 25^\circ\text{C}$, $f = 950 \text{ MHz}$, $R_S = R_L = 50 \Omega$, unless otherwise specified.

Characteristics	Symbol	Limit Values			Unit
		min.	typ.	max.	
Drain current	I_D	—	6	9	mA
Power Gain $V_D = 3 \text{ V}$ $V_D = 5 \text{ V}$	G	—	15.5	—	dB
—	—	—	17	—	
Noise figure $V_D = 3 \text{ V}$ $V_D = 5 \text{ V}$	F	—	1.35	—	dB
—	—	—	1.30	—	
Input return loss $V_D = 3 \text{ V}$ $V_D = 5 \text{ V}$	RL_{IN}	—	10	—	dB
—	—	—	10	—	
Output return loss $V_D = 3 \text{ V}$ $V_D = 5 \text{ V}$	RL_{OUT}	—	11	—	dB
—	—	—	11	—	
Third order input intercept point two-tone intermodulation test $f_1 = 950 \text{ MHz}$, $f_2 = 951 \text{ MHz}$ $P_{IN} = -20 \text{ dBm}$ (both carriers) $V_D = 3 \text{ V}$ $V_D = 5 \text{ V}$	IP_3	—	—	—	dBm
—	—	—	-3	—	
—	—	—	-1	—	
Input power at 1 dB gain compression $V_D = 3 \text{ V}$ $V_D = 5 \text{ V}$	$P_{-1 \text{ dB}}$	—	-10	—	dBm
—	—	—	-8	—	

Electrical Characteristics in PCN-, DECT-Application Circuit
 $T_A = 25^\circ\text{C}$, $f = 1850 \text{ MHz}$, $R_S = R_L = 50 \Omega$, unless otherwise specified.

Characteristics	Symbol	Limit Values			Unit
		min.	typ.	max.	
Drain current $V_D = 3 \text{ V}$ $V_D = 5 \text{ V}$	I_D	—	6	9	mA
Power Gain $V_D = 3 \text{ V}$ $V_D = 5 \text{ V}$	G	—	12.5 13.5	— —	dB
Noise figure $V_D = 3 \text{ V}$ $V_D = 5 \text{ V}$	F	—	1.90 1.85	— —	dB
Input return loss $V_D = 3 \text{ V}$ $V_D = 5 \text{ V}$	RL_{IN}	—	14.5 14.5	— —	dB
Output return loss $V_D = 3 \text{ V}$ $V_D = 5 \text{ V}$	RL_{OUT}	—	14 14	— —	dB
Third order input intercept point two-tone intermodulation test $f_1 = 1850 \text{ MHz}$, $f_2 = 1851 \text{ MHz}$ $P_{IN} = -20 \text{ dBm}$ (both carriers) $V_D = 3 \text{ V}$ $V_D = 5 \text{ V}$	IP_3	—	0 2	— —	dBm
Input power at 1 dB gain compression $V_D = 3 \text{ V}$ $V_D = 5 \text{ V}$	$P_{-1 \text{ dB}}$	—	-7 -5	— —	dBm




Figure 1 Application Circuit for Measuring S- and Noise-Parameters
 $f = 200 \text{ MHz to } 2 \text{ GHz}$

¹⁾ Use 12 to 15 pF for DECT - or PCN - applications.




Figure 2 900 MHz Application (GSM)

PCB - Layouts for Application Circuits




Figure 3 PCN -, DECT - Application Board




Figure 4 GSM - Application Board

PCB - data: Glass fiber teflon board (double sided) TACONIC TLX-9-0150-CH/CH.

$\epsilon_r = 2.45$, thickness = 0.4 mm

Typical S- and Noise-Parameters
 $V_D = 3 \text{ V}$, $Z_0 = 50 \Omega$

<i>f</i>	S11		S21		S12		S22	
	GHZ	MAG	ANG	MAG	ANG	MAG	ANG	MAG
0.1	0.97	- 5	2.98	- 135	0.005	80	0.74	- 34
0.2	0.97	- 9	3.85	- 162	0.009	77	0.51	- 44
0.3	0.96	- 14	4.13	- 177	0.013	74	0.41	- 47
0.4	0.94	- 19	4.27	172	0.017	73	0.35	- 48
0.5	0.93	- 23	4.35	163	0.021	71	0.33	- 49
0.6	0.91	- 29	4.40	155	0.026	67	0.31	- 51
0.7	0.88	- 34	4.45	148	0.029	65	0.30	- 54
0.8	0.85	- 40	4.48	140	0.033	63	0.29	- 58
0.9	0.81	- 46	4.51	132	0.037	60	0.29	- 63
1.0	0.76	- 52	4.55	125	0.042	54	0.28	- 69
1.1	0.71	- 59	4.60	117	0.045	50	0.27	- 74
1.2	0.64	- 66	4.62	110	0.048	46	0.26	- 80
1.3	0.58	- 74	4.63	102	0.051	41	0.26	- 86
1.4	0.51	- 83	4.61	94	0.053	36	0.25	- 93
1.5	0.43	- 93	4.58	85	0.054	31	0.24	- 101
1.6	0.34	- 106	4.51	77	0.055	26	0.23	- 109
1.7	0.26	- 122	4.40	69	0.055	20	0.22	- 118
1.8	0.19	- 149	4.30	60	0.054	15	0.21	- 128
1.9	0.15	172	4.13	51	0.051	11	0.20	- 140
2.0	0.18	131	3.94	43	0.049	5	0.19	- 151
2.1	0.24	106	3.73	35	0.046	2.5	0.18	- 163
2.2	0.32	90	3.56	27	0.043	- 5	0.18	177
2.3	0.39	78	3.33	20	0.038	- 9	0.18	170
2.4	0.46	69	3.09	13	0.033	- 11	0.18	160
2.5	0.52	61	2.87	5	0.028	- 12	0.19	151

<i>f</i>	<i>F</i>_{min}	Γ_{opt}		<i>R_N</i>
		MAG	ANG	
GHz	dB	-	deg	Ω
0.9	1.27	0.70	27	47.8
1.3	1.35	0.63	39	32.7
1.8	1.50	0.42	59	18.2
2.0	1.60	0.30	62	15.0

Typical S- and Noise-Parameters
 $V_D = 3 \text{ V}$, $Z_0 = 50 \Omega$

<i>f</i>	S11		S21		S12		S22	
GHZ	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.1	0.97	- 4	3.58	- 137	0.005	74	0.72	- 31
0.2	0.97	- 9	4.49	- 164	0.009	75	0.52	- 37
0.3	0.96	- 14	4.78	- 178	0.013	74	0.44	- 38
0.4	0.94	- 18	4.91	171	0.017	71	0.39	- 39
0.5	0.93	- 23	4.96	163	0.021	70	0.37	- 40
0.6	0.90	- 28	5.02	154	0.024	67	0.36	- 42
0.7	0.88	- 34	5.09	147	0.028	64	0.35	- 45
0.8	0.85	- 39	5.11	139	0.032	62	0.34	- 50
0.9	0.81	- 45	5.14	132	0.036	60	0.34	- 54
1.0	0.76	- 51	5.16	125	0.041	55	0.33	- 59
1.1	0.71	- 58	5.23	118	0.044	50	0.32	- 64
1.2	0.65	- 65	5.25	110	0.046	45	0.31	- 70
1.3	0.59	- 72	5.25	102	0.049	42	0.30	- 75
1.4	0.52	- 81	5.25	95	0.050	37	0.29	- 81
1.5	0.44	- 90	5.21	87	0.052	32	0.27	- 88
1.6	0.36	- 103	5.15	78	0.052	27	0.26	- 95
1.7	0.28	- 118	5.05	70	0.052	23	0.24	- 102

Typical S- and Noise-Parameters (cont'd)
 $V_D = 3 \text{ V}$, $Z_0 = 50 \Omega$

<i>f</i>	S11		S21		S12		S22	
GHZ	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
1.8	0.20	- 140	4.93	62	0.051	17	0.22	- 111
1.9	0.16	- 176	4.77	53	0.050	13	0.20	- 121
2.0	0.17	141	4.57	45	0.047	8	0.18	- 131
2.1	0.23	113	4.36	37	0.045	5	0.17	- 142
2.2	0.31	95	4.18	29	0.042	- 2	0.16	- 158
2.3	0.38	82	3.92	21	0.037	- 6	0.14	- 173
2.4	0.45	72	3.66	14	0.032	- 8	0.14	174
2.5	0.52	64	3.39	7	0.027	- 9	0.14	162

<i>f</i>	<i>F</i>_{min}	Γ_{opt}		<i>R</i>_N
		MAG	ANG	
GHz	dB	-	deg	Ω
0.9	1.23	0.69	26	47.7
1.3	1.32	0.67	39	33.3
1.8	1.45	0.45	55	18.6
2.0	1.53	0.32	60	15.2


Package Parameters

Dim.	min.	nom.	max.	Gradient	Remark
A	—	—	1.1	—	—
A ₁	—	—	0.1	—	—
A ₂	—	—	1.0	—	—
b	—	0.3	—	—	—
b ₁	—	0.6	—	—	—
c	0.08	—	0.15	—	—
D	2.8	—	3.0	—	—
E	1.2	—	1.4	—	—
e ₁	—	0.95	—	—	—
e ₁	—	1.9	—	—	—
H _E	—	—	2.6	—	—
L _E	—	—	0.6	—	—
a	—	—	—	max 10°	¹⁾
q	—	—	—	2° ... 30°	—

¹⁾ Applicable on all case top sides.

Package Outlines

MW-6 (Special Package)



GPW05794

Sorts of Packing

Package outlines for tubes, trays etc. are contained in our Data Book "Package Information".

SMD = Surface Mounted Device

Dimensions in mm