

Micro Commercial Components

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 (818) 701-4939 Fax:

Features

- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Low Current Leakage
- Low Cost
- Small Outline Surface Mount Package
- Case Material: Molded Plastic. UL Flammability Classificatio Rating 94-0 and MSL Rating 1
- Marking: M5C/T3

Pin Configuration Top View



Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Maximum Thermal Resistance: 556°C/W Junction To Ambient

Electrical Characteristics @ 25°C Unless Otherwise Specified


<u> </u>	CIOO © LO C		nioi mioo opooniou
Reverse Voltage	V_R	100V	
Average Rectified	Io	200mA	
Output Current			
Power Dissipation	P _{TOT}	225mW	
Peak Forward Surge	I _{FSM}	0.5A	t=1s,Non-Repetitive
Current			
Maximum			
Instantaneous	V_{F}	820mV	$I_{FM} = 10mA;$
Forward Voltage			T _J = 25°C*
Maximum DC			V _R =50Volts
Reverse Current At	I_R	1.0μΑ	T _J = 25°C
Rated DC Blocking		100μA	T _J = 125°C
Voltage		,	
Maximum Junction	C _J	2pF	Measured at
Capacitance	-		1.0MHz, V_R =0V
Reverse Recovery	T _{rr}	4nS	I _F =10mA
Time			$V_R = 0V$
			R_L =500 Ω


^{*}Pulse test: Pulse width 300 µsec, Duty cycle 2%

MMBD7000

225mW 100Volt









	INCHES		MM		
DIM	MIN	MAX	MIN	MAX	NOTE
Α	.110	.120	2.80	3.04	
В	.083	.098	2.10	2.64	
C	.047	.055	1.20	1.40	
D	.035	.041	.89	1.03	
Е	.070	.081	1.78	2.05	
F	.018	.024	.45	.60	
G	.0005	.0039	.013	.100	
Ι	.035	.044	.89	1.12	
7	.003	.007	.085	.180	
K	.015	.020	.37	.51	


Suggested Solder Pad Layout



MMBD7000







 V_{F} , INSTANTANEOUS FORWARD VOLTAGE (V) Fig. 1 Forward Characteristics

T_j, JUNCTION TEMPERATURE (°C) Fig. 2 Leakage Current vs Junction Temperature



Ordering Information

Device	Packing
(Part Number)-TP	Tape&Reel3Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.