


200 V - 1,000 V Single Phase Bridge
1.4 A - 1.5 A Forward Current
70 ns - 3000 ns Recovery Time

1102C - 1110C
1102FC - 1110FC
1102UFC - 1110UFC




ELECTRICAL CHARACTERISTICS AND MAXIMUM RATINGS

Part Number	Working Reverse Voltage (V _{rwm})	Average Rectified Current @TC (I _o)		Reverse Current @ V _{rwm} (I _r)		Forward Voltage (V _f)		1 Cycle Surge Current (I _{fsm})	Repetitive Surge Current (I _{frm})	Reverse Recovery Time (1) (T _{rr})	Thermal Impd. θ _{J-C}
		55°C	100°C	25°C	100°C	25°C	Amps	25°C	25°C	25°C	°C/W
		Amps	Amps	µA	µA	Volts		Amps	Amps	ns	
1102C 1106C 1110C	200 600 1000	1.5 1.5 1.5	1.0 1.0 1.0	1.0 1.0 1.0	25 25 25	1.1 1.1 1.1	1.0 1.0 1.0	50 50 50	10 10 10	3000 3000 3000	22.5 22.5 22.5
1102FC 1106FC 1110FC	200 600 1000	1.5 1.5 1.5	1.0 1.0 1.0	1.0 1.0 1.0	25 25 25	1.3 1.3 1.3	1.0 1.0 1.0	25 25 25	6.0 6.0 6.0	150 150 150	22.5 22.5 22.5
1102UFC 1106UFC 1110UFC	200 600 1000	1.4 1.4 1.4	0.9 0.9 0.9	1.0 1.0 1.0	25 25 25	1.7 1.7 1.7	1.0 1.0 1.0	25 25 25	5.0 5.0 5.0	70 70 70	22.5 22.5 22.5

(1)T_{rr} Testing: I_f=0.5A, I_r=1.0A, I_{rr}=0.25A *Op. Temp.= -55°C to +150°C Stg. Temp.= -55°C to +150°C

10



Dimensions: In. (mm) • All temperatures are ambient unless otherwise noted. • Data subject to change without notice.



VOLTAGE MULTIPLIERS INC.
 8711 W. Roosevelt Ave.
 Visalia, CA 93291

TEL 559-651-1402
 FAX 559-651-0740
 www.voltagemultipliers.com

1102C - 1110C • 1102FC - 1110FC • 1102UFC - 1110UFC

