

Class H(K), J and R Fuseblocks



Porcelain Type Fuseblocks

Class H(K) and R Dimensions

Agency Approvals: UL Listed

Class H and K Dimension Fuseblocks - Porcelain Type

| Volts | Amps | Poles | Fuseblocks | | |
|-------|------|-------|---------------|-------|---------|
| | | | Terminal Type | | |
| | | | Pressure | Screw | Box Lug |
| 250 | 1/10 | 1 | — | 2601 | — |
| | to | 2 | — | 2604 | — |
| | 30 | 3 | — | 2607 | — |
| | 31 | 1 | — | — | 2602 |
| | to | 2 | — | — | 2605 |
| | 60 | 3 | — | — | 2608 |
| 600 | 1/10 | 1 | — | 2610 | — |
| | to | 1 | — | — | 2611 |
| | 30 | 1 | — | — | 2611 |
| | 31 | 1 | — | — | 2611 |
| | to | 1 | — | — | 2611 |
| | 60 | 1 | — | — | 2611 |

CE CE logo denotes compliance with European Union Low Voltage Directive (50-1000V AC, 75-1500V DC). Refer to BIF document #8002 or contact Bussmann Application Engineering at 636-527-1270 for more information.

Modular Type Fuseblocks

Class H & J Fuses

Reinforced retaining clips standard

Available in 30A and 60A, 3-pole models only.

Agency Approvals: UL Recognized, Guide IZLT2, File E14853
 CSA Certified, Class 6225-01, File 47235

Modular Type For Class H & J Fuses

| Fuse Type | Volts | Amps | Catalog Number | |
|-----------|-------|------|----------------|-----------|
| | | | Screw | Pressure |
| H | 250 | 60 | 11241-3SR | 11241-3PR |
| | | | 11242-3SR | 11242-3PR |
| | | | 11241-3SR | 11241-3PR |
| | 600 | 30 | 11242-3SR | 11242-3PR |
| | | | 11239-3SR | 11239-3PR |
| | | | 11240-3SR | 11240-3PR |
| J | 600 | 30 | 11241-3SR | 11241-3PR |
| | | | 11239-3SR | 11239-3PR |
| | | | 11239-3SR | 11239-3PR |

Note: Order two blocks per fuse (matched or mixed.)

CE CE logo denotes compliance with European Union Low Voltage Directive (50-1000V AC, 75-1500V DC). Refer to BIF document #8002 or contact Bussmann Application Engineering at 636-527-1270 for more information.

