


RoHS Compliant Product
A suffix of "-C" specifies halogen & lead-free


SOT-323

DESCRIPTION

The SCS705F is designed for general purpose detection and high speed switching.



MARKING: KL5



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	1.80	2.20	G	0.100	REF.
B	1.80	2.45	H	0.525	REF.
C	1.15	1.35	J	0.08	0.25
D	0.80	1.10	K	-	-
E	1.20	1.40	L	0.650	TYP.
F	0.20	0.40			

MAXIMUM RATINGS (T_A=25°C unless otherwise specified.)

PARAMETER	SYMBOL	VALUE	UNIT
Maximum Peak Repetitive Reverse Voltage	V _{RRM}	40	V
Maximum RMS Voltage	V _{RMS}	28	V
Maximum DC Blocking Voltage	V _{DC}	40	V
Peak Forward Surge Current at 8.3mSec Single Half Sine-Wave	I _{FSM}	0.2	A
Typical Junction Capacitance between Terminal ¹	C _J	2.0	pF
Maximum Average Forward Rectified Current	I _O	0.03	A
Total Power Dissipation	P _D	225	mW
Junction & Storage Temperature	T _J , T _{STG}	125, -40~125	°C

ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise specified.)

PARAMETER	SYMBOL	TYP	UNIT	TEST CONDITION
Maximum Instantaneous Forward Voltage	V _F	0.37	V	I _{F1} =1mA
Maximum Average Reverse Current	I _R	1.0	µA	V _R =10V

Note: 1. Measured at 1.0 MHz and applied reverse voltage of 1.0 volts.
2. ESD sensitive product handling required.

CHARACTERISTIC CURVES

