


**MARKING**



MEDER-Label, Type  
 Production code EN60062/  
 Factory code / circuit diagram  
**MEDER-Logo, Typ**  
**Produktionscode**  
**EN60062/Fertigungsstätte/Schaltbild**



Abmessungen / dimensions (mm)  
 tolerances acc. to DIN ISO 2768-m

**CABLE**

single wires LIYV/T, 0.14 mm<sup>2</sup>  
 colour black  
 ends 5±1 stripped and tinned  
**Einzellitzen LIYV/T, 0.14 mm<sup>2</sup>**  
**Farbe schwarz**  
**Enden 5±1 abisoliert und verzinkt**

**CIRCUIT DIAGRAM**



Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull-In	at 20 °C	49		66	AT
Test equipment		KMS-13			

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact - No.		87			
Contact - form		A - NO			
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
Switching voltage	DC or Peak AC			200	V
Carry current	DC or Peak AC			0,5	A
Switching current	DC or Peak AC			0,5	A
Sensor-resistance	measured with 40% overdrive			200	mOhm
Housing material		PBT glass fibre reinforced			
Case colour		black			
Sealing compound		Polyurethan			

Environmental data	Conditions	Min	Typ	Max	Unit
Shock	1/2 sine wave duration 11ms			50	g
Vibration	from 10 - 2000 Hz			20	g
Operating temperature	cable not moved	-30		80	°C
Operating temperature	cable moved	-5		80	°C
Storage temperature		-30		80	°C
Reach / RoHS conformity		yes			

General data	Conditions	Min	Typ	Max	Unit
Mounting advice		over 5m cable, a resistor is recommended.			