

EVXLF28V series

Product code	L ₁ , min mH	L ₂ , min mH	DCR ₁ , max Ω	DCR ₂ , max Ω	Rated current A _{rms}
EVXLF28V-0150	1.50	1.50	0.07	0.07	3.1
EVXLF28V-0270	2.70	2.70	0.12	0.12	2.7
EVXLF28V-0330	3.30	3.30	0.16	0.16	2.5
EVXLF28V-0390	3.90	3.90	0.18	0.18	2.2
EVXLF28V-0470	4.70	4.70	0.20	0.20	2.5
EVXLF28V-0560	5.60	5.60	0.22	0.22	2.1
EVXLF28V-0680	6.80	6.80	0.24	0.24	2.0
EVXLF28V-0820	8.20	8.20	0.26	0.26	1.7
EVXLF28V-1000	10.00	10.00	0.36	0.36	1.4
EVXLF28V-1200	12.00	12.00	0.39	0.39	1.3
EVXLF28V-1500	15.00	15.00	0.70	0.70	1.1
EVXLF28V-1800	18.00	18.00	0.61	0.61	1.2
EVXLF28V-2200	22.00	22.00	0.84	0.84	1.0
EVXLF28V-2700	27.00	27.00	0.93	0.93	1.0
EVXLF28V-3300	33.00	33.00	1.04	1.04	0.8
EVXLF28V-3900	39.00	39.00	1.43	1.43	0.7
EVXLF28V-4700	47.00	47.00	1.56	1.56	0.7

All dimensions in mm

