



**SPECIFICATIONS:**

- MATERIAL**
- TIP ROD, RING AND HANDLE - BRASS, NICKEL PLATED
  - HOUSING AND SLEEVE - ZINC DIE CAST, COPPER AND NICKEL PLATED
  - TIP AND RING TERMINALS - BRASS, TIN PLATED
  - SLEEVE (CLAMP) TERMINAL - STEEL, TIN PLATED
  - INSULATION - THERMOPLASTIC

- ELECTRICAL**
- DIELECTRIC WITHSTANDING VOLTAGE : 500 VAC
  - INSULATION RESISTANCE: 50,000 MEGOHMS MINIMUM (INITIAL)

- OPERATING TEMPERATURE**
- 20°C TO +65°C

- MATING JACK**
- TYP, 1/4 INCH, COMMERCIAL TYPE, 3 CONDUCTOR PHONE JACKS

**H** THIS PRODUCT IS RoHS COMPLIANT.

**CUSTOMER DRAWING**

REV	ECO NUMBER	DATE	BY	APVD
H	25760	12-5-07	TJK	TJK
G	CAD REDRAWN 25124	10-28-05	JL	GG
REVISIONS				

UNLESS OTHERWISE SPECIFIED

- ALL DIMENSIONS IN INCHES
- TWO PLACE DECIMALS ±0.02
- THREE PLACE DECIMALS ±0.005

DO NOT SCALE DRAWING

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.

SIZE *	WIDTH *	MULT *	LBS/M *	TEMPER *
FINISH *				MATERIAL *
SPEC No. *				SPEC No. *
FIRST USED ON *		SCALE 2:1		
DATE DRAWN	BY	CHKD	APVD	<b>Switchcraft®</b>
10-28-05	JL	GG	GG	
		10-28-05	10-28-05	SHEET 1 OF 1
NAME RA PHONE PLUG, 3 CONDUCTOR, RoHS			PART No. 236	REV H

SolidWorks CAD File **B**