

TUNING FORK CRYSTAL UNITS (SMD • Cylinder Type)

CMR200T


2000pcs/reel



FEATURES


- Lead formed SMD type with embossed tape. Automatic mounting and reflowable type.
- Most appropriate for clock source for portable and other various equipment with low power consumption.

DIMENSION [mm]



CMR200T

SOLDER PAD LAYOUT [mm]



CMR200T

STANDARD SPECIFICATIONS

Item	Model	CMR200T	Conditions
Nominal Frequency	f_0	32.768kHz	
Frequency Tolerance	$\Delta f/f_0$	± 20 ppm	at 25°C
Load capacitance	C_L	12.5pF	Need to specify your requirement
Operating Temperature Range	T_{OPR}	-40°C ~ +85°C	
Storage Temperature Range	T_{STR}	-55°C ~ +125°C	
Turnover Temperature	T_M	25°C \pm 5°C	See figure 2 in P4
Temperature Coefficient	β	-0.034 \pm 0.006ppm/°C ²	
Motional (series) resistance	R_1	50K Ω Max.	at 25°C
Level of drive	D_L	1 μ W Max.	
Aging (first year)	$\Delta f/f_0$	± 3 ppm Max.	25°C \pm 3°C
Quality Factor	Q	70000 Typ.	
Shunt capacitance	C_0	1.35pF Typ.	