

**Micro Commercial Components** 



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311


Phone: (818) 701-4933 Fax: (818) 701-4939

## **DAN217**

# **Features**

- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Low Current Leakage and Low Cost
- Small Outline Surface Mount Package
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Pin Configuration Top View



# **Maximum Ratings**


- Operating Temperature: -40°C to +150°C
- Storage Temperature: -55°C to +150°C


## Electrical Characteristics @ 25°C Unless Otherwise Specified

Parameter	Symbol	Limits	Unit
Peak reverse voltage	$V_{RM}$	80	V
DC reverse voltage	$V_R$	80	V
Maximum forward current	I <sub>FM</sub>	300	mA
Average forward current	Io	100	mA
Surge current	I <sub>FSM</sub>	1000	mA
Power dissipation	$P_D$	200	mW
Junction temperature	Tj	125	$^{\circ}$

Parameter	Symbol	Test conditions	MIN	MAX	UNIT
Reverse breakdown voltage	$V_{BR}$	IR=100uA	80		V
Reverse voltage leakage current	I <sub>R</sub>	VR=70V		0.1	uA
Forward voltage	$V_{F}$	IF=100mA		1200	mV


# 200mW 80Volt Plastic-Encapsulate Diode





DIMENSIONS					
	INCHES		ММ		
DIM	MIN	MAX	MIN	MAX	NOTE
Α	.110	.120	2.80	3.04	
В	.083	.098	2.10	2.64	
O	.047	.055	1.20	1.40	
О	.035	.041	.89	1.03	
Е	.070	.081	1.78	2.05	
F	.018	.024	.45	.60	
G	.0005	.0039	.013	.100	
I	.035	.044	.89	1.12	
J	.003	.007	.085	.180	
K	015	020	37	51	

### Suggested Solder Pad Layout





# **DAN217**


# **Typical Characteristics**



**Micro Commercial Components** 







Reverse characteristics

Capacitance between terminals characteristics



## **Ordering Information:**

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.