

Preliminary

# GaN-SiC Pallet Amplifier

# RTP26070-20



## Product Features

- Doherty amplifier design
- GaN on SiC HEMT
- Small and light weight
- 50 Ohm Input/Output impedance matched
- Highly reliable and rugged design
- High efficiency, High Gain
- 70W typical  $P_{AVG}$

## Application

- LTE, WiMAX DPD amplifier
- General purpose RF amplifier



## Description

The RTP26070-20 is designed for RF system application frequencies from 2620MHz to 2690MHz, with high gain. This Pallet Amplifier uses GaN on SiC HEMT technology which performs high breakdown voltage, high linearity, high efficiency. The RTP26070-20 is DPD application amplifier.

## Electrical Specifications @ VDD=+48VDC, T=25°C, 50Ω

PARAMETER	Symbol	Min	Typ	Max	Unit
Frequency Range	BW	2620	-	2690	MHz
Output Power	$P_{AVG}$	-	48.5		dBm
Instantaneous Bandwidth	SBW		20		MHz
Output Power @ Psat G.C.P	$P_{sat}$	-	56.0	-	dBm
Small Signal Gain	SSG	50	55	-	dB
Small Signal Gain Flatness	$\Delta G$	-	$\pm 0.5$	$\pm 1.0$	dB
Gain Variation	$\Delta G_t$		$\pm 3.0$		dB
ACLR @ LTE 10MHz 1FA*1	ACLR		-25		dBc
ACLR with DPD	ACLR		-53		dBc
Forward Coupling Level	FC	9	10	11	dBm
Operating Voltage 1	VDC1		48		Volt
Operating Voltage 2	VDC2		5.6		Volt
Chain Efficiency*2 @ Pout 77.6W	EC	-	45	-	%
Pallet Efficiency @ Pout 70.8W	EP	40	42	-	%
Input Port Return Loss	IRL	-13	-18		dB
Output Port Return Loss	ORL	-15	-18		dB

\*1 Test Signal Condition: LTE 10MHz 1FA(PAR 7.5dB), Test DPD solution: Optichron DPD(OP6180)

\*2 Chain Efficiency is an entire operating transistor efficiency excluded isolator and coupler.

## Environmental Characteristics

PARAMETER	Symbol	Min	Typ	Max	Unit
Operating Temperature	$T_c$	-40	-	+60	°C
Storage Temperature	$T_s$	-45	-	+90	°C

### Mechanical Specifications

PARAMETER	Value	Units	Limits
Dimensions ( L x W x H )	170 x 100 x 20.3	mm	Max
Weight	502	g	Typical
RF Connectors In/Out/Coupling	SMA Female		
DC Connectors / Controls	5566-08(8pin)		
Cooling	External Heat sink + airflow		

### RF Interface Connectors

Pin #	DESCRIPTION	Specifications
1	RF IN	RF Input signal
2	RF OUT	RF Output signal
3	FB OUT	RF Forward Detection signal For Feed-back


### DC Connector

- 5566-08 (4.2mm PITCH, 8Pin)

Pin #	DESCRIPTION	Specifications
1,2	Drive, Main Amp +Vdd	+48Vdc
3	Gain Block Amp +Vgg	+5.6V
4	Enable	TTL High Enable (+5Vdc)
5,6,7	GND	Ground
8	Temp. Monitor	Reporting Temperature data [0.75V/25°C(10mV/°C)]

※ RF connector and DC connector custom design available.

**Outline Drawing**



RFHIC Corporation (RFHIC) reserves the right to make changes to any products herein or to discontinue any product at any time without notice. RFHIC do not assume any liability for the suitability of its products for any particular purpose, and disclaims any and all liability, including without limitation consequential or incidental damages. The product specifications herein expressed have been carefully checked and are assumed to be reliable. However, RFHIC disclaims liability for inaccuracies and strongly recommends buyers to verify that the information they are using is current before placing purchase orders. RFHIC products are not intended for use in life support equipment or application where malfunction of the product can be expected to result in personal injury or death. Buyer uses or sells such products for any such unintended or unauthorized application, buyer shall indemnify, protect and hold RFHIC and its directors, officers, stockholders, employees, representatives and distributors harmless against any and all claims arising out of such use. RFHIC's liability under or arising out of damages, claims of whatsoever kind and nature which RFHIC products could cause shall be limited in amount to the net purchase price of the products sold to buyer by RFHIC.