

Shorting SMA Male Dust Cap



PE6006

TECHNICAL DATA SHEET

Shorting SMA Male Dust Cap Configuration Connector SMA Male Shorting **Connector Specification** MIL-STD-348A Chain Option No Chain Mechanical Specifications Temperature Operating Range, deg C -65 to +165 Size Length, in [mm] 0.335 [8.51] Width, in [mm] 0.315 [8] Connector Type SMA Male Shorting Contact Material and Plating Brass, Gold **Contact Plating Specification** 30µ in. minimum Coupling Nut Material and Plating Brass, Nickel **Coupling Nut Plating Specification** 100µ in. minimum Hex Size, in. 5/16 Torque, in-lbs [Nm] 5 [0.57] Body Material and Plating Brass, Gold **Body Plating Specification** 30µ in. minimum **Dielectric Type** Teflon Compliance Certifications (visit www.Pasternack.com for current document) **RoHS Compliant** Yes **Plotted and Other Data**

Notes:

Values at 25 °C, sea level


Shorting SMA Male Dust Cap from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Shorting SMA Male Dust Cap PE6006

URL: http://www.pasternack.com/50-ohm-sma-male-short-cap-pe6006-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com





PE6006 CAD Drawing Shorting SMA Male Dust Cap

