

RОНП

# Isolated AC/DC Converter **BP5725**


#### Absolute Maximum Ratings

Parameter	Symbol	Limits	Unit	Conditions
7-pin input voltage	VD	800	V	
4-pin input voltage	VG	45	Vpeak	
7-pin input Current	lo	400	mA	
Maximum power	Po	6	W	
Allowable maximum surface temperature	Tcmax	105	°C	Ambient temperature + module self-heating $\leq$ Tcmax
Operating temperature range	Topr	-25 to +80	°C	
Storage temperature range	Tstg	-25 to +105	°C	

#### Electrical Characteristics

<in 12v="" case="" of="" output=""></in>	(Unless	otherwise n	oted, Vi=31	1V, rated loa	d Ta=25°C)	
Parameter	Symbol	Min.	Тур.	Max.	Unit	Conditions
Output detection voltage	Vod	-7.1	-7.6	-8.1	V	lo=500mA
Output current	lo	10	-	500	mA	Refer to derating curve
Line regulation	Vr	-	380	500	mV	Vi=119V to 405VDC Io=500mA
Load regulation	VI	-	90	200	mV	Io=200mA to 500mA
Output ripple voltage	Vp	-	300	500	mVp-p	*1
Power conversion efficiency	η	70	77	-	%	

\*1: Pulse noise is not included.





transformer, and the snubber circuit for noise reduction are connected to this. C1: Input smoothing capacitor 10µF/450V Please verify operation and characteristics in the customer's circuit before actual usage. Ensure that the load current does not exceed C2: Noise reduction capacitor 2200pF/1kV 10µF/50V C3: Vod smoothing capacitor the maximum rating C4: Output smoothing capacitor 1000µF/25V 2200pF/AC250V C5: Noise reduction capacitor C6: Noise reduction capacitor Use if necessary Limiting element voltage DC630V or higher, 0.1 to 0.22µF D1: Rectifier diode FRD 800V/0.5A FRD 200V/1A D2: Rectifier diode 800V/1A D3: Diode bridge R1, R3: Resistor 360kΩ±5% 0.25W R2: Resistor 200kΩ±5% 1W R4: Bleeder resistor In case Io is less than 10mA, connect a bleeder resistor in parallel to C4. T1: Switching transformer FL1: Noise reduction filter Use if necessary FUSE: Fuse Be sure to use this for safety. ZNR: Varistor A varistor is required to protect against lightning surges and static electricity.


#### Usage Precautions

• When the capacitance of the output smoothing electrolytic capacitor C4 is made large the output may not rise. 100 to  $2200\mu F$  is recommended. Set the rise time within 10ms.


- Set the Vod electrolytic capacitor C3 to  $10\mu F$ .
- Be sure to use the VG terminal voltage within the operating voltage range.

• Set the external starting resistor (R1+R3) to 720KΩ. Reducing the resistance value may cause failure during startup.


• A built-in overcurrent protection circuit (reset type) prevents damage due to surge currents. Please discontinue operation if protection circuit is continuously active.



#### Derating Curve




Conversion Efficiency



#### Load Regulation

<In case of 12V output> (Vi=311V, Ta=25°C)



Pin No.

1 Vod

2

3

4

5

6

7

Name

Vod

Vi(-)

VG

Vs

NC

Vn

Function

This is the output detection terminal

This is the output

detection terminal

This is the primary side input minus terminal.

MOSFET, GATE driving input terminal.

This is the start terminal.

This is the NC pin. This is the built-in FET of drain terminal. The primary coil minus side of the exter

Connect this via the externa resistor (720k $\Omega$ ) to Vi (+).

## **Power Module Usage Precautions**

## Safety Precautions

- 1) The products are designed and manufactured for use in ordinary electronic equipment (i.e. AV/OA/ telecommunication/amusement equipment, home appliances). Please consult with the Company's (ROHM) sales staff if intended for use in devices requiring high reliability (e.g. medical/transport/ aircraft/spacecraft equipment, nuclear power/fuel controllers, automotive/safety devices) and whose malfunction may result in injury or death. In this case, failsafe measures must be taken, including the following:
  - [a] Installation of protection circuits in order to improve system safety
  - [b] Incorporation of redundant circuits in the case of single-circuit failure
- 2) The products are designed for use under normal conditions. Application in special environments can cause a deterioration in product performance. Therefore, verification and confirmation of product performance, prior to use, is recommended. The following environments are considered to be 'special':

   [a] Outdoors, exposed to direct sunlight or dust
  - [b] In contact with liquids, such as water, oils, chemicals, or organic solvents
  - [c] In areas where exposure to the sea air or corrosive gases (i.e. Cl<sub>2</sub>, H<sub>2</sub>S, NH<sub>3</sub>, SO<sub>2</sub>, NO<sub>2</sub>) can occur
  - [d] In places where the products may be in contact with static electricity or electromagnetic waves
  - [e] In proximity to heat-producing items, plastic cords, or flammable materials
  - [f] In contact with sealing or coating products, such as resin
  - [g] In contact with unclean solder or exposed to water or water-soluble cleaning agents used after soldering
  - [h] In areas where dew condensation occurs
- 3) The products are not designed to be radiation resistant
- 4) The Company is not responsible for any problems resulting from use of the products under conditions not recommended herein.
- 5) The Company should be notified of any product safety issues. Moreover, product safety issues should be periodically monitored by the customer.

## Application Notes

- 1) A sufficient margin must be allowed if changes are made to the peripheral circuit due to variations in the inherent tolerances of the external components as well as transient and static characteristics. In addition, please be aware that the Company has not conducted investigations on whether or not particular changes in the example application circuits would result in patent infringement.
- 2) The application examples, their constants, and other types of information contained herein are applicable only when the products are used in accordance with standard methods.

Therefore, if mass production is intended, sufficient consideration to external conditions must be made.

## Notes Regarding Industrial Property /

- 1) The specifications included herein contain information related to the Company's industrial property. Their use other than pertaining to the relevant products is forbidden. Duplication and/or disclosure to a third party without express written permission is strictly prohibited.
- 2) Product information and data, including application examples, contained in the specifications are for reference purposes only; the Company does not guarantee the industrial/intellectual property rights or any other rights of a third party. Accordingly, the Company shall not bear responsibility for:
  [a] Infringement of the intellectual property rights of a third party
  [b] Problems arising from the use of the products listed herein
- 3) The Company prohibits the purchaser from exercising or using the intellectual/industrial property rights or any rights belonging to or are controlled by the Company, other than the right to use, sell, or dispose of the products.

## **Power Module Usage Precautions**

## Safety Precautions

- 1) The products are designed and manufactured for use in ordinary electronic equipment (i.e. AV/OA/ telecommunication/amusement equipment, home appliances). Please consult with the Company's (ROHM) sales staff if intended for use in devices requiring high reliability (e.g. medical/transport/ aircraft/spacecraft equipment, nuclear power/fuel controllers, automotive/safety devices) and whose malfunction may result in injury or death. In this case, failsafe measures must be taken, including the following:
  - [a] Installation of protection circuits in order to improve system safety
  - [b] Incorporation of redundant circuits in the case of single-circuit failure
- 2) The products are designed for use under normal conditions. Application in special environments can cause a deterioration in product performance. Therefore, verification and confirmation of product performance, prior to use, is recommended. The following environments are considered to be 'special':

   [a] Outdoors, exposed to direct sunlight or dust
  - [b] In contact with liquids, such as water, oils, chemicals, or organic solvents
  - [c] In areas where exposure to the sea air or corrosive gases (i.e. Cl<sub>2</sub>, H<sub>2</sub>S, NH<sub>3</sub>, SO<sub>2</sub>, NO<sub>2</sub>) can occur
  - [d] In places where the products may be in contact with static electricity or electromagnetic waves
  - [e] In proximity to heat-producing items, plastic cords, or flammable materials
  - [f] In contact with sealing or coating products, such as resin
  - [g] In contact with unclean solder or exposed to water or water-soluble cleaning agents used after soldering
  - [h] In areas where dew condensation occurs
- 3) The products are not designed to be radiation resistant
- 4) The Company is not responsible for any problems resulting from use of the products under conditions not recommended herein.
- 5) The Company should be notified of any product safety issues. Moreover, product safety issues should be periodically monitored by the customer.

## Application Notes

- 1) A sufficient margin must be allowed if changes are made to the peripheral circuit due to variations in the inherent tolerances of the external components as well as transient and static characteristics. In addition, please be aware that the Company has not conducted investigations on whether or not particular changes in the example application circuits would result in patent infringement.
- 2) The application examples, their constants, and other types of information contained herein are applicable only when the products are used in accordance with standard methods.

Therefore, if mass production is intended, sufficient consideration to external conditions must be made.

## Notes Regarding Industrial Property /

- 1) The specifications included herein contain information related to the Company's industrial property. Their use other than pertaining to the relevant products is forbidden. Duplication and/or disclosure to a third party without express written permission is strictly prohibited.
- 2) Product information and data, including application examples, contained in the specifications are for reference purposes only; the Company does not guarantee the industrial/intellectual property rights or any other rights of a third party. Accordingly, the Company shall not bear responsibility for:
  [a] Infringement of the intellectual property rights of a third party
  [b] Problems arising from the use of the products listed herein
- 3) The Company prohibits the purchaser from exercising or using the intellectual/industrial property rights or any rights belonging to or are controlled by the Company, other than the right to use, sell, or dispose of the products.

	copying or reproduction of this document, in part or in whole, is permitted without the nsent of ROHM Co.,Ltd.
The	e content specified herein is subject to change for improvement without notice.
"Pr	e content specified herein is for the purpose of introducing ROHM's products (hereinafte oducts"). If you wish to use any such Product, please be sure to refer to the specifications ich can be obtained from ROHM upon request.
illu	amples of application circuits, circuit constants and any other information contained herein strate the standard usage and operations of the Products. The peripheral conditions mus taken into account when designing circuits for mass production.
Ho	eat care was taken in ensuring the accuracy of the information specified in this document wever, should you incur any damage arising from any inaccuracy or misprint of such prmation, ROHM shall bear no responsibility for such damage.
exa imp oth	e technical information specified herein is intended only to show the typical functions of an amples of application circuits for the Products. ROHM does not grant you, explicitly o plicitly, any license to use or exercise intellectual property or other rights held by ROHM and er parties. ROHM shall bear no responsibility whatsoever for any dispute arising from the e of such technical information.
equ	e Products specified in this document are intended to be used with general-use electronic upment or devices (such as audio visual equipment, office-automation equipment, commu ation devices, electronic appliances and amusement devices).
The	e Products specified in this document are not designed to be radiation tolerant.
	ile ROHM always makes efforts to enhance the quality and reliability of its Products, a oduct may fail or malfunction for a variety of reasons.
aga fail sha	ase be sure to implement in your equipment using the Products safety measures to guard ainst the possibility of physical injury, fire or any other damage caused in the event of the ure of any Product, such as derating, redundancy, fire control and fail-safe designs. ROHM all bear no responsibility whatsoever for your use of any Product outside of the prescribed ope or not in accordance with the instruction manual.
sys ma ins cor of	e Products are not designed or manufactured to be used with any equipment, device o stem which requires an extremely high level of reliability the failure or malfunction of which y result in a direct threat to human life or create a risk of human injury (such as a medica trument, transportation equipment, aerospace machinery, nuclear-reactor controller, fuel- ntroller or other safety device). ROHM shall bear no responsibility in any way for use of any the Products for the above special purposes. If a Product is intended to be used for any ch special purpose, please contact a ROHM sales representative before purchasing.
be	rou intend to export or ship overseas any Product or technology specified herein that may controlled under the Foreign Exchange and the Foreign Trade Law, you will be required to tain a license or permit under the Law.



Thank you for your accessing to ROHM product informations. More detail product informations and catalogs are available, please contact us.

## ROHM Customer Support System

http://www.rohm.com/contact/