



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. RATING: 4A @125VAC, 2A @250VAC
 5. CONTACT RESISTANCE: 10mΩ-1-OHMS
 6. DIELECTRIC STRENGTH: 1500 VAC-1Minute
 7. INSULATION RESISTANCE: 200MΩ-OHMS
 8. MATERIALS:
HOUSING: ZINC ALLOY DIE CAST
CYLINDER: ZINC ALLOY W/CHROME PLATING
TERMINAL AND CONTACTS: SILVER PLATED
KEYS (2) CODE 10001: TUBULAR STEEL, NICKEL PLATED

LEGEND
 ○ = OFF POSITION
 ■ = INDICATES KEY PULL
 X = INDICATES NO KEY PULL

| | | | | |
|------|---------|-------------------------|----------|------|
| REV. | ECN No. | DESCRIPTION | DATE | CHKD |
| A | 11738 | RELEASED FOR PRODUCTION | 10/15/01 | CJB |

| | | | | | | |
|--------------|--|-------|----------|-----|---------|-----|
| TITLE | | SCALE | DATE | DR | DWG | REV |
| K0113B-10001 | | 1.5:1 | 10/15/01 | CJB | K200102 | A |

E-SWITCH®

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED