


PRELIMINARY

High-Reliability Power Inductors ML515PYA



- High temperature materials allow operation in ambient temperatures up to 155°C.
- Passes vibration testing to 80 G and shock testing to 1000 G
- High current and very low DCR
- Soft saturation makes them ideal for VRM/VRD applications.

Core material Composite

Terminations RoHS compliant tin-silver (96.5/3.5) over copper.

Weight 102 – 107 mg

Ambient temperature –55°C to +105°C with Irms current, +105°C to +155°C with derated current

Storage temperature Component: –55°C to +155°C.
Tape and reel packaging: –55°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Enhanced crush-resistant packaging 250 per 7" reel
Plastic tape: 16 mm wide, 0.3 mm thick, 8 mm pocket spacing, 5.21 mm pocket depth

Part number ¹	Inductance ² ±20% (µH)	DCR (mOhML) ³		SRF (MHz) ⁴		Isat (A) ⁵	IrML (A) ⁶	
		typ	max	min	typ		20°C rise	40°C rise
ML515PYA561MLZ	0.56	4.15	4.56	77	96	18.1	10.7	14.3
ML515PYA821MLZ	0.82	5.15	5.66	50	63	14.8	8.9	12.4
ML515PYA122MLZ	1.2	6.16	6.76	43	54	12.9	8.7	11.9
ML515PYA152MLZ	1.5	7.10	7.80	38	48	11.5	8.4	11.6
ML515PYA222MLZ	2.2	9.05	9.95	33	41	9.5	6.8	9.5
ML515PYA332MLZ	3.3	16.90	18.60	27	34	7.4	5.3	7.0
ML515PYA472MLZ	4.7	21.95	24.15	23	29	6.3	4.6	6.2
ML515PYA562MLZ	5.6	23.45	25.80	20	25	5.7	4.0	5.4
ML515PYA682MLZ	6.8	26.75	29.45	17	21	5.4	3.5	4.8
ML515PYA822MLZ	8.2	31.75	34.95	14	18	5.1	3.4	4.6
ML515PYA103MLZ	10	40.90	45.00	12	15	4.6	2.7	3.7
ML515PYA153MLZ	15	69.70	76.70	10	13	3.5	2.2	2.9
ML515PYA223MLZ	22	90.60	99.65	9	11	2.8	1.9	2.6

1. When ordering, please specify **testing** code:

ML515PYA223MLZ

Testing: Z = COTS

H = Screening per Coilcraft CP-SA-10001

N = Screening per Coilcraft CP-SA-10004

2. Inductance tested at 100 kHz, 0.1 Vrms using an Agilent/HP 4192A.

3. DCR measured on a micro-ohmmeter.

4. SRF measured using Agilent/HP 4395A or equivalent.

5. Typical dc current at which the inductance drops 30% from its value without current.

6. Typical current that causes the specified temperature rise from 25°C ambient.

7. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.

Irms Testing

Irms testing was performed on a 0.060" thick pcb with 4 oz. copper traces optimized to minimize additional temperature rise.

Temperature rise is highly dependent on many factors including pcb land pattern, trace size, and proximity to other components. Therefore temperature rise should be verified in application conditions.

Coilcraft CPS
CRITICAL PRODUCTS & SERVICES

1102 Silver Lake Road
Cary, IL 60013
Phone 800-981-0363









Fax 847-639-1508
Email cps@coilcraft.com
www.coilcraft-cps.com

Document ML793-1 Revised 07/20/12

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specifications subject to change without notice. Please check our web site for latest information.

ML515PYA Series (5050)

Typical L vs Current



CRITICAL PRODUCTS & SERVICES

1102 Silver Lake Road
Cary, IL 60013
Phone 800-981-0363






Fax 847-639-1508
Email cps@coilcraft.com
www.coilcraft-cps.com

Document ML793-2 Revised 07/20/12

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specifications subject to change without notice. Please check our web site for latest information.


ML515PYA Series (5050)

Typical L vs Current




ML515PYA Series (5050)


Typical L vs Frequency



Irms Derating



Typical ESR vs Frequency



Dash number	A ±0.008 in ±0.20 mm (in / mm)	B (in / mm)
-561	0.175 / 4.44	0.183 / 4.64
-821	0.175 / 4.44	0.183 / 4.64
-122	0.175 / 4.44	0.183 / 4.64
-152	0.175 / 4.44	0.183 / 4.64
-222	0.175 / 4.44	0.183 / 4.64
-332	0.168 / 4.28	0.173 / 4.40
-472	0.168 / 4.28	0.173 / 4.40
-562	0.168 / 4.28	0.173 / 4.40
-682	0.168 / 4.28	0.173 / 4.40
-822	0.168 / 4.28	0.173 / 4.40
-103	0.167 / 4.24	0.171 / 4.34
-153	0.165 / 4.18	0.167 / 4.25
-223	0.165 / 4.18	0.167 / 4.25

Dimensions are in $\frac{\text{inches}}{\text{mm}}$

Suggested Land Pattern



1102 Silver Lake Road
Cary, IL 60013
Phone 800-981-0363

Fax 847-639-1508
Email cps@coilcraft.com
www.coilcraft-cps.com

Document ML793-4 Revised 07/20/12

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specifications subject to change without notice. Please check our web site for latest information.