

PRELIMINARY SPEC


Features

- BUILT-IN CURRENT LIMITING RESISTOR FOR DIRECT APPLICATION OF DIFFERENT ACROSS CURRENT.
- LONG LIFE.
- LOW CURRENT, POWER SAVINGS.
- LOW MAINTENANCE.
- DIFFERENT COLOR AVAILABLE.
- SOLID STATE, HIGH VIBRATION RESISTANT.
- 12V INTERNAL RESISTOR.
- RoHS COMPLIANT.



Notes:


1. All dimensions are in millimeters (inches).
2. Tolerance is $\pm 0.25(0.01)$ " unless otherwise noted.
3. Specifications are subject to change without notice.







Absolute Maximum Ratings (TA=25°C)		MD-E (InGaAlP)	Unit
Reverse Voltage	V _R	5	V
Forward Voltage	V _F	14	V
Power Dissipation	P _T	280	mW
Operating Temperature	T _A	-40 ~ +70	°C
Storage Temperature	T _{stg}	-40 ~ +85	

Operating Characteristics (TA=25°C)		MD-E (InGaAlP)	Unit
Forward Current (Typ.) (V _F =12V)	I _F	16	mA
Forward Current (Max.) (V _F =12V)	I _F	20	mA
Reverse Current (Max.) (V _R =5V)	I _R	10	uA
Wavelength Of Peak Emission (Typ.) (V _F =12V)	λ P	640	nm
Wavelength Of Dominant Emission (Typ.) (V _F =12V)	λ D	630	nm
Spectral Line Full Width At Half-Maximum (Typ.) (V _F =12V)	Δλ	25	nm

Part Number	Emitting Color	Emitting Material	Lens-color	Luminous Intensity (V=12V) mcd		Wavelength nm λ P	Viewing Angle 2 θ 1/2
				min.	typ.		
XYMDE101W12V	Red	InGaAlP	Water Clear	1500	2490	640	20°







❖ MD-E



PACKING & LABEL SPECIFICATIONS

XYMDE101W12V



P/NO : XYxx101x	
QTY : 100 pcs	CODE: XXX
S/N : XX	
LOT NO:	
 XXXXXXXXXXXXXXXXXXXXXXXX	
RoHS Compliant	