



RECOMMENDED  
CABLE STRIPPING DIM'S

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
  2. BRASS PER QQ-B-613
  3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  4. NICKEL PL. 200 MIN. THICK OVER COPPER STRIKE
  5. NICKEL PL. 100 MIN. THICK OVER COPPER PL. 300 MIN. THICK OVER COPPER STRIKE
  6. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  7. ZINC DIECAST
  8. JIS H 3260, C 3501

1. CRIMPED FERRULE  
HEX CRIMP SIZE .319"

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
10	FERRULE	NOTE 8	NOTE 3	1	FR-91/84-72/65 X172
9	WASHER	NOTE 2	NOTE 3	1	WS-128/9X08
8	SPRING	SK5	NOTE 4	1	B50000-6
7	RETAINER RING	NOTE 1	NOTE 3	1	B50000-5
6	GASKET	RUBBER	RED	1	GS-115/8X15
5	INSULATOR	DELTRIN	NATURAL	1	B5100-5-50
4	CONTACT PIN	NOTE 1	NOTE 6	1	B5020-4-21/076
3	INSULATOR	DELTRIN	NATURAL	1	B5020-3-50
2	BODY	NOTE 1	NOTE 3	1	B5020-2
1	SHELL	NOTE 7	NOTE 5	1	B50000Z-1-RFX

DIMENSIONS ARE IN MILLIMETERS				PART NO.						
UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				B1111L1-001-ND3G-3-50						
				APPROVED	DATE	10-11-01'				
				CHECKED	DATE	10-11-01'				
				DRAWN	DATE	10-11-01'				
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	3/1	ISSUE	A	FILE NO.

<b>Amphenol</b>	
TITLE BNC CRIMP PLUG	
DRAWING NO. KJ-B1111L1-001-ND3G-59U-50	
ITEM NO.	