3 mm Square SMT Trimmer Potentiometers with the rotation stopper (Cermet, Open Frame Type)



## Type: **EVM3V**


#### ■ Features

- Rotation stopper featured type
- Automatic adjustment type
- High reliability realized by cermet element
- Excellent mountability
- Conforms to JIS C5260-1:1999
- RoHS compliant


### ■ Recommended Applications

- Audio/visual, office, and communication equipment
- General electronic equipment

## ■ Explanation of Part Numbers









Taper & Resistance Example : B52=500  $\Omega$ 

# ■ Specifications

Total Resistance Value Resistance Tolerance	100 Ω to 1 MΩ ±25 %
Power Rating Limiting Element Voltage	0.15 W 50 V
Rotation Torque	2 to 10 mN·m
Stopper Strength	15 mN·m min.
Temperature Coefficient of Resistance	±250 × 10 <sup>-6</sup> /°C

### ■ Minimum Quantity/Packing Unit

Doub Number	Taping		
Part Number	Quantity per reel	Packaging quantity	Dia. of reel (mm)
EVM3V	2000	10000	φ178

The standard packaging methods for a reel is  $\phi$ 178.

Please contact us, if you would like different packaging methods. (Bulk, Reel of \$\phi 330\$, Reel of \$\phi 380\$)

## ■ Dimensions in mm (not to scale)

### • 3-terminal, for Automatic Trimming Adjustment

