



SPECIFICATIONS:

- MATERIAL:-
 HOUSING: PA6T
 TERMINAL 1: COPPER ALLOY
 TERMINAL 2: COPPER ALLOY
 TERMINAL 3: COPPER ALLOY
 TERMINAL 10: BRASS
 ELECTRICAL:-
 VOLTAGE PROOF: 500V RMS FOR ONE MINUTE
 CONTACT RESISTANCE: 30 mΩ
 INSULATION RESISTANCE: 50 MΩ MIN. AT 500V
 MECHANICAL:-
 DURABILITY: 5000 CYCLES

RECOMMENDED SOLDER PAD LAYOUT

MODEL NO	M706-50 0 0445	M706-50 1 0445	M706-50 2 0445
SCHEMATIC			

NAME	ISS.	DATE	C/NOTE
Allan	2	31.03.08	A119
Allan	1	01.08.06	-
APPROVED: _____			
CHECKED: <i>Ben</i>			
DRAWN: Allan			
CUSTOMER REF.:			
ASSEMBLY DRG:			

TOLERANCES
 X.X = ±0.20mm
 X.XX = ±0.10mm
 X.XXX = ±0.05mm

NOTES: ALL DIMENSIONS AND NOTES MARKED * ARE CRITICAL AND MUST BE CHECKED IN ACCORDANCE WITH QUALITY DOC. Q1-02A



HARWIN USA
 TEL: 603 893 5376
 FAX: 603 893 5396
 mis@harwin.com

HARWIN Europe (UK)
 TEL: 023 9231 4545
 FAX: 023 9231 4590
 mis@harwin.co.uk

HARWIN Asia
 TEL: +65 6 779 4909
 FAX: +65 6 779 3868
 mis@harwin.com.sg

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
 X. = ±1mm
 X.X = ±0.25mm
 X.XX = ±0.10mm
 X.XXX = ±0.01mm
 ANGLES = ±5°
 UNLESS STATED

MATERIAL: SEE NOTES
 FINISH: SEE NOTES
 S/AREA: mm²

TITLE: 3.5mm SMD AUDIO JACK
 DRAWING NUMBER: M706-50 X 0445