



Relay Type:

Contact Form: 1C

Sealing Type: NIL-Open
S: Sealed
Coil Voltage:- 5 ~ 24VDC

Features	Dimension L * W * H (mm)	32.5 * 27.5 * 26			
	Terminal Type	PCB			
	Weight	32 gm Approximately			
Contact Data	Contact Form	1A, 1C			
	Contact Material	Ag Alloy			
	Contact Capacity	NO: 30A @ 240VAC, NC: 20A @ 240VAC , 30A @ 28VDC			
Coil Data	Coil Voltage ( DC)	5 ~ 24 VDC			
	Coil Power Consumption	0.93W			
		Coil Voltage	Coil Resistance ( $\Omega$ ) $\pm 10\%$	Pull in Voltage (VDC)	Drop Out Voltage (VDC)
	Coil Specification	12 VDC	155	80%	5%
		24 VDC	660	80%	5%
General Data	Dielectric Strength	1500 VAC @ 50 Hz / Min (Between Open Contacts)			
		2500 VAC @ 50 Hz / Min ( Between Coil & Contacts)			
	Insulation Resistance	500ΜΩ			
	Electrical Life	1 x 10 <sup>5</sup>			
	Mechanical Life	$1 \times 10^7$			
	Operating Temperature	- 55°C ∼	+ 85°C		
	3-62.1 2-61.2				

Mounting Diagram



**Application** HVAC, Domestic Applications, Car Control Switching Box etc