Fuse Panels- RTMF, 15600, Relay Module

| COOPER | | | News Events C | 3 Sign-In Employees Contact Us 😭 🛓 | |
|--|---|---|----------------------------|---|--|
| | COOPER BUSSMANN 🕨 🔽 | CONSUMER 🔻 | | | |
| ABOUT US PRODUCTS | SOLUTIONS MARKETS | BRANDS RESOURCES | | | |
| Products | | | | | |
| SEARCH Q | Cooper Industries > Cooper Fuse Panels - ATC, ATM, F | | pmotive Electrical Afterma | rket > Fuse Holders, Panel, Blocks & Taps > | |
| Advanced Search | ectrical | | | | |
| Automotive Electrical Aftermarket Residential Circuit Protection | | | | | |
| | RTMF Fuse Panel | - ATM Footprint | 15600 Fuse Panel | s - ATC Footprint | |
| Recently Viewed Items | | The Rear Terminal 20 Position ATM Fuse Panel provides efficient power distribution in a rugged compact package. The RTMF offers a weather tight enclosure (IP66/67) for ATM blade fuses and circuit breakers when cover, cable seals, and cavity plugs are installed.* | | A single, common power input makes it simple to wire for multiple circuits - each rated to 30 amps, up to 32 volts. Molded of high grade thermoplastic, for superior performance. Quick-connect terminals for easy installation. Recessed fuse contacts provide fingersafe protection. | |
| | | | Fuses and circuit breal | kers sold separately. | |

| Part No. | Description |
|----------|---|
| RTMF | 20 position fuse block |
| RTMF-SC | 20 position fuse block with shallow cover |
| RTMF-DC | 20 position fuse block with deep cover |

* Electrical terminals, cable seals and cavity plugs are either Delphi Packard Metri-Pack® 280 Series terminals (sealed/tangless) or AMP® terminals. They accept #12-22 AWG wire sizes. Delphi Packard 280 Series cavity plugs are installed where wires are not used. Seals and cavity plugs not sold by Cooper Bussmann.

Power Distribution Relay Module



The sealed Power Relay Module (CBPRM) and Power Fuse Module (CBPFM) are compact power distribution modules for high current applications having extreme moisture and high vibration. The 24 volt CBPRM contains a 35A relay and two FMX fuse positions (one protects the relay and the other a single-circuit in-line fuse). The CBPFM

has two FMX fuse positions for separate circuits. Both the CBPRM and CBPFM feature rugged M8 power input studs, and an IP66 removable, weather-tight cover to protect the fuse positions. Electrical terminations not supplied by Cooper Bussmann.

| Part No. | Description |
|----------|--------------------|
| | Power Fuse Module |
| CBPRM | Power Relay Module |

Company

Divisions

Products

Resources

Investors

Short Base

Part No.

15600-04-20

15600-06-20

15600-08-20

15600-10-20

15600-12-20

15600-14-20

15600-16-20

15600-18-20

15600-20-20

Fuse Positions

4

6

8

10

12

14

16

18

20

Blister

Pack

Х*

Tri-Lingual

Blister

Х*

Long Base

Part No.

15600-04-21

15600-06-21

15600-08-21

15600-10-21

15600-12-21

15600-14-21

15600-16-21

15600-18-21

15600-20-21

Careers Environmental Policy Corporate Giving Sustainability Safety & Health Strategic Sourcing Memorandum of Insurance Cooper B-Line Cooper Bussmann Cooper Crouse-Hinds Cooper Lighting Cooper Power Systems Cooper Safety Cooper Wiring Solutions Markets Brands Library Cross Reference Education Programs and Portals Where to Buy Cooper Technology Center

Investor News Event Calendars Terms of Use Contact Us Site Map

