

**BD644 – 646 – 648 – 650 – 652**
**SILICON DARLINGTON POWER TRANSISTORS**

PNP epitaxial-base transistors in a monolithic Darlington circuit and housed in a TO-220 envelope. They are intended for output stages in audio equipment, general amplifiers, and analogue switching application.

NPN complements are BD643, BD645, BD647, BD649 and BD651

Compliance to RoHS.

**ABSOLUTE MAXIMUM RATINGS**

Symbol	Ratings	Value	Unit	
$-V_{CBO}$	Collector-Base Voltage	BD644	45	V
		BD646	60	
		BD648	80	
		BD650	100	
		BD652	120	
$-V_{CEO}$	Collector-Emitter Voltage	BD644	45	V
		BD646	60	
		BD648	80	
		BD650	100	
		BD652	120	
$-V_{EBO}$	Emitter-Base Voltage	BD644	5	V
		BD646		
		BD648		
		BD650		
		BD652		
$-I_C$	Collector Current	BD644	8	A
		BD646		
		BD648		
		BD650		
		BD652		
$-I_{CM}$	Collector Peak Current	BD644	12	A
		BD646		
		BD648		
		BD650		
		BD652		

## BD644 – 646 – 648 – 650 – 652

### ABSOLUTE MAXIMUM RATINGS

Symbol	Ratings		Value	Unit	
$-I_B$	Base Current	BD644	150	mA	
		BD646			
		BD648			
		BD650			
		BD652			
$P_T$	Power Dissipation	@ $T_{mb} < 25^\circ$	BD644	62.5	Watts
			BD646		
			BD648		
			BD650		
			BD652		
$T_J$	Junction <i>Temperature</i>	BD644	150	°C	
		BD646			
		BD648			
		BD650			
		BD652			
$T_s$	Storage <i>Temperature range</i>	BD644	-65 to +150		
		BD646			
		BD648			
		BD650			
		BD652			

Limiting values in accordance with the Absolute Maximum System (IEC 134)

### THERMAL CHARACTERISTICS

Symbol	Ratings	Value	Unit
$R_{thJ-MB}$	From junction to mounting base	2	K/W
$R_{thJ-A}$	From junction to ambient in free air	70	K/W

**BD644 – 646 – 648 – 650 – 652**
**ELECTRICAL CHARACTERISTICS**

TC=25°C unless otherwise noted

Symbol	Ratings	Test Condition(s)	Min	Typ	Max	Unit	
$-I_{CBO}$	Collector Cutoff Current	$-I_E=0, -V_{CB} = -V_{CEO}MAX$	BD644	-	-	0.1	mA
			BD646				
			BD648				
			BD650				
			BD652				
		$-I_E=0, -V_{CB} = 1/2 - V_{CBO}MAX, T_J=150^\circ C$	BD644	-	-	1	mA
			BD646				
			BD648				
			BD650				
			BD652				
$-I_{CEO}$	Collector Cutoff Current	$-I_E=0, -V_{CE} = 1/2 - V_{CEO}MAX$	BD644	-	-	0.2	mA
			BD646				
			BD648				
			BD650				
			BD652				
$-I_{EBO}$	Emitter Cutoff Current	$-V_{EB}=5 V, -I_C=0$	BD644	-	-	5.0	mA
			BD646				
			BD648				
			BD650				
			BD652				
$-V_{CE(SAT)}$	Collector-Emitter saturation Voltage (*)	$-I_C=4 A, -I_B=16 mA$	BD644	-	-	2	V
			BD646				
		$-I_C=3 A, -I_B=12 mA$	BD648	-	-	2	
			BD650				
			BD652				
		$-I_C=5 A, -I_B=50 mA$	BD644	-	-	2.5	
			BD646				
			BD648				
			BD650				
		BD652					
$-V_{BE(SAT)}$	Base-Emitter Saturation Voltage (*)	$-I_C=12 A, -I_B=50 mA$	BD644	-	-	3	V
			BD646				
			BD648				
			BD650				
			BD652				

## BD644 – 646 – 648 – 650 – 652

### ELECTRICAL CHARACTERISTICS

TC=25°C unless otherwise noted


Symbol	Ratings		Min	Typ	Max	Unit	
$-V_{BE}$	Base-Emitter Voltage (*)	$-I_C=4\text{ A}, -V_{CE}=3\text{ V}$	BD644	-	-	2.5	V
		$-I_C=3\text{ A}, -V_{CE}=3\text{ V}$	BD646	-	-	2.5	
			BD648				
			BD650				
			BD652				
$h_{FE}$	DC Current Gain (*)	$-V_{CE}=3.0\text{ V}$ $-I_C=0.5\text{ A}$	BD644	-	2700	-	
			BD646				
			BD648				
			BD650				
			BD652				
		$-V_{CE}=3.0\text{ V}, -I_C=4\text{ A}$	BD644	750	-	-	
			BD646	750	-	-	
			BD648				
			BD650				
		BD652					
		$-V_{CE}=3.0\text{ V}, -I_C=8\text{ A}$	BD644	-	200	-	
			BD646				
BD648							
BD650							
$h_{fe}$	Small Signal Current Gain	$-V_{CE}=3.0\text{ V}, -I_C=4\text{ A}$ $f=1\text{ MHz}$	BD644	10	-	-	
			BD646	10	-	-	
		BD648					
		BD650					
		BD652					
$t_{on}$	turn-on time	$-I_C=3\text{ A}$	All types	-	1	-	$\mu\text{s}$
				$-I_{Bon}=I_{Boff}=12\text{ mA}$	-	5	
$t_{off}$	turn-off time						

(\*) Pulse Width  $\approx 300\ \mu\text{s}$ , Duty Cycle  $\angle 2.0\%$

## BD644 – 646 – 648 – 650 – 652

### MECHANICAL DATA CASE TO-220

DIMENSIONS (mm)		
	Min.	Max.
A	9,90	10,30
B	15,65	15,90
C	13,20	13,40
D	6,45	6,65
E	4,30	4,50
F	2,70	3,15
G	2,60	3,00
H	15,75	17,15
L	1,15	1,40
M	3,50	3,70
N	-	1,37
P	0,46	0,55
R	2,50	2,70
S	4,98	5,08
T	2,49	2,54
U	0,70	0,90



Pin 1 :	Base
Pin 2 :	Collector
Pin 3 :	Emitter
Package	Collector

Revised September 2012

Information furnished is believed to be accurate and reliable. However, Comset Semiconductors assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Data are subject to change without notice. Comset Semiconductors makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Comset Semiconductors assume any liability arising out of the application or use of any product and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Comset Semiconductors' products are not authorized for use as critical components in life support devices or systems.