


MN18801A

■ Features

- Addressing capability: Program area 64 KB
(2MB when MMU is used)
Data area 64 KB
(2 MB when MMU is used)
- Interrupt: External interrupt 3
Timer interrupt 3
Serial interrupt2(send/receive)
A/D interrupt 1
Abnormal run detect interrupt 1
Extension interrupt
Timer 9
DMA 1
Strobe output 1
Handshake 1
Chattering prevention 1
Sync.serial interface 1
- Timer/counter: 16-bit programmable timer × 12
Timer function
Event count function
Baud rate generator
Clock function
Timer sync.output function
PWM function
Input capture function
Strobe output function
Watchdog function
- Serial interface: 8-bit sync.type
1 channel
7-/8-bit start-stop sync.type
1 channel
- Analog interface: 8-bit A/D converter
4 channels
- Standby mode: STOP/HALT mode
- Handshake interface: For CENTRONIX printer
- Chattering preventive input
- DMA controller: Transfer between 1-channel
RAM and I/O

- MMU incorporated for large-capacity memory interface
- Zero cross detect input: × 2
- I/O pins: Memory mapped I/O system
16 for per-bit direction control I/O port
24 for per-byte direction control I/O port
13 for input port(various functions combined)
6 for output port(various functions combined)
21 for address bus
8 for data bus
- Package: 100-QFP

■ Pin Configuration



■ Pin Descriptions

Symbol	Pin Name	I/O	Description
V _{DD}	Power supply	—	Connect to +5V.
V _{SS}	Power supply	—	Connect to 0 V (GND).
OSC1	Oscillation input	I	High-speed system clock oscillation input pin
OSC2	Oscillation output	O	High-speed system clock oscillation output pin
XI	Oscillation input	I	Low-speed system clock oscillation input pin. Input pin when oscillations stop.
XO	Oscillation output	O	Low-speed system clock oscillation output pin. Input pin when oscillations stop.
RST	Reset	I	Pin to reset the microcomputer
TXD (P00)	UART data send	O (I)	Pin to output start/stop sync. serial interface(UART) serial data. Also available as an input port.
RXD (P01)	UART data receive	I	Start/stop sync. serial interface(UART) serial data input pin. Also available as an input port.
SBT	Sync. serial clock I/O	I/O	Pin to input/output sync. serial interface clock. Also available as an input port.
SBD	Sync. serial data I/O	I/O (I)	Pin to input/output sync. serial interface data. Also available as an input port.
TC/TCIO0	Combined	I/O	Timer/event counter I/O pin. Also available as DMA end output and input port.
DMAACK/ TCIO1	Combined	I/O	Timer/event counter I/O pin. Also available as a DMA ACK output and input port.
ACK/PWM12 /TCIO2	Combined	I/O	Timer/event counter I/O pin. Also available as an ACK input pin, PWM output pin, and as an input port.
SO8/PWM13/ TCIO3	Combined	I/O	Timer/event counter I/O pin. Also available as a strobe data output or PWM output pin, and as an input port.
STR1/PWM4/ TCIO4	Combined	I/O	Timer/event counter I/O pin. Also available as a strobe data latch pulse output or PWM output pin, and as an input port.
POW1/PWM5/ TCIO5	Combined	I/O	Timer/event counter I/O pin. Also available as a power control output or PWM output pin, and as an input port.
STR2/PWM6/ TCIO6	Combined	I/O	Timer/event counter I/O pin. Also available as a strobe data latch pulse output or PWM output pin, and as an input port.
POW2/PWM7/ TCIO7	Combined	I/O	Timer/event counter I/O pin. Also available as a power control output or PWM output pin, and as an input port.
IRQ0/Z0 IRQ1/Z1	External interrupt input	I	External interrupt input pin. Also available as a zero cross input pin or input port.

■ Pin Descriptions(Continued)

Symbol	Pin	I/O	Description
IRQ2/ $\overline{RST2}$	External interrupt input	I	External interrupt input pin. Also available as an extension reset input pin or input port.
V_{ref+}	Ref. power supply	—	"+" side of the reference power supply for the AD/DA converter
V_{ref-}	Ref. power supply	—	"-" side of the reference power supply for the AD/DA converter
S/H	Sample/hold capacitor	—	Sampling/holding capacitor connection pin for the AD converter
ADC0/SW4~ ADC3/SW7	AD input	I	AD converted value input pins. Also available as chattering preventive input pins or pulse detect input pins. Also available as input ports.
E	E pulse output	O	Output pin for an enable pulse which indicates a validity time of the data bus, \overline{RE} , and \overline{WE} .
\overline{WE}	Write enable	O	RAM write control signal output pin
\overline{RE}	Read enable	O	RAM read control signal output pin
\overline{PSEN}	Program select	O	ROM read control signal output pin
SO0~SO7	Strobe output	O	Strobe data output pins. Also available as output ports.
HS0~HS7	Handshake I/O	I/O	CENTRONIX interface data I/O pins for the printer. Also available as I/O ports.
BUSY/SW0/ ICR4	Combined	I/O	CENTRONIX interface Busy signal input pin for the printer. Also available as a chattering preventive input, pulse detect input or input-capture input pin, and as an input port.
STB/SW1/ ICR5	Combined	I/O	CENTRONIX interface strobe signal output pin for the printer. Also available as a chattering preventive input or pulse detect input or input-capture input pin, and as an input port.
SW2/ICR6/ DMAREQ	Combined	I	DMA request signal input. Also available as a chattering preventive input, pulse detect input or input-capture input pin, and as an input port.
SW3/ICR7	Combined	I	Chattering preventive input, pulse detect input or input capture input pin. Also available as an input port.
TO0~TO3	Timer sync. output	O	Sync. output ports for the timer 11. Also available as general purpose output ports.
TO4~TO7	Timer sync. output	O	Sync. output ports for the timer 12. Also available as general purpose output ports.
P10~P17	I/O	I/O	General purpose I/O pins. Input/output is specified for each bit.
AB0~AB20	Address bus	O	Address output pins for ROM, RAM, I/O
DB0~DB7	Data bus	I/O	Data I/O pins for ROM, RAM, I/O

Request for your special attention and precautions in using the technical information and semiconductors described in this book

- (1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.
- (2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products. No license is granted in and to any intellectual property right or other right owned by Panasonic Corporation or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information described in this book.
- (3) The products described in this book are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
 - Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
 - Any applications other than the standard applications intended.
- (4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
 - Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.
- (7) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of our company.