



ON Semiconductor®

www.onsemi.com

NDDP010N25AZ

Power MOSFET 250V, 10A, 420mΩ, N-Channel

Features

- High Speed Switching
- ESD Diode-Protected Gate
- Pb-Free, Halogen Free and RoHS Compliance
- Low Gate Charge
- 100% Avalanche Tested

Specifications

Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Value	Unit
Drain to Source Voltage	V_{DSS}	250	V
Gate to Source Voltage	V_{GSS}	± 30	V
Drain Current (DC)	I_D	10	A
Drain Current (Pulse) $PW \leq 10\mu\text{s}$, duty cycle $\leq 1\%$	I_{DP}	40	A
Power Dissipation $T_c = 25^\circ\text{C}$	P_D	1 52	W
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature	T_{stg}	-55 to +150	$^\circ\text{C}$
Source Current (Body Diode)	I_S	10	A
Avalanche Energy (Single Pulse) *1	E_{AS}	15.5	mJ
Lead Temperature for Soldering Purposes, 3mm from Case for 10 Seconds	T_L	260	$^\circ\text{C}$

Thermal Resistance Ratings

Parameter	Symbol	Value	Unit
Junction to Case Steady State	$R_{\theta JC}$	2.40	$^\circ\text{C/W}$
Junction to Ambient *2	$R_{\theta JA}$	125	

Note : *1 $V_{DD} = 50\text{V}$, $L = 1\text{mH}$, $I_{AV} = 5\text{A}$ (Fig.1)


*2 Insertion mounted

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


Ordering & Package Information

Device	Package	Shipping	Memo
NDDP010N25AZT4H	DPAK(TP-FA), SC-63, TO-252	700pcs. / reel	Pb-Free and Halogen Free
NDDP010N25AZ-1H	IPAK(TP), SC-64, TO-251	500pcs. / bag	



Electrical Connection




Packing Type: TL



Marking



DPAK



IPAK

NDDP010N25AZ

Electrical Characteristics at Ta = 25°C

Parameter	Symbol	Conditions	Value			Unit	
			min	typ	max		
Drain to Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D=1mA, V_{GS}=0V$	250			V	
Zero-Gate Voltage Drain Current	I_{DSS}	$V_{DS}=250V, V_{GS}=0V$			1	μA	
Gate to Source Leakage Current	I_{GSS}	$V_{GS}=\pm 24V, V_{DS}=0V$			± 10	μA	
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=10V, I_D=1mA$	2.5		4.5	V	
Forward Transconductance	g_{FS}	$V_{DS}=10V, I_D=5A$		6.5		S	
Static Drain to Source On-State Resistance	$R_{DS(on)}$	$I_D=5A, V_{GS}=10V$		320	420	$m\Omega$	
Input Capacitance	C_{iss}	$V_{DS}=20V, f=1MHz$		980		pF	
Output Capacitance	C_{oss}				80		pF
Reverse Transfer Capacitance	C_{rss}				25		pF
Turn-ON Delay Time	$t_{d(on)}$	See Fig.2		18		ns	
Rise Time	t_r			26		ns	
Turn-OFF Delay Time	$t_{d(off)}$			44		ns	
Fall Time	t_f			31		ns	
Total Gate Charge	Q_g	$V_{DS}=125V, V_{GS}=10V, I_D=10A$		16		nC	
Gate to Source Charge	Q_{gs}			4.7		nC	
Gate to Drain "Miller" Charge	Q_{gd}			4.6		nC	
Forward Diode Voltage	V_{SD}	$I_S=10A, V_{GS}=0V$		0.96	1.2	V	
Reverse Recovery Time	t_{rr}	See Fig.3		130		ns	
Reverse Recovery Charge	Q_{rr}	$I_S=10A, V_{GS}=0V, di/dt=100A/\mu s$		540		nC	

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Fig.1 Unclamped Inductive Switching Test Circuit




Fig.2 Switching Time Test Circuit



















Fig.3 Reverse Recovery Time Test Circuit



NDDP010N25AZ



NDDP010N25AZ




Package Dimensions

NDDP010N25AZT4H

DPAK / TP-FA

unit : mm


- 1:Gate
- 2:Drain
- 3:Source
- 4:Drain



Pin 2 is idle pin with electrical designation only carried.

*1:Lot indication

Recommended Soldering Footprint




Package Dimensions

NDDP010N25AZ-1H

IPAK / TP

unit : mm

- 1:Gate
- 2:Drain
- 3:Source
- 4:Drain



Note on usage : Since the NDDP010N25AZ is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.