GOT3157W-832-PCT

15.6" WXGA TFT Fanless Multi-Touch Panel Computer with Intel® Atom™ Processor D2550 (-10°C ~ +50°C)





- Power switch
 Terminal block for DC porwer input
- 2. Terminal block for D 3. USB 2.0 x 2
- 3. USB 2.0 x 2 4. COM 1 (RS-232)
- 221
- 5. COM 2 (RS-232/422/485)
- 6. Ethernet x 2
- 8. Audio(Line-out) 9. CF slot 10. Backlight switch 11. Brightness adjustment

7. USB 2.0 x 2



Introduction

The G0T3157W-832-PCT adopts a 15.6-inch WXGA LCD and supports Intel® Atom™, processor D2550 1.86 GHz Bay Trail SoC. By supporting a wide range operating temperature from -10°C to +50°C, it can be used in harsh environment. The 15.6″ fanless human machine interface also provides one PCIe mini card slot for wireless network connectivity. The rugged fanless touch panel computer is suitable for transportation, heavy-duty industry, smart factory automation, and oil pipe monitoring systems.

Wide Temperature Range Support (-10°C to +50°C)

The Intel® AtomTM-based touch panel PC, GOT3157W-832-PCT, applies unique extended temperature technology with wide temperature range support as we as fanless operation. It also has a compact design for harsh environment.


WALN Antenna Support (optional)

The 15.6" WXGA IP65 industrial panel PC, GOT3157W-832-PCT, provides one PCIe mini card slot and WLAN antennas for wireless network connectivity.

Features

- 15.6" WXGA wide screen with modulized design
- Multi-Touch 15.6" projected capacitive
- Supports 2.5" SATA HDD & CompactFlash™ type II
- Supports WLAN module & antenna (optional)
- Supports 2 Gigabit LAN, 4 USB 2.0 & 2 COM ports
- IP65 front bezel
- Supports panel mount and optional VESA arm/desktop stand/ wall mount
- Supports wide temperature range of -10°C ~ +50°C





Specifications

Front Bezel	IP65 front bezel	
LCD Panel	Display Type	15.6" WXGA TFF LCD
	Brightness (cd/m ²)	400 nits
	Resolution	1366 x 768
Main System	CPU	Intel® Atom™ processor D2550 2C @1.86 GHz
	Chipset	Intel® NM10
	System Memory	1 x 204-pin DDR3-800/1066 SO-DIMM max. up to 4 GB
	BIOS	AMI UEFI BIOS
	Storage	1 x 2.5" SATA HDD 1 x CompactFlash™
	Watchdog Timer	255 levels, 0~255 sec.
	Onboard Graphics	Integrated Intel® GFX

Specifications

I/O Connector	1 x RS-232 (COM 1)	
	1 x RS-232/422/485 (COM 2)	
	1 x Switch for power on/off (ATX)	
	1 x Audio (Line-out)	
	4 x USB 2.0	
	2 x 10/100/1000Mbps Ethernet	
Expansion Interface	1 x PCle Mini Card slot	
Touchscreen	Projected capacitive multi-touch	
Power Supply	10-30VDC	
Dimensions	396 mm (15.6") (W) x 53.9 mm (2.12") (D)	
	x 247.1 mm (9.73") (H)	
Packing Dimensions	525 mm (20.67") (W) x 186 mm (7.32") (D) x 470 mm (18.51") (H)	
Weight (net/gross)	5.0 kg (11.02 lb)/7.0 kg (15.43 lb)	
Environment	Operating temperature: -10°C ~ +50°C (+14°F ~ +122°F)	
	Storage Temperature: -20°C ~ +60°C (-4°F ~ +140°F)	
	Relative humidity: 20% ~ 90% @ 40°C; non-condensing	
	Operation vibration:	
	2G, 10 ~ 500Hz, random for CompactFlash™	
Certificate	CE	

Ordering Information

GOT3157W-832-PCT-DC	15.6" WXGA TFT fanless touch panel computer with Intel®
	Atom™ D2550 1.86 GHz dual core processor, projected
	capacitive multi-touch screen and 10~30VDC terminal block
	connector

Optional EOS Installation

WES (single-touch function)	
WES 7E (32-bit, single-touch function)	
WES 7P (32-bit, multi-touch function)	

Optional OS Installation

Windows® XP (single-touch function) Windows® 7 (32-bit, multi-touch function)



▲ Ideal for factory automation & self-service kiosk in retail





Touch Panel Computers

2 Heavy-duty Fanless Touch Panel Computers



Industrial Touch Panel Computers



Industrial Touch panel Monitors



0

Healthcare & Medical Solutions

Open Frame Panel



Accessories

Dimensions

