

MATERIALS

CONNECTOR	BRASS NICKEL PLATED
CONTACT	GOLD PLATED
INSULATOR	PTFE
HEAT SINK	ANODIZED ALUMINUM



HEAT SINK

LENGTH = 12.000"
 HEIGHT = 6.875"
 WIDTH = 6.000"

SPECIFICATIONS

FREQUENCY RANGE: DC TO 500 MHz
 ATTENUATION: 3 dB
 IMPEDANCE: 50 OHMS
 ACCURACY: ±.5 dB
 VSWR: 1.15:1 MAXIMUM
 RF INPUT POWER: 500 WATT AVERAGE AT 25°C
 DERATED TO 250 WATTS AT 100°C



PASTERNACK ENTERPRISES, INC.
 P.O BOX 16759, IRVINE, CA 92623
 PHONE (949) 261-1920 FAX (949) 261-7451
 WEB ADDRESS: www.pasternack.com
 E-MAIL ADDRESS: sales@pasternack.com
COAXIAL & FIBER OPTICS

DWG TITLE		DES.			
PE7032-3		N ATTENUATOR MALE TO FEMALE 500 WATT, FREQUENCY RANGE: DC TO 500 MHz			
SIZE A	FSCM NO. 53919	CAD FILE	072902	SCALE	N/A
					127

- NOTES:
- UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 - ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.