

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

10A01GP THRU 10A07GP

Features

- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- High Current Capability and Low Forward Voltage Drop
- Surge Overload Rating to 200A Peak
- Low Reverse Leakage Current and Galss Passivared Junction
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Halogen free available upon request by adding suffix "-HF"

Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C


MCC	Device	Maximum	Maximum	Maximum
Catalog	Marking	Reccurrent	RMS	DC
Number		Peak Reverse	Voltage	Blocking
		Voltage		Voltage
10A01GP	10A01GP	50V	35V	50V
10A02GP	10A02GP	100V	70V	100V
10A03GP	10A03GP	200V	140V	200V
10A04GP	10A04GP	400V	280V	400V
10A05GP	10A05GP	600V	420V	600V
10A06GP	10A06GP	800V	560V	800V
10A07GP	10A07GP	1000V	700V	1000V

Bectrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	10 A	$T_A = 50^{\circ}C$
Peak Forward Surge Current	I _{FSM}	200A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	V _F	1.2V	I _{FM} = 10A; T _A = 25°C
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	10μΑ 100μΑ	T _A = 25°C T _A = 100°C
Typical Junction Capacitance	CJ	150pF	Measured at 1.0MHz, V _R =4.0V
Typical Thermal Resistance Junction to Ambien	R _{thJA}	10K/W	

Notes:1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

10 Amp Glass Passivated Rectifier 50 to 1000 Volts





DIMENSIONS						
	INCHES		ММ			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	.340	.360	8.60	9.10		
В	.340	.360	8.60	9.10		
С	.048	.052	1.20	1.30		
D	1.000		25.40			

10A01GP thru 10A07GP





Micro Commercial Components





NUMBER OF CYCLES AT 60 Hz Fig. 3 Maximum Non-Repetitive Peak Forward Surge Current







Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 500pcs/Reel
Part Number-AP	Ammo Packing: 450pcs/Ammo Box
Part Number-BP	Bulk: 4.8Kpcs/Carton

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.