





Rev	AWO #	Description	Date	Appr
-		RELEASED	12/29/04	

APPROVED: \_\_\_\_\_ TITLE: \_\_\_\_\_  
 DATE: \_\_\_\_\_



**SPECIFICATIONS:**

Material: Insulator: Hi-Temp Nylon, rated UL 94V-0  
 Insulator color: Black  
 Contacts: Brass  
 Plating: Tin over Copper underplate overall  
 Electrical: Operating voltage: 250 VAC max.  
 Current rating: 1 Amp max.  
 Contact resistance: 20 mohms max. initial  
 Insulation resistance: 5,000 Mohms min. @ 500 VDC  
 Dielectric withstanding voltage: 1,000 VAC for 1 minute  
 Temperature Rating: Operating temperature: -40°C to +105°C

Positions: 8, 10, 14, 16, 20, 24, 26, 30, 34, 40, 44, 50, 60, 64  
 A = .079 [2.00] x No. of Spaces + .362 [9.20]  
 B = .079 [2.00] x No. of Spaces

**ADAM TECH**

909 Rahway Avenue, Union, NJ 07083  
 Phone: 908-687-5000 Fax: 908-687-5710

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED		TITLE	
X ± .10	ØX ± .10	.079 [2.00] BOX HEADER, STRAIGHT, TIN PLATED, SURFACE MOUNT	
.XX ± .020	ØXX ± .015	SIZE	PART NO.
.XXX ± .015	ØXXX ± .010	X	2BHR-XX-VT-SMT
APPROVALS	DATE	SCALE:	NTS
DRAWN SS	12/29/04	SHEET	1 OF 1
CHECKED		REV.	
APPROVED			